RAIN RATE ESTEIMATION IN SUMMER OF TAIWAN Thwong Zong Yang Central Weather Bureau

ABSTRACT

Mr. Zhao has derived an algorithm (Zhao, L. and Weng, F. ,2002) to estimate rain rate over both land and ocean, in this presentation we only discuss rain rate over land. We use AMSUA ch1,ch2 and AMSUB ch1,ch2,ch3 to estimate rain rate , the accuracy about diagnose rain-area is 83%, its mean value is 87%, the rms error of rain rate is about 3.6mm/hr.

METHOD AND DATA

(Weng and Grody, 2000) derived a formula

$$T_{B}(Zt,\mu) = \frac{T_{B}(Z_{b},\mu)}{1+\Omega(\mu)}$$

Where TB(Zt,µ), the upwelling brightness

Temperature at the cloud top, is a direct measurement from satellites. TB(Zb,µ), the upwelling brightness temperature at the cloud base, is derived from an empirical formula. μ is cosine of zenith angle, Ω is scattering parameter, so then we can derive cloud ice water path

IWP =
$$\mu$$
 De ρ_i (Ω / Ω_N)

ρi is ice particle bulk volume density

Ω_N is normalized scattering parameter

De is particle effective diameter

rain rate rr can be derived as

$$rr = C_0 + C_1 IWP + C_2 IWP^2$$
(3)

When the rain rate data are retrieved, we use automatic rain gauge stations hourly data (less than 3 km far from observation point) to verify its accuracy, we also use radar echo map to compare its pattern. c,c,c,c are coefficients got from the website of NOAA

- 1. We collect 37 samples from July 2002 to Aug 2003 and compare its retrieved value with that of automatic rain gauge station, its results is shown in table 1.

 2. A typhono called MINDULLE passed Taiwan area from 28 June 2004 to 4 July 2004 and brought strong damage to Taiwan, its track is shown in Fig 1. We retrieve a NOAA pass at 18uTC, 1 July, its rain rate map and radar echo map are shown in Fig 2 and Fig 4, the rain rate map for automatic rain gauge station is shown in Fig 3, we find the pattern is similar, but the retrieved value is lower than that of automatic rain gauge station.

CONCLUSIONS AND FUTUREWORK

- 1. This algorithm is sensitive to scattering index or ice cloud so that retrieved number is small for a pass.
- 2. The retrieved rain rate values are lower than that of automatic rain gauge station, maybe we should adjust some coefficients to get better retrieved value

REFERENCES

Weng, F. and N. C. Grody, 2000 Retrieval of ice cloud parameters using a microwave

radiometer. J. Atmos. Sci., 57, 1069-1081.
Zhao, L. and Weng, F., 2002 Retrieval of ice cloud parameters using the advanced microwave sounding unit. J. Apple. Meteor., 41, 384-395.



Fig 1.typhoon MINDULLE'S track

Table 1 retrieval samples statistics from July 2002 to Aug 2003

	Accuracy of diagnose	Rms of rain rate	Sample size
Rain	83%	3.6mm/hr	12
No-rain	92%		25
Total or mean	87%		37



Fig 2 retrieved rain rate map at 18 UTC 1 July



Fig 3 rain rate map of automatic rain gauge station at 18 UTC 1 July




Fig 4 radar echo map at 18 UTC 1 July

International TOVS Study Conference, 14th, ITSC-14, Beijing, China, 25-31 May 2005. Madison, WI, University of Wisconsin-Madison, Space Science and Engineering Center, Cooperative Institute for Meteorological Satellite Studies, 2005.