Space Stanc UW SSEC Publication No. 92.00 M2

# Man computer Interactive Data Access System

# McIDAS-OS2 Users Guide

Issued January 1989 Revised February 1992



Space Science and Engineering Center University of Wisconsin - Madison 1225 West Dayton Street Madison, WI 53706 Telephone 608-262-2455 TWX 608-263-6738

# **Reader Response**

We would like your comments on our manual. Please take a moment to fill out this self-mailing form and return it to SSEC - McIDAS User Services and Documentation. Thank you.

Manual name (from the title page)								
Did you find	this m	nanual l	nelpful?	Did it	provide th	ne required	information?	
					eplin	Legion .		
Did you find	errors	or omis	ssions i	n the ma	anual? Pl	lease be ver	ry specific.	
Please rate th	his ma	inual or	the fol	lo <b>wing</b> i	tems fron	n 1 to 5, wit	th 1 as low and	5 as high.
Text	1	2	3	4	5			
Graphics	1	2	3	4	5			
Ease-of-use Overall	1 1	$\frac{2}{2}$	3 3	$\frac{4}{4}$	5 5			
What is the w	vorst f	eature (	of this n	nanual?	grafi b	log.		
				^				
Your name ar	nd title	e						
Date								
McIDAS site							And the second	
Address		H.	10000			The of Wiles	SACTIAL!	
Telephone					Burret.	natyaC re	eW 3227	
Check here if	you w	ould lik	e a wri	tten rep	ly.			

Reader Response

Fold Here

Fold Here

Space Science and Engineering Center McIDAS User Services and Documentation, Room 611 University of Wisconsin - Madison 1225 West Dayton Street Madison, WI 53706

# McIDAS-OS2 Users Guide

Installation	Procedure				
Setting Hardware Characteristics					
Installing OS/2 Version 1.3 Standard Edition					
Installing OS/2 Version 1.3 Extended Edition for TCP/IP					
	ng TCP/IP Version 1.1				
	synchronous Communication				
_	ng McIDAS-OS2 Software				
	g the SETUP Program				
	ring MD File Schemas				
	guring a WWW for Local and Remote Use				
	g Briefing Frames on a WWW 1-18				
E - E	CHO				
	n to McIDAS-OS2				
	ng Domains				
	g Commands				
	the Command Line				
	g, Printing and Erasing Text Windows				
	ext Window Keywords				
	eting the Status Line				
	ng Graphics Colors				
_	tring Tables and Function Keys				
McIDAS	S-OS2 Loop Control System 2-8				
Commanda					
	eting Bold and Italicized Terms				
	nating Commands				
	ne Alt Key				
	zing Screen Prompts				
_	eting the Command Information				
_	Command Description				
& Sample	Recalls a previously entered command				
A					
?	Recalls commands by backing up the command queue				
/ 200 0					
A	Terminates a command				
AA	Advances one frame				
AAMAP					
ASK1	Remaps an area into a Mercator or polar stereographic projection 3-11				
AVGI	Defines a question to prompt the user for string input 3-12				
	Reduces image resolution by averaging				
В	Backs up one frame position				
BATCH	Executes McIDAS-OS2 commands serially from a text file				
C	Lists an image frame's directory				
CA	Modifies the area directory				
CCODE	Lists country codes				
CLEAR	Clears a text window				
CM	Generates a graphics movie				
COLORS	Displays the text window color table 3-91				

Revised 2/92

COTV	Contours data in the cursor and produces a 2- or 3-dimensional plot 3-22
CTRL	Sends control characters to a modem
CUR	Defines cursor size, type and color
CW	Fills or erases the graphics within the cursor
D	Lists the digital values at the cursor center
DEFLOOP	Lists, saves and restores the workstation's loop state 3-29
DF	Displays a digital area on an image frame 3-31
DIST	Finds the distance on a satellite image
DMAP	Lists the name and size of LW files
DOQTL	Selectively deletes MD files
DOSTOLW	Converts DOS format files to LW format files
DR	Defines the dwell rates for frame looping
E	Lists the earth coordinates at the cursor center
EB	Invokes black and white contrast stretching
ECHO	Displays a line of text on the workstation
EG	Erases graphics frames
ET	Provides pseudocoloring for image frame overlays
EU	Enhancement utility
EXIT	Exits McIDAS-OS2 to the OS/2 operating system
F	Displays the video terminal status
GD	Sets graphics display parameters
GRDIMG	Converts a grid to a TV image
GU	Graphics utility
H	Toggles the host command entry mode on and off
HELP	Lists the on-line help for McIDAS-OS2 commands
IGG	Grid utility
IGTV	Generates contours and streamlines from grids
IGU	Grid file utility
IMGPRO	Generates satellite image products
ISENT	Calculates theta surface levels for all RAOB stations 3-71
J	Toggles graphics frames to and from the loop control system 3-72
K	Toggles image frames on and off
L	Toggles frame looping on and off
LA	Lists the digital area directory
LB	Sets image or graphics frame loop bounds
LF	Lists an image frame directory
LOGOFF	Logs you off the system and workstation
LOGON	Logs you onto the system
LS	Creates random loop sequences for image and graphics frames 3-82
LSCHE	Lists an MD file schema 3-84
LVF	Lists virtual frame files
LWTODOS	Converts LW format files to DOS format files
LWU	LW file utility
MA	Modifies a digital area
MAKMNU	Creates a menu file from text orders
MAP	Outlines map and latitude/longitude lines on a graphics frame 3-93
MC	Combines two areas to produce a new output area
MDE	Edits MD files
MDL	Lists the MD file data
MDU	
WIDO .	MD file utility

MDX	Plots or grids data from MD files or grids	3-109
MG	Plots a 24-hour surface meteorogram	3-116
MOVIE	Displays a sequence of loops	3-117
MOVIT	Copies areas and updates an image frame loop	3-118
MSL	Lists information from the international master weather station list	3-120
N	Moves the pseudocoloring table in/out of the video refresh data path	3-122
0	Switches the image frame position to the opposite frame	3-123
OD	Lists the digital area inside the cursor	3-124
OS	Sends a command to the OS/2 operating system	3-126
P	Locks and unlocks the cursor in its present position	3-127
PC	Positions the cursor at a desired point on the frame	3-128
PID	Lists the names and Process IDs for each task running in McIDAS-OS2.	3-130
PROMPT	Edits command text and then executes it	3-131
PSB	Displays a PLEASE STAND BY message on the text window	3-132
QA	Deletes digital areas	
REDIRECT	Writes the LW file path redirection memory block	
REMAP	Remaps an area into a different projection	
REPEAT	Repeats a McIDAS-OS2 command using a string table	
ROUTE	Routing table utility	3-137.
RUN	Runs a McBASI program	3-138
RVF	Restores virtual frames saved with command SVF	3-140
SC	Grids and contours surface data	
SCHE	Adds a schema to the schema file	
SCRDMP	Writes graphics frames to a graphics printer	
SEE	Lists the text in an LW file	
SENAA	Copies digital data from McIDAS-OS2 to McIDAS-MVS	
SENGRD	Sends grids to the mainframe	
SENLW	Sends an LW file to the host	
SENST	Sends the current string table to the host	
SF	Displays an image frame	
SG	Displays a graphics frame	3-153
SHOMNU	A debugging tool for the F Key Menu System	
SHOWVG	Displays virtual graphics	
SKE	Enters a McIDAS-OS2 command in the command scheduler	
SKEWT	Plots a sounding on a skew T thermodynamic diagram	3-158
SKL	Lists the entries in the command scheduler file	3-160
SKU	Command scheduler utility function	3-162
SL	Lists surface station data	3-164
SP	Plots surface data	3-167
SU	Image data stretching utility	3-170
SVF	Saves VGA virtual frames that can be restored with RVF	3-173
SYSKEY	Reads values from SYSKEY.DOC into SYSKEY.TAB	3-174
SYSVAL	SYSKEY utility	3-174
TD	Deletes one or more strings from the current string table	3-176
TE	Enters a string in the string table	3-177
TEDIT	Edits a string in the string table	3-179
TERM		3-179
TFILE	Sets the state of the J, K, L, N, O, P, V, W, Y and Z toggles	
	Sends text output to a disk file	3-181
TL	Lists the strings in a string table	3-182
TU	String table utility	3-183

Revised 2/92 iii

UC	Grids and contours RAOB data 3-18					
UCU	Inspects the User Common (UC) memory block					
UL	Lists RAOB data					
UP	Plots RAOB data					
V	Toggles the velocity cursor on/off when tracking cloud drift winds 3-19					
VASTBL	Creates calibration transforms for VAS (Mode AA) data					
VV	Computes the velocity vector					
w	Toggles the graphics frame on and off					
X	Tracks cloud drift wind targets with one knowntake					
XSECT	Tracks cloud drift wind targets with one keystroke					
Y	Displays a vertical cross section					
Z	Toggles image frames to and from the loop control system					
ZA	Toggles the zoom and roam functions on/off on a WWW					
2 7 2 2 1 1 2 1	Places an annotation on a graphics frame at the cursor position 3-20					
ZLM	Permits freehand drawing using the mouse					
ZM	Sets the zoom factor for a WWW					
E 17 M	TO WELL Woley the Life party redirection pages with Wales the Co.					
F Key Menu						
Introduc	ion					
Creating	a Menu Template File					
Instruct	n Characters					
Pseudo a	nd Other Special Commands					
Defining	Loops					
Testing a	Menu Template File					
Example	T10					
ASK User In	erface					
Introduc	on					
Invoking	ASK					
Termina	ng ASK					
Creating	an .ASK Text File					
Manipul	ting Text					
Example	5-7					
#0176 D						
Soft Tablet I	terface					
Introduc	on					
Creating	Soft Tablet Template File					
Compilin	a Soft Tablet Template File					
Entering	he Soft Tablet Interface					
Selecting	a Region					
Exiting t	e Soft Tablet					
Soft Tabl	t Commands					
Appendix A.	WWW Frame Allocation					
Appendix B.	FrailBlazer Plus Modem B-1					
Appendix C.	Asynchronous Communication					
Appendix D.	McIDAS-OS2 System Drivers					
Appendix E						
Appendix F						
Annendiy C	Exception Vector Assignments					
Annendie U	File Redirection					
Therrary 11.	MICHAEL INTERPRETATION INCLUME-084					

# **Installation Procedure**

Use the procedure below to install McIDAS-OS2. Read all instructions before starting the installation. These instructions assume that you are familiar with the OS/2 Presentation Manager<sup>TM</sup> graphical interface. If you need more information, see the *IBM OS/2 Getting Started* manual.

If you're installing McIDAS-OS2 for the first time, begin with the Setting Hardware Characteristics procedure on the next page.

If you're installing OS/2 Version 1.3 Standard Edition, turn to page 1-3 and begin with the Installing OS/2 Version 1.3 Standard Edition procedure.

If you're upgrading to OS/2 Version 1.3 Extended Edition for TCP/IP, turn to page 1-5 and begin with the Installing OS/2 Version 1.3 Extended Edition for TCP/IP procedure.

If you're installing a software upgrade and already have McIDAS-OS2 on your system, turn to page 1-11 and begin with the Installing McIDAS-OS2 Software procedure.

Revised 9/91

# **Setting Hardware Characteristics**

#### AT-Based Workstations

To set the hardware characteristics for AT-based workstations, you must determine the type of mouse, alter the hardware and replace the ProNET card.

- 1. To determine the mouse type, first remove the computer cover then remove the mouse card. In the upper-right corner of the card is some text describing the card. Locate the REV level (e.g., REV C) and mouse type (Bus, Inport or Other, if listed) and write them down. You'll need this information later. Put the mouse card back in the computer.
  - 2. To make hardware alterations, first remove the AST extended memory card. On switch pack 2, place switch 2 in the ON position. On Jumper Pack J6, attach a jumper strap on pins 3 (second from the right). There are two 3 pins (see below).

75433 ...|. ...|. 75433

Replace the AST card.

- 3. Remove the ProNET card. If your ProNET card is a one-half slot length board, locate the Interrupt Jumper Block and strap pin 17 to pin 14. If it is a full slot length board, locate the Interrupt Jumper (over the bus connection) and wire wrap JP17 to JP14. Replace the ProNET card.
- 4. Replace the cover on the computer.
- 5. To install OS/2 Version 1.3 Standard Edition, go to page 1-3; to install OS/2 Version 1.3 Extended Edition for TCP/IP, go to page 1-5.

# PS/2-Based Workstations

If you have a PS/2-based workstation, perform step 1 below to alter the hardware.

- Install the computer's reference diskette and boot the system.
   Change the configuration of the ProNET card so the I/O address reads x10E0.
- 2. To install OS/2 Version 1.3 Standard Edition, go to page 1-3; to install OS/2 Version 1.3 Extended Edition for TCP/IP, go to page 1-5.

# Installing OS/2 Version 1.3 Standard Edition

- To install OS/2 Version 1.3 Standard Edition, follow the procedure on pages 1 through 8 of the IBM Operating System/2 Standard Edition Version 1.3 Getting Started manual (the 159-page spiral insert).
   Select the appropriate responses for your system configuration.
- 2. The second step of the installation procedure asks you to select one of these base operating system installation options:
  - 1. Accept the default base operating system configuration
  - 2. Select base operating system configuration

Select option 2. The following choices appear on the screen:

Country Information
Documentation
Fonts
High Performance File System
Optional System Utilities
OS/2 DOS Environment
Picture Utilities
Serial Device Support
Serviceability and Diagnostic Aids

Choose the Optional System Utilities and Serial Device Support options. Choosing other options depends on your system needs and available disk space. Each option is described in Appendix A, Selecting System Installation Options, in the IBM Operating System/2 Standard Edition Version 1.3 Getting Started manual. Also see the on-line help for the installation procedure.

3. When you get to the step that asks you to select the mouse type, the choices below will appear on the screen if you have a PS/2.

IBM Personal System/2 Mouse
Microsoft Mouse, Serial Version (039-099)
Microsoft Mouse, Serial Version (039-199)
Microsoft Mouse, Serial Version (056-X99)
Microsoft Mouse, PS/2 Version (056-X99)
PC Mouse Systems Mouse
Visi-On Mouse
None of the Above

Revised 9/91 1-3

If you have a PC/AT system, these choices appear on the screen.

Microsoft Mouse, Bus Version (037-099)

Microsoft Mouse, Bus Version (037-199)

Microsoft Mouse, Bus Version (056-X99)

Microsoft Mouse, Inport Version

Microsoft Mouse, Serial Version (039-099)

Microsoft Mouse, Serial Version (039-199)

Microsoft Mouse, Serial Version (056-X99)

PC Mouse Systems Mouse

Visi-On Mouse

None of the Above

Select the correct mouse for your system. NOTE: If the mouse driver does not install properly during the boot, if the screen goes black and the system is locked, or if the mouse doesn't function properly after the boot, you may have selected the wrong mouse. Reinstall the operating system selecting a different mouse.

- 4. When you are asked to choose the default printer driver for your system, choose IBMNULL.DRV, the IBMNULL driver. The system will then ask you to choose the port your printer is connected to. Serial printers are usually connected to COM1; parallel printers are usually connected to LPT1. However, your system may be different.
- 5. System performance can sometimes be greatly improved by changing the MAXWAIT statement to one (MAXWAIT=1) and the DISKCACHE statement to 200 (DISKCACHE=200) in your CONFIG.SYS file.
- 6. When the installation is complete, boot the computer. Then turn to page 1-11 to install the McIDAS-OS2 software.

# Installing OS/2 Version 1.3 Extended Edition for TCP/IP

- 1. The first part of this installation is identical to that of OS/2 Version 1.3 Standard Edition. Therefore, perform steps 1-5 on the previous two pages before continuing with these instructions.
- 2. When you complete the base operating system installation, you will see a menu labeled IBM OS/2 Extended Edition Installation Option. Under that will appear this question:

Do you have a Custom Installation Diskette?

Your choices are Yes or No.

Select: No Press: Enter

 The Select Basic Configuration Services menu is displayed on the screen. It looks like this:

#### Select Basic Configuration Services

Basic Configuration Services allows you to create a Communications Manager Basic Configuration file for one or more of the following:

- 3270 terminal emulation
- ASCII terminal emulation
- 5250 workstation feature
- Remote Data Services on LAN
- LAN services

Do you want to create a Basic Configuration file?

- 1. Yes
- 2. No

Select: Yes

by moving the highlight bar to Yes and pressing Enter. Then type an appropriate file name and comment for the configuration file.

Revised 9/91 1-5

4. The Basic Configuration Services Main Menu is then displayed on the screen. It looks like this:

#### Basic Configuration Services Main Menu

Select a Communications Manager Basic Configuration feature that you want to create or change.

- 1. 3270 terminal emulation
- 2. ASCII terminal emulation
- 3. 5250 workstation feature
- 4. Remote Data Services on LAN
- 5. LAN services

You will return to this menu for additional selections. Select F3=Exit when your last selection is complete.

#### Select: LAN services

5. The Specify LAN Services Configuration menu is displayed on the screen. Your two choices are:

LAN requester LAN server

#### Select: LAN requester

6. The Select LAN Adapter Defaults menu is displayed on the screen. It looks like this:

#### Select LAN Adapter Defaults

Use the spacebar to select the adapter type. An arrow is displayed next to the option when it is selected. Press Enter when you have completed the selections.

Adapter type . . . . . . . . . :

IBM Token Ring Network
IBM PC Network
3Com Etherlink Network
Western Digital EtherCard PLUS Network
Ungermann-Bass NIU Network

Select the type of LAN address for your workstation:

Use universal address Specify a locally administered address First specify the adapter type, i.e., the type of Ethernet card your workstation has.

Then select the type of LAN address for your workstation.

#### Select: Use universal address

 You will return to the Basic Configuration Services Main Menu. To continue,

Press: F3

8. Next you will be asked the Target Drive Specification for the Communications Manager. To accept the default drive C:,

Press: Enter

If you want to install the Communications Manager on another drive, type that drive letter, press Enter.

9. The Communications Manager Install Menu is displayed on the screen. To install the Communications Manager,

Press: F3

10. You will then be asked the Target Drive Specification for the LAN Requester. To accept the default C: drive,

Press: Enter

Or designate an alternate drive, if desired.

11. The LAN Requester Install Menu is then displayed on the screen. It looks like this:

#### LAN Requester Install Menu

Select an option below to install LAN Requester base or additional features or the entire LAN Requester component.

- 1. LAN Requester base
- 2. Online Reference and Help panels
- 3. API data structures
- 4. All of the above

You will return to this menu for additional selections when option 1, 2, or 3 is selected.

Select F3=Exit when your last selection is complete.

You must choose number one.

#### Select: LAN Requester base

Select other options as needed for your workstation. Also specify appropriate requester and default domain names.

12. You will then be asked to select requester services from this menu:

#### Select Requester Services

Select the services to start when the requester is started. Services available are Messenger and Message Popup.

- Messenger
- 2. Messenger and Popup
- 3. Neither of the services above

Select either number 1 or number 2.

You will then return to the LAN Requester Install Menu. To continue with the installation process,

Press: F3

13. The IBM OS/2 Extended Edition Install/Remove Menu is displayed on the screen. Again,

Press: F3

This completes the installation process. Boot your system; then go to the next page and install TCP/IP Version 1.1.

Note

If you have a Western Digital Ethercard, you will encounter an error during the boot-up process. Press Enter to continue. When the Presentation Manager comes up, you must edit the file \CMLIB\PROTOCOL.INI. In that file is a statement that reads:

#### BINDINGS=TCMAC2

Change that line to read:

#### BINDINGS-WDMAC

Save the file and boot your system. The error should be gone.

# Installing TCP/IP Version 1.1

1. Be sure an OS/2 prompt, either windowed or full screen, is displayed on the screen. Insert Diskette #1 of the TCP/IP for OS/2 in the A: drive. Then,

Type: A:ICAT Press: Enter

2. From the Main Menu.

Select: Install

 The Installation Tool menu is displayed on the screen. Click on the boxes next to the products you want to install. You <u>must</u> choose the Base Product option.

When you've made your choices, click on the Install button. As the installation progresses, you will be asked to insert diskettes into the A: drive.

 When the installation is complete, the Main Menu is again displayed on the screen. Now,

Select: Configure

- 5. The TCP/IP Configuration Tool menu options, shown below, appear on the screen.
  - 1. Network Interface Parameters
  - 2. SLIP Interface Parameters
  - 3. Automatic Starting of Services
  - 4. Configure Services
  - 5. Routing Information

#### Select: Network Interface Parameters

This selection displays a window for configuring the parameters for your system. Click on the box next to Enable LAN Adapter 0. Then fill in the box labeled IP Address, which is the address for the workstation you're installing this software on. Click on the Menu button to save your settings and return to the Configuration Tool menu.

6. Select: Routing Information

This selection displays the Configure Routing Information window on the screen.

To insert an entry,

Press: F5

A small Route-Insert Before window is displayed on the screen. It has four boxes to fill in. At the Route Type box,

Press: D

The word Default appears in the box.

In the box labeled Gateway, type the IP address of your gateway machine. Then click on the Enter button.

When the Configure Routing Information window is again displayed on the screen, click on Menu to save the settings and return to the Main Menu.

7. From the Main Menu, click on the Exit button to quit the installation/configuration procedure.

Now go to the next page for instructions on installing McIDAS-OS2 software.

# **Using Asynchronous Communication**

fill in the box labeled IP Address, which is the address for the

You need a TrailBlazer modem and either a dial-up or dedicated telephone line to use asynchronous communication with McIDAS-OS2. See Appendix B in this manual for specific line requirements and modem configurations. Appendix C describes how to establish a McIDAS session with a host.

To successfully log on to the host, you must have a valid user ID and project number combination on the mainframe you want to connect with. Some sites may require a password.

# **Installing McIDAS-OS2 Software**

The McIDAS-OS2 Version 5 software series runs under IBM's OS/2 Version 1.3 operating system on IBM PS/2 workstations.

The installation diskettes are divided into two groups. The first group (labeled Disk 1 through Disk 7) contains the software required for your system to run host-based and local (PC-based) commands.

The second group of diskettes (labeled Development) contain source code for subroutines and programs, the link libraries and the MAPS needed for cross referencing. If you plan to develop PC-based applications, install these files. If you do not want to install the Development software, press Ctrl+C when prompted to end the installation.

The OS/2 operating environment consists of one or more sessions or partitions. You can move between them by pressing Alt+Esc, i.e., hold down the Alt key and press the Esc key, releasing both at the same time. You can also use the Presentation Manager Windows to move between partitions. The number of sessions or partitions depends upon your workstation's configuration.

If you're performing a routine upgrade, be sure to exit McIDAS-OS2 before beginning the procedure. See the EXIT command for more information.

1. Begin the installation by accessing the Presentation Manager interface. To do this,

Press: Ctrl+Esc Select: Group-Main Select: OS/2 Full Screen

You will know you are in the OS/2 mode when the system displays this prompt:

[C:\]

2. Place the diskette labeled Disk 1 in drive A.

 If you are installing McIDAS-OS2 for the first time, or are skipping several upgrades,

Type: A:INSTALL

Press: Enter

To perform a routine upgrade:

Type: A:UPDATE

Press: Enter

An INSTALL on a new system requires 10 mb (minimum) of free disk space. Although an UPDATE theoretically requires less than 1 mb of free disk space, be sure enough space is provided for new files or files that have increased in size.

Throughout the installation procedure, the system will pause and ask you to insert diskettes into drive A by number. If the needed diskette is already in the A drive, press Enter to continue.

4. When you've installed the required files from the diskettes, the system will prompt you with the following message.

Preparing to install additional files for software DEVELOPMENT environments

Either insert DEVELOPMENT Diskette 1 and press ENTER - or -

type CTRL+C to stop

You must now decide whether to install the Development software. The Development files contain source code for subroutines and programs, the link library and the MAPS needed for cross referencing. If you do not want to install this software, press Ctrl+C to end the installation. Otherwise, insert the Development diskette and press Enter to continue.

After completing the INSTALL procedure, this OS/2 prompt appears on the screen:

[C:\MCIDAS\TOOLS]

5. If you have not already done so, remove the diskette from drive A.

# **Running the SETUP Program**

After you install the McIDAS-OS2 software, run the SETUP program using the instructions below.

#### Caution!

The SETUP program alters the \CONFIG.SYS and \STARTUP.CMD files on your system. Interrupting the execution of this program with a Ctrl+C or BREAK may corrupt these files. If you make a mistake and need to correct an error, answer the remaining questions, then rerun SETUP without booting your system.

1. From an OS/2 prompt, check that you are in the \MCIDAS\TOOLS subdirectory. Then,

Type: SETUP Press: Enter

The system prompts you with a series of questions about your system configuration.

2. If you are using Asynchronous Communications, the two questions below will appear on the screen:

Communications port for data connection? . . . . .

Normally, the default value of COM1 is displayed. You must type the name of a port, e.g., COM1, COM2, etc.

Modem command for LOGON to use to dial-up host (or NONE)? . . .

If you want LOGON to attempt to dial up the host that you normally connect to, enter the required modem command text here, e.g., ATDT9,6085551234. Subsequently, the LOGON command will issue this modem command if no host session exists.

3. If you're using TCP/IP communications, this question will appear on the screen:

IP ADDRESS for LOGON to use to connect to host (or NONE)? . . .

Enter the IP ADDRESS of the host that you want the LOGON command to attempt to connect to.

- 4. If you don't have a printer, select the parallel printer option when prompted in the SETUP program.
- 5. If you use a serial printer, this question will appear on the screen:

Port to use for Printer connection? . . . . . .

Normally, the default value of COM1 will appear unless it conflicts with the asynchronous connection for data communications. If this is the case, the default value of COM2 is displayed. You must type the name of a port, e.g., COM1, COM2, etc.

6. The following question relates to the VDISK that McIDAS-OS2 needs for communications.

Virtual Disk (VDISK) is assigned to what letter (D, E, etc.)?

OS/2 assigns this letter when the system boots up and the CONFIG.SYS file is interpreted. During this process the message below is briefly displayed on the screen.

#### VDISK Version 1.30 Virtual Disk D

The letter D is the logical drive letter that the system assigned to the Virtual Disk. Its value depends on your hardware configuration.

If you do not know the correct answer to the question,

Type: D

After the SETUP program is completed, boot your system and look for the message shown above.

If the letter D does not appear in the message, DO NOT start McIDAS. Rather, rerun SETUP and substitute the correct letter for the default given in the message. When you're done running SETUP, you may start McIDAS.

7. If you use ProNET or TCP/IP communications, the following question will appear on the screen:

Would you like auto logon when host is connected (Y/N)? . . .

If you answer yes, the following response is displayed:

Type the complete image of the LOGON command to use for Auto Logon, including the word LOGON and your password, if needed:

Type the complete LOGON command that you want to use for Auto Logon. For example,

Type: LOGON ABC 1234 X PASSWD

Press: Enter

- 8. If you have a VGA display, specify the number of image frames as a nonzero value. If you have 4 mb of memory, specify 4 image frames. Each additional megabyte adds about 8 frames. As the number of frames is increased, disk size also becomes important.
- 9. If you have a WIDE WORD workstation and want to create briefing frames, see page 1-18 for more information.
- 10. If you answer Y to this question:

Provide for inclusion of USER programs (Y/N)? . . .

Your search paths are modified to include \MCIDAS\USER\CODE. We recommend you place any locally developed programs in \MCIDAS\USER\CODE for inclusion with McIDAS-OS2 on your system. If you specify your own alternate search path, it is removed if you answer N to the above prompt and you must reinsert it manually.

11. Boot the system.

Press: Alt+Ctrl+Del (simultaneously)

The first logon under OS/2 will take some time due to memory management software that runs on initialization.

If the system does not initialize properly when you boot, it could be your mouse driver. If you're using OS/2 Version 1.3, see the NOTE in instruction 3 on page 1-4.

12. If you have a VGA workstation, enter the McIDAS-OS2 command below when you boot the system for the first time after installing the software. Otherwise, graphics won't appear correctly on VGA frames.

Type: EG I 1 maximum number of frames on the workstation

Press: Enter

# **Registering MD File Schemas**

Each version of McIDAS-OS2 includes copies of the LW files DCSVCA, DCRAOB and DCISFC in the \MCIDAS\DATA subdirectory. These files define the SVCA, RAOB, RSIG and ISFC MD file schemas. RAOB and RSIG are in schema DCRAOB. Additional schemas will be supplied as needed.

When you register a schema using McIDAS-OS2 command SCHE (in the Commands section of this manual), the LW file is read and the schema's internal form is copied into LW file SCHEMA, which also resides in the \MCIDAS\DATA subdirectory. Command SCHE can also add locally developed schemas to the PC.

The MD file input/output routines read, write and extract data to and from MD files of registered schema types only. This is why you should always register the supplied schemas using the SCHE command after installing McIDAS-OS2 for the first time.

Once a schema is registered on the PC, it is not necessary to register it every time you install a new version of McIDAS-OS2. When a schema is updated, it is noted in the Significant Program Changes document supplied by SSEC for your site coordinator. You must register the new schema version to remain compatible with SSEC.

To register the MD file schemas, first complete the software installation procedure. Then bring up McIDAS-OS2 in the local mode (H key turned off). Finally, use McIDAS-OS2 command SCHE to register each schema.

To register the schema SVCA,

Type: SCHE DCSVCA

Press: Enter

To register the schemas RAOB and RSIG,

Type: SCHE DCRAOB

Press: Enter

To register the schema ISFC,

Type: SCHE DCISFC

Press: Enter

Use the list schema command, LSCHE, to verify the registered schema types and version numbers or to search the schemas for a specified key.

# Reconfiguring a WWW for Local and Remote Use

In principle, you can configure the WIDE WORD Workstation (WWW) by running the SETUP program in \MCIDAS\TOOLS. In practice, this is undesirable because it requires you to make decisions that should be made by the system administrator.

When the WWW is connected asynchronously, as it will be when running on a remote backup, the frame/graphic configuration must be 480/640. Protocols don't permit wide frames to transmit over asynchronous communications. You must transfer the digital data using command SENAA first and then use the McIDAS-OS2 DF command to display wide frames. When you configure back to ProNET, you must know the workstation's original configuration.

Since only two data files (STARTUP.SYS and ALLOC.WWW) in \MCIDAS\DATA are affected, keep one copy of each file for each configuration. It is then an easy process to construct batch files that invoke the correct copy and the swap is easy. A side benefit of this procedure is that you can test both configurations ahead of time.

Revised 2/92 1-17

When you define briefing frames, Mai DAS-OSE loads two cytra

# **Creating Briefing Frames on a WWW**

When you configure a WIDE WORD Workstation (WWW) with the SETUP program, you can allocate part of its memory to briefing frames. To do this, watch for the prompt below on the screen.

Should remaining memory be allocated as I (image) or G (graphics) frames?

Then,

Press: I

Pressing I allocates the remaining memory to as many 480 by 640 image frames as possible. Frames in this group are like VGA frames in that they combine images and graphics in one frame. Image levels 1-8 are converted to level 9 before they are written into the WWW memory. Graphics written to these frames are written in levels 1-8. Level 0 and levels 9-255 are unchanged. Command EG erases the entire frame.

The advantage of briefing frames is that you can display them on channel two of the WWW, independently of what is happening on the main display. Thus, the workstation simultaneously controls two different displays, each of which may contain image and graphic data.

When you define briefing frames, McIDAS-OS2 loads two extra modules during its initialization process. These modules are a Briefing Manager and a Briefing Control Interface. The Briefing Control Interface monitors the serial COM3 port looking for ASCII characters 0 through 9. Characters 1 through 9 are interpreted as requests to show briefing loops 1 through 9. The 0 character starts and stops looping on the briefing display. You may need to insert a MODE command into the STARTUP.CMD of the system to characterize the COM3 port to read the device that commands the Briefing Control Interface. If you use the SSEC recommended keypad, the mode command should read:

MODE COM3:9600, N, 8, 1

Insert it just before the START command for the McIDAS session.

Briefing loops are produced and previewed on the main WWW. Use command SG to ensure that graphics will be imbedded in the image. Turn the W command toggle off when previewing briefing loops to avoid confusion.

You can save nine loops as briefing loops with the DEFLOOP command. For example,

Type: DEFLOOP SAVE 3

Press: Enter

This entry defines the current looping state of the workstation as loop number 3. It saves the current loop bounds set with the LB or LS command (use even if the loop you want to save is a single image or graphic). It also saves the dwell rates and initial looping state of the WWW. To display loops 1-9 defined with DEFLOOP, press briefing keypad keys 1-9.

You can define the loop in motion or static, depending on the state of the main display when you entered DEFLOOP.

See the McIDAS-OS2 Loop Control System information in the Introduction section of this manual for information about using briefing frames in displaying loops.

Revised 2/92

1-20

Revised 2/92

# Introduction to McIDAS-OS2

The McIDAS-OS2 Version 5 software series operates under version 1.2 of the IBM Operating System/2. This system operates in two modes, OS/2 and DOS. OS/2 allows multitasking of commands where more than one program can operate at a time. The DOS mode, or DOS Compatibility Box, is similar to the IBM DOS version 3.3.

Since each operating mode has its own command processor, it is possible to execute DOS or OS/2 commands and continue running McIDAS-OS2. Pressing Ctrl+Esc invokes the OS/2 Task Selection Menu. Use it to leave the McIDAS-OS2 environment for word processing or file maintenance. McIDAS-OS2 will be unaffected.

# **Switching Domains**

To leave the McIDAS-OS2 domain,

Press: Alt+Esc (simultaneously)

Each time you do this, OS/2 rotates to the next session.

Alternatively,

Press: Ctrl+Esc

to return to the Task Manager. From there you can select the desired session.

The DOS Compatibility Box provides a 640K DOS partition for running DOS-based applications. It only works with applications that do not require either extended/expanded memory or system resources in use by other sessions.

If you develop software, create a session of TOOLS if one does not already exist. First, select the OS/2 Full Screen prompt. Then,

Type: \TOOLS
Press: Enter

See the McIDAS Applications Programming Manual for more information about software development.

Revised 9/90

## **Entering Commands**

Use the following protocols when entering McIDAS-OS2 commands.

- Enter up to 160 characters on each command line. The command line scrolls to the right as necessary.
- · Do not precede commands with a linefeed.
- After typing a command, press Enter to execute it.
- Execute system defined single-letter commands by simultaneously
  pressing the Alt and letter keys, or typing the letter and pressing
  Enter. You can enter single-letter commands with the Alt key
  during entry of multiple-letter commands.
- Enter single-letter strings with a pound sign (#). Press Ctrl and the letter if the single-letter string is a complete command.
- Run commands on either the host or PC. An H on the text window status line means that commands entered from the keyboard will execute on the host (except those which control the video system or enhancements).
- Since the same command may exist on both the PC and host, precede a command with a period to bypass execution on the PC while in the PC mode (no H is seen on the status line).
- Commands used in strings or entered into the PC-based scheduler must contain a period (.) if they are to run on the host.
- Use the question mark (?) command in the local mode to display local status. Active PC commands are listed with a Process IDentification (PID) number. To terminate a command, use the slash (/) command with this PID value. Use the SS command to obtain the status on the host.
- If multiple commands are entered on one line, they must all be sent to the host or run on the PC.

2-2

# Editing the Command Line

Listed below are the command line editing keys. If your keyboard has a numeric keypad that is not separate from the cursor arrows, enter the commands with an asterisk (\*) after them by simultaneously pressing the Ctrl key.

Editing Keys	Function
Home*	Moves the cursor to the beginning of the line.
End*	Moves the cursor to the end of the line.
Insert*	Toggles the insert typing mode.
Delete*	Deletes the character under the cursor.
Backspace	Deletes the character to the left of the cursor.
Right/left arrows*	Moves the cursor one character to the right or left.
Tab or Shift+Tab	Moves the cursor one parameter to the right or left.
Enter	bottom showing the echoed command.
Esc	Erases the command and places the cursor at the front of the line.
Alt+?	Obtains HELP information for PC-based commands.
& and ^	Recalls a command if the command line is empty, or contains a command recalled with & or ^. The & recalls the previous command from a circular list of the last 20 commands entered. ^ scans the recall list in the opposite direction.
Space	Is ignored in the first column of the command line, unless you are in the Insert mode.

Revised 9/90 2-3

# Selecting, Printing and Erasing Text Windows

You can select 10 CRT text windows with the numeric keypad. Windows 0-4 are scrollable to 80 lines of text and may be written by any command. You can view 23 lines at a time. Windows 5-9 are nonscrollable, fixed sized, point-addressable display windows written by PC-based user definable applications, e.g., the F Key Menu System and ASK user interface.

Text directed to windows 1-4 is not repeated on window 0. If text is written to a window you are not viewing, a flashing yellow window number will appear at the far right of the command status line. See the status line information on page 2-6. When you switch to that window, the system removes the indicator from the status line.

EGA and VGA workstations using OS/2 version 1.2 have a standard configuration of 8 graphics/image frames. Each frame uses 128,160 bytes of on-board memory. More frames may be used if the memory capacity is increased. You can toggle between graphics frames and text windows with the plus key (+) on the numeric keypad. When a graphics frame is displayed, typing a number on the numeric keypad will display that text window.

The text windows employ the following color code.

Color	Application	
blue	window background	
gray	output from local commands	
white	output from host-based programs	
yellow	error messages from local programs	
magenta	output from communications activities	
green	command echo	
cyan	input command line	

Pressing the Print Screen key prints the currently displayed text on your local printer.

PC command CLEAR erases the text window.

# **Using Text Window Keywords**

All commands support the TWIN, TCOL and TMOD text window keyword parameters. These keywords direct output to any text window in a color you select.

TWIN

TWIN directs output to the specified text window. For example, TWIN=3 directs output to window 3.

TCOL

TCOL defines the text output color. The COLORS command displays a color palette. You can also select a blinking text mode. Host commands use the color range from 0-15 listed below. PC commands can use all colors. COLORS displays the palette and TCOL values on window 5.

Number	Color	
0	blue	
1	black	
2	green	
3	cyan	
4 Man bowled	red	
5	magenta	
6	brown	
7 and no beamer	gray gray	
8	dark gray	
9	bright blue	
10	bright green	
11	bright cyan	
12	bright red	
13	bright magenta	
14	yellow	
15	white walls and amount	

**TMOD** 

TMOD sets the mode of TWIN. However, this does not apply to window zero.

TMOD=2 displays the window specified by TWIN. It is available for host commands only.

TMOD=4 neither erases nor displays the window. It is the default.

Revised 6/91

# **Interpreting the Status Line**

A status line is displayed above the command line. Below is an example, followed by a description of each part.

Δ-H-049-001-064-RT	-K-W-L-P-J-Y-N-Z-V 7 FEB 910401515100-37-01234
Δ w. For example,	A cyan triangle means the insert mode for command line editing is on. Whatever you type is inserted in the command line at the cursor position.
Recommend displays at mode. Float selow, PC commends and TCOL values on	H means the host mode is active. It is activated whenever the ProNET or asynchronous communications encounters a connect condition. The PC sends most commands to the host when the H key is on. Some loop control and enhancement commands are reflected back to run on the PC.
049 001 064	These numbers are the current image frame number and loop bounds. The loop bounds do not appear for random loops defined with the LS command.
R	R means the workstation has received data and not decoded it. The R disappears when the receive queue is empty.
Т	T means the workstation is requested to transmit data but is not done yet. The T disappears when the transmit queue is empty.
KWLPJYNZ	These letters are listed when the corresponding command is active. Use Alt+letter to toggle them. EGA/VGA workstations do not support Y, J and N. Z is only supported on WIDE WORD workstations.
V	V means the velocity cursor is invoked during a cloud drift wind tracking session (PCMW is running).
7 FEB 91040	This is the current date (DD MMM YYDDD) taken from the workstation, not the host.
151510	This is the current time (HHMMSS) taken from the workstation, not the host.
0	This is the current text window number.

37

This is the top line number of the text window. It is displayed if the window bottom is not shown. Use the up/down arrows to move by single lines. Use the Page Up/Down keys to move by 20 lines. Older keyboards use Ctrl+function to activate arrows, Up/Down keys, etc.

01234

These flashing numbers at the end of the line indicate that there are text windows with text that you have not viewed. They disappear after displaying the text. A yellow number on a black background means a window is activated for text capture by the command TFILE.

# **Changing Graphics Colors**

The tower workstation graphics color level range is 0 to 7; 0 is the background level that covers the entire screen. Command GU modifies these colors.

VGA workstations have color levels ranging from 0 to 15. The graphics palette named IMAGE.ET is automatically loaded when a host-based graphics command is executed. You may want to use command GU to load a graphics palette when executing a PC-based command. When graphics overlay a satellite image, only levels 1 to 3 are used for graphics. All 16 levels may be used when displaying graphics alone.

# **Using String Tables and Function Keys**

String Tables

Local string tables are always active, even when commands are sent to the host. The string table commands TD, TE, TL and TU are identical to the mainframe commands. Your local terminal number, needed when saving and restoring strings, is always number 1. Use the SAVEFILE keyword in TU to keep personal copies of your strings. To send a string with one pound sign (#NAME) to the host, enter two pound signs (##WAME). To enter #NAME in a host string table, enter four pound signs (####NAME).

Use command SENST to transfer string tables to the host or PC.

#### **Function Keys**

To program your own function keys, use the PC string table commands while in the PC mode (H is toggled off). Using the Alt, Shift, and Ctrl keys, there are 40 combinations for the function keys.

TE	KEYFn	"command	where $n$ defines the function keys from F1
			to F10
TE	KEYAFn	"command	combines the Alt key with a function key
TE	KEYSFn	"command	combines the Shift key with a function key
TE	KEYCFn	"command	combines the Ctrl key with a function key

The F Key Menu interface supports more than 1000 menu screens. For more information, reference the McIDAS-OS2 F Key Menu System documentation that begins on page 4-1.

# McIDAS-OS2 Loop Control System

#### **Defining a Loop**

McIDAS-OS2 can display an automatically repeating sequence of images and/or graphics much like a movie loop. You define the frame sequence with either the LS (Loop Sequence) or LB (Loop Bounds) command. Command DR (Dwell Rate) determines the amount of time that each frame is displayed. Once a loop is defined, several single-letter commands can further define the state of your display.

- The L command starts and stops the loop. If the loop is actively
  stepping through frames, pressing Alt L stops on the first frame of
  the loop. Similarly, if looping is inactive, pressing Alt L starts the
  animation. When the loop is active the letter L appears on the
  command status line.
- The A command manually advances one frame while the loop is stopped.
- The B command backs up one frame while the loop is stopped.
- The Y command toggles the image loop control on and off. The looping control can treat graphics and images independently on tower and WIDE WORD workstations. If the letter Y appears on the command status line, it means the images are not included in the looping. Simply press Alt Y to change this. Conversely, if the letter J appears on the status line, it means graphics frames are included in the looping. Y and J are defined opposite one another because in the normal state, images are included in the looping, but not graphics.
- The J command toggles the graphics loop control on and off.

The loop control system also includes commands that modify the cursor, graphics, enhancements and nortel (N-key) state. Basically, any command that defines the state of the display is considered part of this system, i.e., the User Common display state.

#### Saving and Recalling Loops

After you define a loop or display state using the commands described above, use F Key Menu System pseudo commands \*S and \*R or command DEFLOOP to save the definition. The loop can be quickly reinstated later by pressing a function key or using the MOVIE command. You can define up to 99 loops for each workstation. For more information and an example, see the F Key Menu System section of this manual.

The MOVIE command automatically steps through the predefined loops at user defined rates. If you have a WIDE WORD Workstation (WWW), you can create special briefing frames and use either the MOVIE command or a separate numeric keypad connected to the extra serial port on the PS/2 to display the briefing loops on channel 2.

# Automatically Updating Loops

Each time you use command DF or DFASAP to display a new image from the mainframe, the PC checks the loop state definition for the loops saved with the F Key Menu (loop numbers 1-29 only), DEFLOOP, and the current loop. If any of these contexts were set up with command LS and contains a reference to the frame just displayed, the loop sequence is rotated until the new frame is in position 1 of the loop.

The dwell rates are not changed. Therefore, the newest image always has the dwell initially set for position 1. In addition, this position is always the frame displayed when animation is stopped since the system always stops a loop on the first frame of that loop. This automatic updating of loops works identically on all McIDAS-OS2 workstations. Graphics are not automatically updated.

# Creating Briefing Loops

Briefing loops are loops of images and/or graphics created to produce manual or automated presentations. They are created on any workstation display and may be shown on either the main display or channel 2 of a WWW. For WWWs, see the Creating Briefing Frames on a WWW section in the Installation Procedure Chapter.

Create briefing loops to set the display to the desired state. When the display is set, use the DEFLOOP command to assign the current state of the terminal to a loop number from 1 to 99. For WWW briefing frames, loops 1-9 can be used with the keypad.

# Using Briefing Frames on a WWW

When you configure a WWW with the SETUP program, you can allocate part of its memory to briefing frames. See Appendix A in this manual for further details. These special frames combine images and graphics into one frame that can be displayed independently through the second video channel of the WWW. Hence, a second monitor allows you to control two simultaneous, high resolution displays.

In addition, you can create briefing loops with these special frames. This allows you to set up an independent briefing display on any WWW. To make this more flexible, McIDAS-OS2 loads two extra modules during its initialization process if briefing frames exist on the workstation. One of the modules monitors the serial COM3 port, looking for ASCII characters 0 through 9. If a suitable ASCII keypad is connected to this port, keys 1 through 9 are interpreted as requests to display briefing frames 1 through 9. The 0 key starts and stops the looping on the briefing display. In the absence of such a keypad, use command MOVIE.

## Commands

This section of the manual contains the McIDAS-OS2 commands. Below is an explanation of the conventions used in documenting these commands.

# Interpreting Bold and Italicized Terms

Actual keyboard entries appear in BOLD type. Type these entries exactly as they appear. Command names, some parameters, all keywords and examples are bolded. For example:

### IGG MAKE 2 SUB 1

Variable entries, such as parameters, appear in italics. For example,

### HELP command

If you want to list the on-line documentation for command CUR, type the following entry at the keyboard:

### HELP CUR

Use capital letters and leave a space between each term/number in a command line.

## Concatenating Commands

You can concatenate commands with semicolons. For example:

### SF 3; EG 3; DF 101 3 EC MSN; MAP

### Using the Alt Key

When you see an Alt entry, it means you will press two keys simultaneously. The Alt key is like the Shift key in that you hold it down while typing another key. For example,

### Press: Alt B

means that you should hold down the Alt key and press the B key.

# Recognizing Screen Prompts

System prompts and responses look like this:

Boxed text displayed in this typestyle indicates a screen message.

# Interpreting the Command Information

Most of the command descriptions have Format, Default, Parameter, Keyword, Remark and Example sections. However, some commands have only a Remarks section. To better understand the information in each of these sections, see the sample command description on the next page.

## **Command Name**

This line gives a brief description of the command's function.

Format

The format contains the command name along with any positional parameters and/or keywords that it needs to perform its function. Commands can have several formats. Enter BOLDED terms exactly as they appear in the command format. *Italicized* terms are variables. You must enter a value or option in place of it in the command line. If a format takes more than one line, the second line is indented.

Default

The default is the shortest useful version of the command. Below the default is a description of its function. If a command doesn't have a default, you must specify the parameters. Typing the letter X in a command tells McIDAS-OS2 to insert the default value for that parameter.

**Parameters** 

Parameters are numbers or letters that provide information to a McIDAS-OS2 command. To the right of each parameter is an explanation of its function. Enter parameters in the exact order specified in the command format. It is not always necessary to include every parameter. Insert the letter X in place of a parameter if you want to use its default value. Enter BOLDED parameters exactly as they appear in the text. If a parameter is *italicized*, insert the appropriate number/letter in the command format.

Keywords

Keywords further clarify a command function; they are optional. Keywords are from 1 to 6 characters in length followed by an equals sign (or comma) and a value, e.g., COLOR=3, LAT=20 40, UNIT=A. Text values must be typed exactly as they are listed with the keyword. Use as many keywords as you want in a single command format. Although keywords are listed alphabetically in the documentation, their order in the command format is not important. Just be sure they come after the parameters in the command line. To the right of each keyword is an explanation of its function. Most keywords may be truncated to three characters. For example, you can enter COL instead of COLOR, or UNI in place of UNIT.

Remarks

Additional information about the command is contained here.

See Also

Mentioned here are other related commands that you can reference.

Examples

One or more examples are provided for each command. If an example takes more than one line, the second line is indented. Directly below each bolded command line is an explanation of what the entry does.

# & (Ampersand)

Recalls a previously entered command.

#### Remarks

The & command displays a previously entered command on the screen's command line. You can backtrack up to 20 commands by repeatedly typing the ampersand.

You can modify the command line before entering the command.

The ampersand command works in this manner only if you have not typed any other characters on the command line.

### See Also

The caret (^) command tracks previously entered commands in the opposite direction.

Revised 9/90 3-3

# ^ (Caret)

Recalls commands by backing up the command queue.

### Remarks

To recall commands in the direction opposite the ampersand (&),

Type: ^

Each press of the caret key backs up the command queue by one.

# ? (Question Mark)

Lists the McIDAS-OS2 command status.

### Remarks

The question mark (?) command lists all commands that are currently executing on the PC.

The output format is as follows:

Column	Output Format
1	the command entered; it may be truncated if it's a long command
2	the Process IDentification (PID) number used when terminating a command
	terminating a command

### See Also

See the slash (/) command for information about terminating a program. You cannot terminate a program that is running on another workstation.

Revised 9/90

# / (Slash)

### Terminates a command.

### Remarks

To terminate a command, enter a slash followed by the Process IDentification (PID) number. If you don't know the PID number, use the question mark (?) command to list it.

To determine the PID number,

Type: ?

Press: Enter

Then,

Type: / PID number

Press: Enter

You cannot terminate a program that is running on another workstation.

### Example

/4

This entry terminates PID number 4.

### A

Advances one frame.

Remarks

To advance the frame position by one,

Press: Alt A

or

Type: A
Press: Enter

destination are a grant for an area of the second production and the second statement and the second second

reformer point (delicated AU, meaning the area coordinates

Revised 2/92

## AA

### Copies and displays a digital area.

**Formats** 

AA sarea darea frame locate station mag line ele [keywords]
AA sarea darea frame locate y-coord x-coord mag line ele [keywords]

Default

AA sarea darea

This entry copies sarea to darea beginning at the upper-left corner of the area and provides a darea size of 500 lines by 640 elements. It is not displayed on an image frame.

**Parameters** 

sarea source area number of the data

darea destination area number; it must be different than sarea

frame image frame number for display; the data in darea is displayed on the frame

OPP displays the image on the opposite image frame

0 does not display the image (default)

locate

type of coordinates the area transfers and TV load use as a reference point (default=AU, meaning the area coordinates are displayed with the upper-left corner line and element); use one of these coordinate systems:

A area

E earth

I image

followed by one of these locations:

C centered

D lower-right corner

U upper-left corner

station station ID, e.g., MSN, DSM, 2C2; it must be preceded by

EU, EC or ED

y-coord y-axis coordinate (default=upper-left corner of the area)

x-coord x-axis coordinate (default=upper-left corner of the area)

mag image blowup or blowdown factor; positive numbers blow

up; negative numbers blow down; blowups repeat data

values; blowdowns sample data (default=1)

line line number dimensioning darea (default=500 if subsecting a sounder)

ele element number dimensioning darea (default=500 if subsecting a sounder)

Keywords ASIZE= ALL moves the entire area including all bands; it is not necessary to designate a frame number

BAND= band number to move, the range is 1 to 9, A, B, C where A=10, B=11 and C=12; (default=8 for VAS, 2 for AVHRR) ALL moves all bands if subsecting a sounder

EMAG= element only blowup or blowdown

GRAY= OFF does not display a gray wedge (default)
YES adds a gray wedge to the bottom of the image, the
range is 0-63 for tower workstations, 0-255 for
WWWs, 0-15 for EGA/VGA workstations; it uses
the defaults below

repeat inc start line

repeat brightness repetition factor (default=10 for tower workstations, 5 for WWWs, 40 for EGA/VGA workstations)

inc if > 0, it increments black to white; if < 0, it increments white to black (default=1 for tower and EGA/VGA workstations, 2 for WWWs)</p>

start starting brightness value (default=0)
line starting TV line (default=bottom of the image minus 10 lines)

IR= 1 moves the IR or sounder imagery documentation

LMAG= line only blowup or blowdown

You cannot specify keyword ASIZE and parameter *locate* in the same command line.

The coverage of one TV frame on tower workstations and WWWs is 480 lines by 640 elements. The coverage on a VGA workstation is 350 lines by 640 elements.

You cannot copy areas with the DOS or OS/2 COPY command as you will lose calibration information.

Remarks

The coordinates for displaying images are listed below.

Location Reference	Y-coordinate	X-coordinate	Format
A	line	element	0 to 5 digits
E Submuse	latitude	longitude	DDD:MM:SS
the enurs age in I	line	element	0 to 5 digits

### **Examples**

### AA 101 2000 1 EC 38 90 -4

This entry copies area 101 to area 2000 and displays the image on image frame 1, earth centering it at 38° N and 90° W. It has a blowdown factor of 4.

### AA 101 2000 1 ASIZE=ALL IR=1

This entry copies the entire area 101 into area 2000, including IR/sounder imagery documentation. All other forms of AA do a line-by-line transfer of data subsections. The image is displayed on image frame 1.

### AA 104 2000 10 EC 36 90 2

This entry copies area 104 into area 2000 and displays the image on image frame 10. It is centered on earth coordinates 36° N and 90° W. The brightness values are averaged while making a two times blowup.

### AA 101 3000 OPP IU 5000 6000

This entry copies area 101 into area 3000 and displays it on the image frame opposite the displayed frame. The area is moved and displayed by upper-left corner image coordinates 5000 and 6000.

### AA 110 5000 OPP EC MSN

This entry copies area 110 into area 5000. It displays the area on the opposite image frame, centering it on Madison, WI.

### **AA 105 6512 ASIZE=ALL**

This entry moves the entire area 105 plus all bands to area 6512. It does not display the image.

## **AAMAP**

Remaps an area into a Mercator or polar stereographic projection.

**Format** 

AAMAP sarea darea frame projection clat clon res line ele [keywords]

Default

AAMAP sarea darea X projection clat clon
This entry remaps sarea into the specified projection, centering it on
clat and clon. It stores the remapped projection in darea but does not
display the remapped image.

**Parameters** 

sarea source area number of the data

darea destination area number; it must be different than sarea

frame image frame number for display; the data in darea is

displayed on this frame

0 does not display an image (default)

projection MERC remaps to a Mercator projection

PS remaps to a polar stereographic projection

clat center latitude

clon center longitude

res remapped image resolution in kilometers (default=1)

line number of lines in darea (default is workstation dependent)

ele number of elements in darea (default is workstation

dependent)

Keyword BAND= band number for multiband images

SPLINE= spline size (default=20)

Remarks Command AAMAP remaps any navigated image to a polar

stereographic or Mercator projection.

Example AAMAP 4960 6848 2 MERC 35 90 4

This entry remaps area 4960 into a Mercator projection centered on 35° N and 90° W. The new image, which has a resolution of 4 km, is

stored in area 6848 and displayed on image frame 2.

## ASK1

Defines a question to prompt the user for string input.

Format ASK1 row col color string [keyword] "question

Default No default; you must specify the parameters.

Parameters row of the display to use for the question; the range is

0-22 (default=1)

col column of the display to start the question; the range

is 0-79 (default=1)

color color for the question; the range is 0-255 (default=3)

string string name to place the user's answer in

"question the question to ask; quotes are required; use either

uppercase or lowercase letters

Keyword CLEAR= YES clears the display window before asking the

question

NO does not clear the display window (default)

Remarks Command ASK1 defines a question that prompts the user for a value.

The value is entered in the string named by ASK1. ASK1 is well suited for user interface tools like the F Key Menu System.

ASK1 always uses text window 8 to ask its question.

Full editing keys are available to change the string entry.

When you press the Enter key, everything that you typed following

the question on window 8 is placed in the string.

Example ASK1 10 15 14 PARA "Enter parameter to be plotted:

This entry prints 'Enter parameter to be plotted:' on row 10, column 15 in yellow. The result goes into string PARA in the current string

table.

## **AVGI**

Reduces image resolution by averaging.

**Format** 

AVGI sarea darea lres eres [keyword]

Default

AVGI sarea darea

This entry averages sarea by one line and element, and places the

new area in darea.

**Parameters** 

sarea

source area to average

darea

destination area of the averaged data

lres

number indicating the resolution reduction for lines

eres

number indicating the resolution reduction for elements

(default=lres)

Keyword

BAND=

band number from multibanded areas (default=lowest

numbered band)

Remark

The area size cannot exceed 26000 elements.

Example

AVGI 10 20 4

This entry blows down area 10 four times by averaging pixel values.

The new area number is 20.

power thought week hobbact to a mediantina band

B

Backs up one frame position.

Remarks

To go backwards through the frames,

Press: Alt B

name of the DOS file contains the commands

Type: B
Press: Enter

Stay in the local mode (H key off) while BATCH is running otherwise

equaring this McIBAS-OSS command: BATCH 101 3 "file

Revised 6/91

## **BATCH**

Executes McIDAS-OS2 commands serially from a text file.

**Formats** 

BATCH [keyword] "file

BATCH par1 par2 ... parn [keyword] "file

Default

No default; you must specify the file name.

**Parameters** 

"file name of the DOS file containing the commands

par1...n

value to substitute in the command text wherever the

notation % X appears

Keyword

DEST=

name of the text file to write commands into instead of

running them; the file contains the list of expanded commands and can be used by other programs.

C directs commands to the screen for viewing only

Remarks

The source file containing the commands must be in the DOS text format (i.e., lines must end with a carriage return or carriage return/linefeed) and must reside in the \MCIDAS\DATA subdirectory, unless you enter a fully qualified name that includes the disk drive and path. Most text editors place a carriage return or carriage return/linefeed at the end of each line.

Commands are performed serially, i.e., each must finish before the next one begins. This is NOT true, however, for commands beginning with a period (.). These commands are sent to the mainframe where they are performed in random order. BATCH does not wait for their completion before going to the next command line. If a command aborts, the entire BATCH file is abandoned at that point.

Normal string table substitution may be used within each command and will take place as the command is executed.

Stay in the local mode (H key off) while BATCH is running; otherwise all commands will be sent to the mainframe.

Example

If you have a BATCH file that contains the following command line:

DF %1 %2 EC MSN

entering this McIDAS-OS2 command: BATCH 101 3 "file will result in: DF 101 3 EC MSN.

## C

Lists an image frame's directory.

### Remarks

To list the current image frame's directory,

Press: ALT C

or

Type: C

Press: Enter

The output looks like this:

FRM SS YYDDD HHMMSS BAND LINE ELEM LMAGN EMAGN AREA 5 61 91042 91300 4 2923 41 1/ 3 1/ 5 1

Each of the columns is described below.

Column	Meaning		
FRM	image frame number		
SS	sensor source		
YYDDD	year and Julian day		
HHMMSS	image time		
BAND	band number		
LINE	first (uppermost) image line loaded into the image		
	frame		
ELEM	first (leftmost) image element loaded into the image		
	frame		
LMAGN	line magnification; the first number is the blowup		
	factor of the displayed data relative to the resolution of		
	the data in the area; the second number is the		
	blowdown factor of the displayed data relative to the		
	best sensor resolution		
EMAGN	element magnification; see LMAGN above		
AREA	area number		

### Remarks

If the area number is -1, the frame contains an image loaded from the mainframe. To list the mainframe image frame directory, type Alt C in the host mode. If an image is loaded on the PC, its frame directory will differ from the mainframe; the mainframe commands have no knowledge of the PC frame directory.

## CA

STYPE=

## Modifies the area directory.

Format	CA area par1 par2 par11 [keywords] "text			
Default	CA area par1par11 This entry changes the parameters in the area directory. Insert the letter X in places where you don't want to change the parameter.			
Parameters	area	digital area number for the directory you want to change		
	par1par 11	new directory values; insert the letter X to indicate no change		
	"text	the text to replace the memo portion of the area directory as seen by typing the command line:  LA area FORM=EXP; quotes are mandatory		
Keywords	BAND=	replaces the band sequence; the range is 1-32 NA means not applicable		
	CAL=	changes the length of the calibration section of the prefix		
	CTYPE=	changes the calibration type		
	DOC=	changes the length of the documentation section of the prefix		
	LEV=	changes the length of the level section of the prefix		
	NAV=	pri sec changes the primary and secondary codicil navigation pointers; for system navigation, enter: NAV=0 0		

Remarks

Parameters entered with the CA command replace the current values listed by typing: LA areas.

The values for keywords DOC, CAL and LEV must be multiples of four.

changes the source type

### **Example**

To change the line and element coordinates from 2162 and 9229 to 2100 and 9000, you must first list area 2. To do this,

Type: LA 2 Press: Enter

The system displays the following information on the screen.

area ss yyddd hhmmss Icor ecor Ires eres zres Isiz esiz zsiz bands 2 32 89128 164600 2162 9229 1 1 1 500 640 1 NA

To change the line and element coordinates,

Type: CA 2 X X X 2100 9000

Press: Enter

The area directory's LCOR and ECOR are changed to 2100 and 9000, respectively. The system displays the following information on the screen.

area ss yyddd hhmmss lcor ecor lres eres zres Isiz esiz 2 32 89128 164600 2100 9000 1 1 1 500 640 proj: 0 created:89128 173302 memo: AAA-MSI TO VIS IN REAL TIME type: VISR cal type: BRIT area offsets: data=768 navigation= 256 calibrations= 0 doc length: 0 cal length: 0 lev length: 0 PREFIX= valcod: 0 zcor: 1 band-8: NA reel#: 0 start yyddd: 89128 start time: 164602 start scan: 101

## CCODE

Lists country codes.

Format CCODE parm

Default CCODE

This entry lists all country codes.

Parameter parm country to list (default=ALL)

Remarks If parm is two characters, CCODE looks for the one country whose

code matches it. If more than two characters are specified, all string

matches are found.

Examples CCODE UK

This entry lists the country with UK as its country code.

CCODE FRANCE

This entry lists the country code for France.

CCODE ISLAND

This entry lists all country codes that have the word ISLAND in them.

CCODE Z

This entry lists all country codes that contain the letter Z.

## **CLEAR**

Clears a text window.

**Format** 

CLEAR bwin ewin

Default

CLEAR

This entry clears all text from the current window.

**Parameters** 

bwin beginning text window number to clear; the range is 0-4

(default=current)

ewin ending text window number to clear; the range is 0-4

(default=bwin)

**Examples** 

CLEAR 4

This entry clears text window 4.

CLEAR 2 3

This entry clears text windows 2 and 3.

## CM

### Generates a graphics movie.

**Format** 

CM blev elev [keywords]

Default

No default; you must specify the parameters.

**Parmeters** 

beginning graphics level to loop; the range is 1-7 blev

(default=1)

elev

ending graphics level to loop; the range is 1-7

(default=blev)

Keywords

GO=

YES starts looping immediately

NO does not loop immediately (default)

INT=

timing interval (looping speed) in milliseconds

(default=33)

TIMOUT=

sets the timeout (default=500 msec)

Remarks

Use command CM with tower and WIDE WORD workstations only.

CM creates a graphics movie that steps through the specified graphics color levels one at a time. Press the left mouse button to begin the movie, the right button to pause, and both buttons to stop the program. CM will hold an initiator until you press both mouse buttons.

See Also

Use CM with host command GMOVIE to animate streamlines.

**Examples** 

CM 2 6 INT=500

When you press the left mouse, the graphics will loop between levels

2 and 6, remaining on each color for 500 milliseconds.

CM 1 7

This entry loops graphics levels 1 to 7.

## **COLORS**

Displays the text window color table.

### Remarks

Command COLORS displays a color chart on text window 5.

The value for text color consists of a COLOR value, which is listed down both sides, and the ATTRIBUTE ADDITION VALUE which is listed along the top row only. The ATTRIBUTE VALUE is for reference purposes during software development.

For example, solid bright yellow is COLOR VALUE=14. A green background has an ATTRIBUTE ADDITION VALUE=32. Keyword TCOL colors any text window output and may be added to any command. To select the above combination, add the values, i.e., TCOL=46.

Colors 0-15 are the only available colors for mainframe commands.

### Example

### LWU LIST A TCOL=175

This entry displays the output from LWU in the current text window in flashing white letters on a green background.

Revised 9/91

## COTV

Contours the digital data within the cursor and produces a 2or 3-dimensional plot.

**Format** COTV interval unit [keywords]

Default COTV

> This entry contours the entire brightness range of the digital data within the cursor with an interval of 1 count. The 2-dimensional plot

is plotted in color level 1.

**Parameters** interval contour interval number; do not use this parameter

with a 3-dimensional plot (default=1)

BRIT unit brightness value (default)

> RAD radiance TEMP temperatures

Keywords BAND= band number of the area; the range is 1 to 9, A, B and (General)

C where A=10, B=11 and C=12 (default=current image

band)

COLOR= color level; the range is 1-7 (default=1)

DIM= draws a 2-dimensional display within the cursor

draws a 3-dimensional histogram

OPTION= digital data counts (default)

G 2-dimensional gradient

RANGE= beg end range of values to contour (default=0-255)

Keywords LMOD= labels every line

(2-Dimensional Only) labels alternate lines (default)

> SIZE= height of the labels in pixels (default=6)

SMO= smooths contours (default=20) **Keywords** (3-Dimensional Only)

ELE=

min max

element limits for the plot

(default=50 600)

ELV=

elevation viewing angle (default=20)

LINE=

min max

line limits for the plot (default=50 450)

PAN=

graphics panel number; the range is 1-4

ROT=

rotation angle (default=45)

Remarks

You may need to blow up the image resolution when using 2-dimensional contours. Otherwise, the plot inside the cursor may be too cluttered to read. You can use a maximum of 10,000 pixels within the cursor when plotting.

The maximum cursor size on a WWW is 256 x 256 pixels.

**Examples** 

COTV 3 COLOR=3

This entry contours the data inside the cursor every 3 counts in color

level 3.

COTV DIM=3

This entry draws a 3-dimensional histogram of the data within the

cursor.

## **CTRL**

Sends control characters to a modem.

**Format** 

CTRL "codes

Default

No default; you must specify the codes.

**Parameter** 

"codes

the letters corresponding to the ASCII control codes; quotes

are mandatory

Remarks

Use this command to send ASCII control characters to the asynchronous communications device. It is useful for those

installations requiring special codes for establishing communications. You may also use it to cause an escape condition in Hayes-compatible

modems.

**Examples** 

CTRL "ABC

This entry sends CTRL A, CTRL B and CTRL C to the modem.

CTRL "+++

This entry sends three plus signs, which is often useful with modems.

## CUR

Defines cursor size, type and color.

**Formats** 

CUR height width type color

(use with tower or WWW)

CUR height width type blue green red

(use with tower or WWW)

CUR height width type number

(use with VGA)

CUR option

Default

CUR

This entry displays a 31 x 31 red crosshair cursor on tower

workstations and WWWs; it displays a 31 x 31 crosshair cursor in the

current color level on a VGA display.

**Parameters** 

height

cursor height in pixels; even size is rounded up to odd size;

if entered as X, the size does not change (default=31)

width

cursor width in pixels; even size is rounded up to odd size;

(default=height)

type

BOX

box cursor

XHAIR

crosshair cursor (default)

**XBOX** 

crosshair inside box cursor

SOLID

solid box cursor (tower and WWWs only)

BULL

external crosshair with bullseye cursor (tower

and WWWs only)

color

color name from the color palette; tower workstation or

WWW only (default=RED)

blue

blue color intensity; the range is 0-255 (default=0)

green

green color intensity; the range is 0-255 (default=0)

red

red color intensity; the range is 0-255 (default=255)

number

VGA workstation color level; the range is 0-15 (default=2)

option

on

**OFF** 

makes the cursor visible (default)

makes the cursor invisible

Remarks

Options vary among PC configurations.

CUR is a reflected command, meaning it runs locally even if a dot is placed in front of it.

To list the VGA workstation color levels, enter: GU TABLE. To list palette colors and gun intensities for tower workstations and WWWs, enter: GU COLORS.

Even cursor sizes are always rounded to the next odd number. It is not possible to use even-sized cursors.

### **Examples**

### CUR 21

This entry makes the current cursor 21 x 21 pixels.

### CUR 20 40 BOX GREEN

This entry changes the cursor to a green box, 21 x 41 pixels, on a tower workstation or WWW.

### CUR 40 30 XBOX BLUE

This entry makes a 41 x 31 pixel, blue, crosshair inside box cursor on a tower workstation or WWW.

### CUR X 53 XHAIR

This entry makes a crosshair cursor. The width of the cursor is 53, the height and color do not change.

### CUR 32 25 BOX 45 15 25

This entry makes a 33 x 25 box cursor colored by 45 blue, 15 green and 25 red color intensities on a tower workstation or WWW.

### CUR OFF

This entry makes the cursor invisible.

## CW

Fills or erases the graphics within the cursor.

**Format** 

CW level frame height width

Default

 $\mathbf{C}\mathbf{W}$ 

level

This entry erases the graphics within the cursor.

**Parameters** 

graphics color level; the range is zero to the maximum

available for the display type (default=0 to erase all graphics

within the cursor)

frame

graphics frame number (default=current)

height

height of the area to erase in pixels (default=cursor height)

width

width of the area to erase in pixels (default=cursor width)

See Also

Use the EG command to erase the entire graphics frame.

Examples

CW 1 3

This entry fills the cursor with color level 1 on graphics frame 3.

CW 6 2 50 30

This entry fills a 50 x 30 box centered at the cursor with color level 6 on graphics frame 2.

## D

Lists the digital values at the cursor center.

### Remarks

To list the digital brightness value of the image pixel under the cursor's center,

Press: Alt D

 $\mathbf{or}$ 

Type: D
Press: Enter

The D command lists area number, area coordinates, image coordinates, Raw digital values, brightness values, radiance, and blackbody temperature for appropriate data sources.

This command does not execute if the area is not on your disk.

## **DEFLOOP**

Lists, saves and restores the workstation's loop state.

**Format** 

DEFLOOP LIST bloop eloop

DEFLOOP SAVE loop "label

DEFLOOP REST loop

Default

No default; you must specify a set of parameters.

**Parameters** 

LIST lists the directory of saved display states

SAVE saves the state of display

REST restores a previously saved display state

bloop beginning loop to list (default=all defined loops)

eloop ending loop to list (default=beloop)

loop loop number to save or restore; the range is 1-99

"label to be saved with the loop state; 48 characters

maximum including blanks

Remarks

DEFLOOP saves the state of the workstation display by saving the display parameters in User Common. This includes loop bounds, commands set by TERM, enhancements, graphics and cursor state and the nortel key (N).

DEFLOOP and F Key Menu pseudocommands \*R and \*S have the same basic function of saving the state of your workstation display. They also use the same filing system to save loops.

Loop state information saved with DEFLOOP is displayed with the MOVIE command. For WWWs, video channel 2 may be used independently of the main display by using an ASCII keypad connected to serial port COM3; keys 1-9 recall loops 1-9 only.

If you use a briefing frame on the WWW that uses imbedded graphics, use the SG and SF commands before saving the loop state. Display state data is stored in the file CONTEXT.SLT in \MCIDAS\DATA.

### **Examples**

### DEFLOOP SAV 3 'East US visible hourly

This entry saves the workstation's current display state as loop number 3 with the label 'East US visible hourly.'

#### **DEFLOOP RES 27**

This entry restores loop 27 and displays its label if one was specified. The LS, DR and F commands may be used to interrogate the state.

## DEFLOOP LIST

This entry lists loop numbers and labels for loops saved with a label.

## DF

### Displays a digital area on an image frame.

**Formats** 

DF area frame locate y-coord x-coord mag repeat [keywords]

DF area frame locate station mag repeat [keywords]

Default

DF area frame

This entry displays the *area* digital data on the image *frame* number, displaying the upper-left corner of the area in the upper-left corner of the image frame.

**Parameters** 

area digital area number of the data to display

frame image frame number to display

OPP displays the image on the opposite image frame

locate

coordinate type for loading images (default=AU, meaning the area coordinates are displayed with the upper-left corner line and element); use one of these coordinate systems:

A area

E earth

I image

T TV (displays the image using the cursor location)

followed by one of these locations:

C centered

D lower-right corner

U upper-left corner

y-coord y-axis coordinate (default=upper-left corner of the area)

x-coord x-axis coordinate (default=upper-left corner of the area)

station ID, e.g., MSN, DSM, 2C2; must be preceded by EU,

EC or ED

mag image blowup or blowdown factor (default=1)

repeat number of consecutive frames loaded from consecutive

areas (default=1)

Keywords

BAND= area band number; the range is 1-9, A, B and C where A=10, B=11, C=12 (default=8 for VAS; 4 for AVHRR)

CAL= QTIR the calibration module name; use QTIR for a fast POES load (default is from the area directory); the first calibration is used for the entire image; the digital area is unaffected

EMAG= element blowup or blowdown (default=1)

EU= name.ET name of the enhancement to apply to the image

GRAY= OFF doesn't display a gray wedge (default)
YES adds a gray wedge to the bottom of the image using the defaults below; the range is 0-255 for WWWs,

0-63 for tower, 0-15 for VGA workstations

rep inc str lin

rep brightness repetition factor (default=5 for WWWs, 10 for tower workstations and 40 for VGA workstations)

inc if > 0, it increments black to white; if < 0, it increments white to black (default=2 for WWWs, 4 for tower workstations and 1 for VGA workstations)</p>

str starting brightness value (default=0)

lin starting TV line (default=the number of lines in that particular frame minus 23 lines)

INC= ainc finc area/ frame increments for repeat parameters

LEVELS= lev brange erange sets the VGA gray levels used for image

and graphics enhancements

lev gray shade levels used for an image; the range is 1-255 (default=13, where 13 levels are used for image levels and 3 for graphics; 14 levels for radar images

with no stretch table)

brange beginning of the gray range to change; the range is 0-255 (default=20 for no stretch for a satellite image; 0 for stretch for a satellite image or no stretch for a

radar image)

erange end of the gray range to change; the

range is 0-255 (default=250 for no stretch for a satellite image; 255 for stretch for a satellite image or no stretch for a radar

image)

LMAG= line blowup or blowdown (default=1)

SF= YES automatically sets the image frame to the frame to be loaded prior to the display (default=NO)

SU= name of the stretch table to apply to the image

UPDATE=ON checks to see if the image to be loaded is already displayed on the frame; if the image is already displayed, it won't be redisplayed (default=OFF)

Remarks

If more than 16 levels are specified in the *lev* option of keyword LEVELS, the available 16 gray shades are wrapped around. If the number of levels is a multiple of 8, all 16 shades are used; otherwise, 13 shades are used, allowing 3 for graphics colors.

DF displays images from areas up to 10,000 lines and elements in size. The coordinates for displaying images are listed below.

Location	Y-coordinate	X-coordinate	Format
Α .	line	element	0-5 digits
E uo lastini edi	latitude	longitude	DDD:MM:SS,
			DDD.fraction or the
			station ID
. I signa ben	line	element	0-5 digits
Т .	raster	pictel	0-3 digits

See Also

Use command EU or GU to restore a palette for VGA workstations.

Examples

### DF 1 10 EC 36.50 90.50 -4 2

This entry loads areas 1 and 2 into image frames 10 and 11, respectively. The images are centered at  $361/2^{\circ}$  North and  $901/2^{\circ}$  West, with a 4x blowdown.

### DF 4 2 ED MSN

This entry loads area 4 into image frame 2 with the lower-right corner centered on Madison, WI.

### DF 1 OPP GRAY=X

This entry loads area 1 (from the upper-left corner of area 1) into the image frame opposite the displayed frame and displays a gray wedge.

### DF 3 2 EC STL LEVELS=11 60 200

This entry displays area 3 on frame 2, centered on St. Louis. VGA workstations use 11 levels as the gray scale and 5 as graphics levels. The gray scale is stretched from approximately 60 to 200.

## DF 200 5 EC EGLL SF=YES GRAY=YES SU=BRITST

This entry displays area 200 on image frame 5, centered on London's Heathrow Airport. The image frame is displayed before the image is loaded on the screen. A gray wedge is displayed at the bottom of the image. The image is stretched by an existing stretch table called BRITST.

# DIST

Finds the distance on a satellite image.

Formats	DIST R	IR angle inc distance [keywords] OT angle inc distance [keywords] IE angle din distance [keywords] lat lon [keywords] line ele [keywords] raster pictel [keywords]
Default	DIST	
	This entr satellite i	y finds the distance between two points on a navigated mage.
Parameters	CIR	draws a circle around the initial cursor location beginning at a specified distance and angle
	ROT	draws all or part of a circle around the initial cursor location beginning at a specified distance and angle
	STE	steps the cursor away from the initial cursor location at a specified distance and angle
tageth and but West.	E	steps the cursor away from the initial cursor location by the specified latitude and longitude increments
	I s difw _ soon	steps the cursor away from the initial cursor location by the specified line and element increments
	T	steps the cursor away from the initial cursor location by the specified raster and pictel increments
adpan Auth z skepta	angle	moves the cursor away from the original location by this angle (default=0)
25 St. Louis, VGA 2 as graphics levels. 20 to 200	inc	increment (in degrees) to shift the cursor along its circular path
1711.608-U	distance	number of km to move the cursor from its original location
e'ncheal so beretan's believe the image is	din	increment (in km) to step the cursor along its straight-line path

positive

degrees of latitude to move the cursor; northward is

line number of lines to move the cursor; westward is positive

ele number of elements to move the cursor; rightward is positive

raster number of rasters to move the cursor; downward is positive

pictel number of pictels to move the cursor; rightward is positive

### Keywords

COLOR= graphics color level of the characters; the range is 1-7 (default=2)

SIZE = height of the plotted characters in pixels (default=5)

SYM=

- . a period marks off the distances (default)
- a plus sign marks off the distancesan asterisk marks off the distances
- o a lowercase letter O marks off the distances

### Remarks

Command DIST will not execute unless the satellite image is navigated. Each cursor location that you mark on the graphics frame is indicated by a period (default) or a symbol chosen with keyword SYM. Parameters ROT, STE, E, I and T run interactively. A symbol is plotted on the graphics frame at the new cursor location each time you press the left mouse button.

### **Examples**

Position the cursor at the point on your navigated satellite image that is the starting point of the calculation. Then,

Type: DIST Press: Enter

The program replies:

Press LEFT mouse button to measure point.
Press RIGHT mouse button to exit DIST.

Move the cursor to the point where you want the distance measured. Press the LEFT mouse button. The distance from the initial cursor location appears on the screen. Repeat this sequence to measure the distance from the initial cursor location to other points.

#### DIST CIR 45 30 100 SYM=\*

This entry draws a circle of asterisks on the graphics frame 100 km away from the original cursor location beginning at angle 45. The circle contains 12 asterisks since the increment is 30 degrees.

## DMAP

Lists the name and size of LW files.

**Formats** 

DMAP bstring estring

DMAP \*.ext

**Default** 

**DMAP** 

This entry lists the name and size of all LW files in the

\MCIDAS\DATA subdirectory.

**Parameters** 

bstring

beginning text string to search for (default=all)

estring

ending text string to search for (default=bstring)

\*.ext

lists all files with this extension; the asterisk cannot be

mixed with characters

Remarks

Command DMAP lists in the ASCII collating sequence.

An asterisk may be used as a wild card character when a file extension is explicitly given. No other ASCII characters can

accompany the asterisk.

**Examples** 

DMAP AREA0001

This entry lists information about the LW file AREA0001.

DMAP A C

This entry lists the LW files beginning with letters A, B and C.

DMAP MDXX0001 MDXX9999

minutes the configuration of the college for the following and the first and the first

This entry lists information about MD files 1 to 9999.

DMAP \*.MNU

This entry lists information about all files with the .MNU extension.

## **DOQTL**

### Selectively deletes MD files.

**Format** 

DOQTL bmdfile emdfile cutoff

Default

No default; you must specify the parameters.

**Parameters** 

bmdfile beginning MD file in the range (no default)

emdfile

ending MD file in the range (no default)

cutoff

maximum number of MD files kept on the system, in days

(no default)

Remarks

Command DOQTL allows you to delete unwanted MD files on the PC according to the specified cutoff. If cutoff=4, only the MD files for the last four days are retained on the PC; the rest are deleted. This assumes that the MD file allocation on the PC is the same schema as that on the mainframe, i.e., MD files 1 to 10 are for SVCA schema data, MD files 11 to 20 are for RAOB schema data, etc.

Example

DOQTL 1 30 2

If the current day is 91223, this entry saves MD files 2, 3, 12, 13, 22

and 23, and deletes the rest.

## **DOSTOLW**

Converts DOS format files to LW format files.

Format DOSTOLW sfile dfile R

Default No default; you must specify the files.

Parameters sfile source DOS file name and extension

dfile destination LW file name; it must be different than sfile

R replaces the destination file if it already exists

Remarks The LW file format is an 80-character card image, blank padded as

needed, with no carriage returns.

Example DOSTOLW SFCPLT.RUN SFCPLT

This entry converts the DOS file named SFCPLT.RUN to an 80-

character card image format LW file named SFCPLT.

## DR

### Defines the dwell rates for frame looping.

**Formats** 

DR rate1 rate2 ... raten

DR repeat\*rate repeat\*rate ...

DR INI DR AUTO

Default

DR

This entry lists the current dwell rates within the loop.

**Parameters** 

rate1...n

dwell rate for each frame (no default)

repeat

number of frames for which the rate applies (no default)

INI

initializes the dwell rates to 9 units for the first frame and 6 units for all subsequent frames

**AUTO** 

assigns the longest dwell to the latest image

Remarks

The rate is in units of 1/15 second for tower and WWWs, while it is PC-dependent for EGA and VGA workstations.

The last frame assigned a rate determines the rate for all subsequent frames in that loop. See the examples.

You can mix the command formats. For example, DR 3 3 5\*8 3 is the same as DR 3 3 8 8 8 8 8 3.

Set the dwell rates to compensate for irregularly spaced image times. Graphics frames within a loop are assigned dwell rates identical to image frames. EGA and VGA workstations do not differentiate graphics from image frames.

Examples

DR 12 6 6 12

This entry sets dwell rates to 6 for the second and third frames, and 12 for the first, fourth and all subsequent frames of the loop.

DR 3\*5 4 3

This entry sets dwell rates to 5 on the first three frames, 4 on the fourth frame, and 3 on the fifth and all subsequent frames of the loop.

DR 7

This entry sets all frames to dwell rate 7.

## Ε

Lists the earth coordinates at the cursor center.

#### Remarks

ole, DR S S S S S se

To list the earth coordinates at the cursor center,

Press: Alt E

or

Type: E Press: Enter

#### Command E lists:

- the latitude and longitude of a pixel on a displayed navigated image in the format HH:MM:SS
- satellite image line and element coordinates
- TV monitor raster and pictel coordinates; position raster=1 and pictel=1 is the upper-left corner of the screen; position raster=488 and pictel=640 is the lower-right corner of the screen

On tower workstations and WWWs, the E key lists the current image's coordinates. On EGA/VGA displays, the last displayed graphics or image is used.

The output format of E is shown below.

Frame	Latitude	Longitude	Tvline	Tvelem	Line	Elem
nn	DDD:MM:SS	DDD:MM:SS	nnnn	nnnn	nnnn	nnnn

## EB

### Invokes black and white contrast stretching.

**Format** 

EB inlo inhi outlo outhi

Default

 $\mathbf{EB}$ 

This entry invokes interactive mouse-controlled contrast stretching. Pressing the left mouse button begins the process. Pressing the right mouse button ends the process, leaving the current enhancement.

**Parameters** 

inlo lowest input brightness value (default=0)

inhi highest input brightness value (default=255)

outlo new low brightness value (default=0)

outhi new high brightness value (default=255)

Remarks

Use command EB with tower workstations and WWWs only.

The input brightness values correspond to the brightness levels of the imagery stored in the terminal refresh memory. Input brightness levels below *inlo* and above *inhi* are not changed. *Inlo* is output at level *outlo* and *inhi* at level *outhi*. Brightness values between *inlo* and *inhi* are output at levels determined by linear interpolation between *outlo* and *outhi*.

When using the mouse-controlled version, moving the cursor to the right along the x-axis decreases the upper brightness bound (from level 255) to be enhanced as white (255). Moving the cursor upward along the y-axis increases the lower brightness bound (from level 0) to be enhanced as black (0).

To save the current enhancement, use command EU SAVE.

**Examples** 

#### EB 50 150 0 255

This entry rescales input brightness level 50 as 0 (black) and input brightness level 150 as 255 (white). The 100 counts between 50 and 150 are linearly stretched along the 255 counts between 0 and 255.

#### EB 30 255 50 200

This entry rescales input brightness level 30 as 50, and input brightness level 255 as 200. The 225 counts between 30 and 255 are linearly stretched along the 150 counts between 50 and 200.

## **ECHO**

Displays a line of text on the workstation.

**Format** 

ECHO "text

Default

**ECHO** 

This entry echoes a blank line.

**Parameter** 

"text the text to display on the screen; the quote is mandatory

Remark

You will use ECHO primarily in a RUN command.

Example

ECHO "This is a test

This entry prints 'This is a test' on the screen.

## EG

### Erases graphics frames.

Formats .....

EG bframe eframe [keyword]

EG I bframe eframe (use with EGA/VGA workstations only) EG B bframe eframe (use with EGA/VGA workstations only)

Default

EG

This entry erases the current graphics frame.

**Parameters** 

bframe beginning frame in the range to erase (default=current)

eframe ending frame in the range to erase (default=bframe)

I erases graphics and image frames on EGA/VGA displays and back planes

B erases graphics and image frames on EGA/VGA displays only; the back plane is not erased

Keyword

LEV=

specifies a level number (bit plane) to erase; the range is

1 to 8 (use with WWWs only)

Remarks

The I and B erase options are only valid on EGA/VGA workstations if you select the SAVE IMAGE FRAME option during the SETUP procedure. When you select this option, a copy of the image portion of the display is saved in a file referred to as the "back plane." During an EG command, graphics are deleted from the display by restoring the image saved in the back plane. This gives the impression of separate image and graphics frames. Entering the B option in an EG command will erase the display only. Since the image still exists in the back plane, it can be redisplayed by entering an EG command. The I option erases both the display and the back plane.

If you have an EGA/VGA workstation, you must enter the command below when you boot up the system for the first time after installing software. Otherwise, the graphics will not appear correctly on VGA frames.

Type: EG I 1 maximum number of frames on your workstation

Press: Enter

### **Examples**

### EG 6 12

This entry erases graphics frames 6 through 12.

### EG I 2 3

This entry erases the graphics and images on frames 2 and 3 on EGA/VGA displays and back planes.

### EG B 2 3

This entry erases the graphics and images on frames 2 and 3 on EGA/VGA displays; the back plane is saved.

### EG LEV=3

This entry erases color level 3 on the current graphics frame on a WWW.

## ET

Provides pseudocoloring for image frame overlays.

**Formats** 

ET NOR

ET option table1 table2

ET CUR scale

ET TIN scale ry yg gc cb bm

ET CON vlo vhi irlo irhi scale ry yg gc cb bm

Default

No default; you must specify a set of parameters. Enter X for each desired parameter default; press N to display the pseudocoloring frame overlay.

**Parameters** 

NOR coloring for false stereo which combines straight red with a straight green enhancement table

CUR uses the current enhancement of the IR image (created

with command EU) to color the overlay of the IR and

visible images

TIN

colors the visible sensor image with the information derived from the IR image; although the colors are predefined, you can select the breakpoints and saturation

CON

colors the visible sensor image with the information derived from the IR image; only brightness values falling within both thresholds are colored; the colors are predefined, but you can choose the breakpoints and thresholds

option

AND logical AND
MUL geometric mean

OR logical OR

SUB arithmetic difference

table1

pseudocoloring table, the range is 1 to 256; it is saved with

the EU command (default=current)

table2

pseudocoloring table, the range is 1 to 256; it is saved with the EU command (default=frame opposite the current

frame)

scale

color depth, the range is 1 to 10 (default=5)

ry the point in the opposite frame scale to change from a red to a yellow tint; the range is 0-63 for tower workstations and 1-255 for WWWs yg the point in the opposite frame scale to change from a yellow to a green tint; the range is 0-63 for tower workstations and 1-255 for WWWs the point in the opposite frame scale to change from a gc green to a cyan tint; the range is 0-63 for tower workstations and 1-255 for WWWs the point in the opposite frame scale to change from a cyan to a blue tint; the range is 0-63 for tower workstations and 1-255 for WWWs bmthe point in the opposite frame scale to change from a blue to a magenta tint; the range is 0-63 for tower workstations and 1-255 for WWWs vlolowest visible threshold; the range is 0-63 for tower workstations and 1-255 for WWWs vhihighest visible threshold; the range is 0-63 for tower workstations and 1-255 for WWWs irlo lowest IR threshold; the range is 0-63 for tower workstations and 1-255 for WWWs irhi highest IR threshold; the range is 0-63 for tower workstations and 1-255 for WWWs

### Remarks

The ET command generates a color enhancement table (also called a pseudocoloring table) for overlaying TV frames. Not all terminals have the pseudocoloring hardware.

Use the N key to toggle the table in and out of the video refresh data path. When the table is in the data path, two video frames are combined pixel by pixel and the combination is displayed on the TV monitor. The pixel value from the current frame is indexed into the rows of the table, while the pixel value from the frame opposite the current frame is indexed into the columns of the table. The value at the intersection contains the red-blue-green levels to display for this pixel. A common application is to tint clouds in varying colors according to height. In this case, the opposite frame displays an IR image complementing the current visible picture.

To construct a pseudocoloring table, use the EU command to generate and save two enhancement tables. Call them TF and TO and call the pseudocoloring table T12. The ET command generates T12 as follows:

$$T12 (R,C) = F (TF (R), TO (C))$$

Combining the two images depends on function F which takes the form of one of the following:

 $F = OR \qquad T12 (R) . OR . TO (C) (Logical OR)$   $F = AND \qquad T12 (R, C) = TF (R) . AND.TO (C) (Logical AND)$   $F = SUB \qquad T12 (R, C) = TF (R) . TO (C) (Arithmetic Difference)$   $F = MUL \qquad T12 (R, C) = TF (R) \times TO (C) (Geometric Mean)$ 

This method of generating the table applies the designated function to the two frames, pixel by pixel. The result is displayed on the screen. For example, if you use a straight line red pseudocoloring for TF and a straight line green pseudocoloring for TO, the combination produced by ET places both frames on the screen simultaneously, one in red and the other in green. The pseudocoloring hardware is a specialized high speed computer for performing pixel rate computations on two images at one time. The pseudocoloring table contains the program for the computations.

#### **CON Enhancement**

The CON (deep CONvection) enhancement is similar to the TIN method described below, except it also accepts IR and visible input thresholds. Assume a visible image is placed on a frame and the corresponding IR image on its opposite frame. The CON option lightly colors the visible image based on the IR data. It enhances only the image data that falls within both the visible and IR thresholds. The color scheme is based on five color breakpoints which may or may not fall within the IR threshold. The lowest shading of the IR is red. The visible input threshold enables you to differentiate between deep convection cloud tops and high cirrus, indistinguishable from the IR data alone.

#### **TIN Enhancement**

The TIN (cloud height TINting) enhancement sets up a special table to achieve the following effect. Assume the current frame contains a GOES image from the visible sensor and the opposite frame contains the corresponding image from the IR sensor. The TINT table lightly colors the visible sensor image with information derived from the IR image. The lowest values of IR tint the visible image with red, followed by yellow, green, cyan, blue and magenta. Since the brightness values in the IR correspond roughly to temperature, and temperature to height, the color tint of the visible image is an indication of cloud height.

You can control the color depth of the tint and breakpoints of the ry, yg, gc, cb and bm changes in the IR brightness scale.

### **Examples**

In the following examples, press the N key to display the pseudocoloring frame overlay.

#### ET NOR

This entry applies red and green pseudocoloring to view a false stereo image with red and green glasses.

#### ET SUB 1 2

This entry generates a new overlay by subtracting pseudocoloring save table 2 from 1.

### ET CUR 3

This entry uses the current pseudocoloring on the IR image to tint the visible image. The 3 lightens the color saturation.

#### ET TIN X 20 30 40 50 60

This entry uses the default saturation to tint the overlay using brightness breakpoints 20, 30, 40, 50 and 60.

## EU

### Enhancement utility.

**Formats** EU COLORS EU DEL name EU LIST EU MAKE lo hi bcolor ecolor bframe eframe EU MAKE lo hi bcolor ecolor [keyword] EU MAKE lo hi blo bhi glo ghi rlo rhi bframe eframe EU MAKE lo hi blo bhi glo ghi rlo rhi [keyword] EU REST name bframe eframe EU REST name [keyword] EU SAVE name EU TABLE name Default  $\mathbf{EU}$ This entry restores the default enhancement to the current frame. **Parameters** COLORS lists the defined colors DEL deletes a saved enhancement LIST lists all saved enhancements on the PC MAKE sets the enhancement. REST restores a saved enhancement SAVE saves the current enhancement **TABLE** 

lists the values of an enhancement (default=current)

nameenhancement name (default=default enhancement)

lo lowest brightness value; the range is 0-255 (default=0)

hihighest brightness value; the range is 0-255 (default=255)

bcolor, ecolor color name range

bframe beginning video frame (default=current image frame)

eframe ending video frame (default=bframe)

## EU

### Enhancement utility.

**Formats** 

EU COLORS

EU DEL name

EU LIST

EU MAKE lo hi bcolor ecolor bframe eframe

EU MAKE lo hi bcolor ecolor [keyword]

EU MAKE lo hi blo bhi glo ghi rlo rhi bframe eframe

EU MAKE lo hi blo bhi glo ghi rlo rhi [keyword]

EU REST name bframe eframe

EU REST name [keyword]

EU SAVE name

EU TABLE name

Default

EU

This entry restores the default enhancement to the current frame.

**Parameters** 

COLORS

lists the defined colors

DEL

deletes a saved enhancement

LIST

lists all saved enhancements on the PC

MAKE

sets the enhancement

REST

restores a saved enhancement

SAVE

saves the current enhancement

**TABLE** 

lists the values of an enhancement (default=current)

name

enhancement name (default=default enhancement)

lo

lowest brightness value; the range is 0-255 (default=0)

hi

highest brightness value; the range is 0-255

(default=255)

bcolor, ecolor color name range

bframe

beginning video frame (default=current image frame)

eframe

ending video frame (default=bframe)

blo lowest blue gun intensity value; the range is 0-255 (default=0) bhihighest blue gun intensity value; the range is 0-255 (default=0) glo lowest green gun intensity value; the range is 0-255 (default=0) ghi highest green gun intensity value; the range is 0-255 (default=0) rlolowest red gun intensity value; the range is 0-255 (default=0) rhihighest red gun intensity value; the range is 0-255 (default=0) Keyword LOOP= YES applies the enhancement to all frames defined in a loop NO does not apply the enhancement (default) The files created when you execute an EU SAVE are transportable to Remarks any PC-based workstation via the SENLW command or diskette. **Examples** EU LIST This entry lists all the saved enhancement tables on the terminal. EU MAKE 20 75 255 255 0 0 255 255 This entry color enhances all image pixels with brightness values between 20 and 75 to solid magenta.

### EU MAKE 100 200 RED YELLOW 1 3

This entry color enhances the image pixel brightness values between 100 and 200 on image frames 1 to 3 from red to yellow.

#### EU SAVE VAPOR

This entry saves the enhancement on the current frame to a file named VAPOR.

### EU REST VAPOR LOOP=YES

This entry restores an enhancement called VAPOR to all frames defined in a loop.

### **EU TABLE**

This entry lists the values of the current enhancement.

## **EXIT**

Exits McIDAS-OS2 to the OS/2 operating system.

### Remarks

Because you can run OS/2 commands in McIDAS-OS2, you will not ordinarily need to use the EXIT command.

To return to McIDAS-OS2 after an EXIT,

Type: MCIDAS
Press: Enter

If you have a serial interface on your printer, you cannot send output to the printer while in OS/2 unless you redirect the printer output with the following command.

Type: MODE LPT1=COM1

Press: Enter

When returning to McIDAS-OS2, boot the PC to direct the printer output back to its default device.

Do NOT use the Presentation Manager "Close" option to stop the entire McIDAS-OS2 session; doing so is likely to prevent other workstations on the same ProNET ring from working properly. To remove the entire session, first use the McIDAS-OS2 EXIT command. When you receive the OS/2 command prompt,

Type: EXIT Press: Enter

The final lines of the output formet describe the aumber and also of

This terminates the OS/2 session. Boot your computer to restart McIDAS-OS2.

### F

Displays the video terminal status.

#### Remarks

To list the workstation status,

Press: Alt F

or

Type: F Press: Enter

This command is reflected back to the PC.

The output format of F is shown below.

	Image Frame(	s) Graphics Frame(s)
Number Available	nn	nn
Current	nn (Opp=nnn	n) nn
Loop Bounds via LB	n to n	n to n
Random Looping via LS	Yes/No	Yes/No
Visible (K & W toggle)	Yes/No	Yes/No
Connected (Y & J toggle)	Yes/No	Yes/No
Looping (L toggle)	Yes/No	Yes/No
Cursor parameters: Size	nnn/nnn	Type =cursor type
Center position		Color=color

The F command will not display the <u>Graphics Frame(s)</u> column on a VGA workstation since image and graphics frames are identical on a VGA workstation.

If you use the command LB to set image or graphics loop bounds, the table indicates the loop bound set. If you use the command LS to set the loop bounds, random looping is in effect. In this case, you can enter LS or LS G to list the current loop definition.

The final lines of the output format describe the number and size of the image and graphics frames. These values vary depending on your workstation. If you have a WWW, you can redefine the frame allocation. See Appendix A in this manual for instructions.

### See Also

Use commands K, W, J, Y and L to modify the loop control system. Command K toggles the image on/off. W toggles the graphics on/off. J toggles the graphics loop control on/off. Y toggles the image loop control on/off. L toggles the image and graphics looping on/off.

Use command U to list the host terminal number (see the McIDAS Reference Manual).

## GD

### Sets graphics display parameters.

Format

GD INI

GD width dlength gcolor glength

Default

GD

This entry lists the current graphics parameters.

**Parameters** 

INI initializes the graphics parameters to their logon values

width graphics line width in pixels (default=last value set; at

logon the default is 1)

dlength length of the dashes in a line (default=last value set; at

logon the default is 10 pixels)

gcolor color level of the gaps in dashed lines; the range is 0-7 for

tower and WWWs, 0-3 for VGA workstations (default=last

value set; at logon the default is 0, no color)

glength length of the gaps in dashed lines (default=last value set;

at logon the default is 10 pixels)

Example

GD 3 5 3 5

This entry sets the line width to 3 pixels. The length of dashes and gaps in the dashed lines is 5 pixels. The color of the gaps is set to

color level 3.

## **GRDIMG**

Converts a grid to a TV image.

**Format** 

GRDIMG grid area rmag cmag [keywords]

Default

GRDIMG grid area

This entry places grid in digital area using the minimum and maximum grid values to determine the digital value range.

**Parameters** 

grid source grid number

area destination area number generated by GRDIMG

rmag grid row magnification factor for the blowup (default=1)

cmag grid column magnification factor for the blowup (default=1)

Keywords

COL= begin end beginning and ending column limits

(default=1 maximum column)

GRIDF= grid file number (default=current or that set by

IGU SET gridf)

RANGE= low value high value low bright high bright

specifies the range of grid values

low value lowest grid data value (default=minimum

value)

high value highest grid data value (default=maximum

value)

low bright lowest digital brightness value (default=0)

high bright highest digital brightness value (default=255)

ROW= begin end beginning and ending row limits

(default=1 maximum row)

Remarks

The maximum grid size is 120 columns. Use keyword COL to specify a subset. The maximum element size is 640. Use a smaller column magnification or specify keyword COL if an error results.

Example

GRDIMG 1 5000 RANGE=270 300

This entry places grid 1 in area 5000. The grid is 20 by 20 and contains temperatures (K). The temperatures from 270 to 300 K take on digital values ranging from 0 to 255. All values below 270 are 0; those above 300 are 255.

## GU

### Graphics utility.

**Formats** 

GU COLORS

GU DEL name

GU LIST

GU MAKE level color bframe eframe

GU MAKE level blue green red bframe eframe

GU OFF level bframe eframe GU ON level bframe eframe

GU REST name bframe eframe

GU SAVE name frame

GU TABLE name

Default ( ) ( ) ( ) ( ) ( ) ( )

GU not retent moltanting

This entry restores the default graphics file to the current graphics

frame.

**Parameters** 

COLORS

lists the predefined colors

DEL

deletes a graphics file

LIST

lists all saved graphics files on the PC

MAKE

sets the graphics levels

OFF

turns a graphics level off; use with tower workstations

and WWWs only (default=turns all levels off)

 $\mathbf{ON}$ 

turns a graphics level on; use with tower workstations

and WWWs only (default=turns all levels on)

REST

restores a saved graphics file

SAVE

saves the current graphics file

**TABLE** 

lists the values in a graphics file (default=current)

name

graphics file name; on VGA workstations and WWWs,

the file name does not include an extension, e.g., .GRA,

ET.

level

graphics level number (default=0-7 for tower

workstations, 1-8 for WWWs, 1-15 for VGA displays)

color predefined color bframe beginning graphics frame number; use with WIDE WORD and VGA workstations (default=current) eframe ending graphics frame number; use with WIDE WORD and VGA workstations (default=bframe) blue blue color gun intensity; the range is 0-255 (default=0) green color gun intensity; the range is 0-255 (default=0) green redred color gun intensity; the range is 0-255 (default=0) frame graphics frame number; use with WIDE WORD and VGA workstations (default=current)

### **Examples**

### GU MAKE 7 WHITE 1 3

This entry sets graphics color level 7 to white for graphics frames 1 to 3.

### GU OFF 7 1 3

This entry turns graphics color level 7 off on graphic frames 1 to 3 only.

### **GU TABLE**

This entry lists the values in the current graphics file.

## H

Toggles the host command entry mode on and off.

### Remarks

To toggle the host command entry mode on and off,

Press: Alt H

or

Type: H Press: Enter

An H appears on the status line whenever the ProNET or asynchronous communications encounters a connect condition.

Most commands will execute on the host when the H key is toggled on. Some commands, primarily loop controls and enhancement commands, are either intercepted by the PC or reflected by the host and run on the PC.

The system automatically inserts a period before any command that you manually enter while in the host mode.

While in the local mode, with no H on the status line, precede any host command with a period or it will attempt to run locally.

You must enter a period (.) before all commands in the scheduler or string table that will run on the host.

## HELP

Lists the on-line help for McIDAS-OS2 commands.

**Formats** 

HELP command

HELP 'McBASI command

Default

HELP

This entry lists the currently supported McIDAS-OS2 commands.

**Parameters** 

command

the McIDAS-OS2 command name

'McBASI command

a McBASI command name preceded by a single

quote

Remarks

To list mainframe command documentation, precede HELP with a

period, e.g., .HELP LA.

McBASI programs are assumed stored in the \MCIDAS\DATA

subdirectory.

The HELP command can be invoked while entering a command from

the keyboard. After you type the command name,

Press: ALT?

An abbreviated help is displayed on the window; the full text is

displayed on window 5.

See Also

For more information about commands, see the McIDAS Reference

Manual or the McIDAS Applications Guide.

**Examples** 

HELP CUR

This entry lists the on-line documentation for McIDAS-OS2 command

CUR.

HELP WHO

This entry lists the help for the McBASI program WHO.

## **IGG**

### Grid utility.

**Formats** 

IGG DEL bgrid egrid [keywords]

IGG LIST bgrid egrid [keywords]

IGG GET sgridf bgrid egrid dgridf bgrid

IGG MAKE grid1 option1... gridn optionn [keywords]

**Defaults** 

IGG LIST

This entry lists all the grids in your workstation's default grid file.

IGG DEL

This entry deletes grid one in the default grid file.

**Parameters** 

DEL

deletes grids

LIST

lists grids

GET

moves grids from one file to another or within the same file

MAKE

arithmetic operations performed on the grids; see option

below

**bgrid** 

beginning grid number

egrid

ending grid number

sgridf

source grid file number (default=terminal number, or from

IGU SET gridf)

dgridf

destination grid file number

grid1..n

a grid number

option1...n ABV

creates a grid of vorticity when the grid is u-comp (grid + 1 = v - comp) with the coriolis force; the second grid in the command is not used; units are

 $10^{-5} \, \text{sec}^{-1}$ 

 $\mathbf{ADD}$ 

adds grids on a point-by-point basis

ADV

advects the parameter specified as the second grid

by the wind of the first grid (u-comp assumes

grid + 1 = v - comp

AVG averages grids

CHGT changes the values greater than the value of the second grid

CHLT changes the values that are less than the value of the second grid

COM compares two grids for overlapping values; for a threat score, the second grid should be followed by two numbers that specify the range of values to include, e.g., MAK 12 COM 18 -500 500

COR creates a grid of the coriolis force using the boundaries of grid1

DIV divides grids

DSH for deformation shear when the grid is u-comp (grid + 1 = v - comp); the second grid is not used

DST for deformation stretch when the grid is u-comp (grid + 1 = v - comp); the second grid is not used

DVG creates a grid of divergence when the grid is u-comp (grid + 1 = v - comp); units are 10<sup>-6</sup> sec <sup>-1</sup>; if you specify a second grid, the divergence of that parameter is computed; if the second grid is 0, type ZERO for that grid

FIL creates a grid with the specifications of the first grid but fills it with the value specified for the second grid, e.g., MAK 12

GEO creates u and v component grids of the geostrophic wind; grid1 must be a height grid

MPY multiplies points by a value

RMS computes RMS and bias differences of two named grids

SPD creates a grid of wind speed; grid input is u-comp (grid + 1 = v - comp); the second grid is not used; it is not linked to u and v grids; it can be used with any two successive grids to reproduce a grid of the square root of the sum of the squares

SQR square root; applies to the first grid only

Revised 9/91

SUBsubtracts values from each point VOR creates a grid of vorticity when the grid is u-comp (grid + 1 = v - comp); units are  $10^{-6}$  sec<sup>-1</sup>; the second grid in the command is not used Keywords ADD= YES includes an additional term for divergence (default) NO does not include an additional term for divergence DGRID= destination grid number for MAKE parameter (default=next available grid) GRIDF= grid file number to work on (default is from IGU SET gridf) LAB= labels the resulting grid (default depends on operation) PLANET= planet name (default=earth) SMO= smooths the resulting grid (default) YES NO does not smooth the resulting grid number of the v grid to input if it does not follow the u grid (default=u grid + 1)

#### Remarks

For arithmetic functions (ADD, SUB, MPY, DIV), the second named grid may be negative. The absolute value is treated as a constant, not as a grid.

To plot grid points on a line printer, enter: IGTV grid X map 3.

The CRT format of the grid directory is as follows.

Column	Format
1	grid number
2 sulava	year, Julian day
3	hours, minutes, seconds of the grid
4 Milb and	name of the gridded parameter
5	description of the atmospheric level and units
6	name of the program that generates the grid
7 been by	hours that the forecast grid is valid after generation
8	number of rows in the grid
9	number of columns in the grid
10	latitude and longitude of the upper-left corner; it will
	be PS if polar stereographic
11	row grid spacing in degrees
12	column grid spacing in degrees

### **Examples**

IGG GET 10 5 7 20 1

This entry moves grids 5, 6 & 7 from grid file 10 into grid file 20, starting at grid 1.

IGG LIST 1 20

This entry lists all grids from 1 to 20 from the default grid file.

IGG MAKE 2 SUB 1

This entry creates a new grid by subtracting grid 1 from grid 2.

IGG MAKE 2 MPY 4 ADD 5 DIV 60

This entry creates a new grid by multiplying each grid point in grid 2 by 4, adding them to grid 5 and dividing by 60.

## **IGTV**

Generates contours and streamlines from grids.

**Format** 

IGTV grid interval map output [keywords]

Default

IGTV grid

This entry contours grid and displays it with a contour interval of 2.

**Parameters** 

grid u-grid component grid number to contour

interval contour interval; intervals must be factors of ten, e.g., 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 20, 30 . . . (default=2)

enter a string name with up to 64 values

map DEF defines your own boundaries; use LAT and

LON keywords (default)

MID Midwest USA map

NA North American map

NONE does not draw a map

SAT satellite projection

USA USA map Post Office Abbreviation

output if DEV=C or P, use 1 to display contours, 2 to display the

grid and contours, 3 to display grid points on the CRT or

printer

Keywords

CMAP= map color level; the range is 1-7 (default=1)

COLOR= graphics contour color level; the range is 1-7 for solid lines,

-1 to -7 for dashed lines; no map is drawn with negative

numbers (default=2)

DASH= NEG dash negative contours only

POS dash positive contours only

ALL dash all contours

DEV= C displays grid points to the CRT

P displays grid points to the printer

ELE= graphics TV element bounds

FRA= image frame number (default=current)

GRA= graphics frame to display the plot (default=current)

GRIDF= grid file number (default=current)

LAT= min max minimum and maximum latitude extents

LIN= graphics TV line bounds

LINT= contour label interval (default=labels each contour)

LON= min max minimum and maximum longitude extents

LSIZE= height of the contour labels in pixels (default=7)

MAG= magnifies the data values (default=0)

PAN= panel number; the range is 1-4

PRO= CONF conformal projection MERC Mercator projection (default)

scale for conformal projection, maximum of 108 (a ratio. SCALE= e.g., 30); multiply values under 1,000 by 1,000,000

SF= YES displays image/graphics frame (VGA only)

SLAT= lat1 lat2 standard latitude; for polar stereographic specify lat1; for Lambert conformal specify

lat1 lat2 (default=60)

SLON= lon normal longitude; for polar stereographic specify longitude and Lambert conformal, e.g., PRO=CONF (default=center longitude

of the map limits)

UNIT= contour units; depends on the contoured parameters

V= v-grid component if the v-grid doesn't follow the u-grid (default=u-grid+1)

Remarks

IGTV does not generate gridded data. Use commands MDX, SC, UC, etc., to generate the grids. Use commands IGG and IGU to manipulate grids and grid files.

IGTV allows for scaling up to 10<sup>8</sup>. Entered values should be integers less than 1000. The scale value is the integer multiplied by 1,000,000. For example, SCALE=33 gives a 33,000,000 to 1 scale.

To view the wind's u-grid component, assign the v-grid component (keyword V) a nonexistent grid value such as V=0.

### **Examples**

### IGTV 5 X X 3 DEV=P

This entry prints the grid points from grid 5.

### IGTV 2 X MID 2 DEV=C

This entry displays the grid points and contours from grid 2 over the Midwest.

### IGTV 3 10 USA DASH=NEG GRIDF=14

This entry displays the contours from grid 3 in grid file 14 on a USA Mercator projection. It uses a contour interval of 10 with dashed negative values.

### IGTV 17 4 USA PRO=CONF SLAT=25 50 SCALE=10

This entry displays the contours from grid 17 with a contour interval of 4. The map is a Lambert conformal projection of the USA with standard latitudes of 25° N and 50° N. The map is scaled 10,000,000 to 1.

Create the following string called LEV:

TE LEV "30 50 60 65 80

Then use IGTV to contour the grid:

IGTV 1 LEV MID UNIT=F

This entry contours only the 30, 50, 60, 65 and 80 degree isotherms. Note that in this special feature of IGTV, there is no pound sign before the string name, i.e., #LEV.

## **IGU**

### Grid file utility.

**Formats** 

IGU LIST bgridf egridf [keywords]

IGU DEL bgridf egridf

IGU SET gridf

IGU COPY sgridf dgridf RENUMBER

IGU MAKE gridf maxgrd "text IGU DIR gridf date project "text

Default

No default; you must specify a group of parameters.

**Parameters** 

LIST

lists a directory on the CRT

DEL

deletes a grid file

SET

points at a grid file number

COPY

copies a grid file

MAKE

generates a grid file

DIR

creates a directory for a grid file

RENUMBER

renumbers grids after copying a file

bgridf

beginning grid file number

egridf

ending grid file number

gridf

grid file number

sgridf

source grid file number

dgridf

destination grid file number

maxgrd

maximum number of grids in the grid file

date

date the grid file was generated

project

your project number

"text

identification text for your grid file; quotes are

mandatory

Keywords

DAY= lists the s

lists the grid files with this date, YYDDD

PROJ=

lists the grid files with this project number

**Examples** 

IGU LIST 1000 1020 DAY=79100

This entry lists the grid files from 1000 to 1020 for day 100 in 1979.

IGU COPY 1000 2000 RENUMBER

This entry copies grid file 1000 into grid file 2000 renumbering the

grids to compact the file.

**IGU SET 2000** 

This entry points at grid file 2000. All subsequent grid operations are performed on file 2000 until you execute another IGU SET command.

# **IMGPRO**

Generates satellite image products.

**Format** 

IMGPRO sarea darea [keywords] "text

Default

No default; you must specify the areas.

**Parameters** 

source area number; keyword AREA overrides this

entry (no default)

darea

sarea

destination area number (no default)

"text

text to attach to the destination area directory;

32 characters maximum

Keywords

AREA=

single or multiple source area numbers (default=sarea)

BAND=

single or multiple band numbers (default=lowest band

number)

COEF=

coefficients for each term in the equation (default=+1.0)

CONST=

constant for the equation (default=0.0)

FACTOR=

internal source and destination integer scaling factors

(default=1.0)

FORM=

ADD

adds each term in the equation (default)

MULT

multiplies each term in the equation

FUNC=

allows a transcendental function operation on the

additive or multiplicative expression, i.e., LOG, ALOG,

LN, EXP (default=NONE)

LLMT=

lower limit thresholds, inclusive, for each term in the

equation (no default)

NAME=

derived imagery product name; up to 4 characters

(default=PROD)

OFF=

offsets for each term in the equation (default=0.0)

POW=

powers for each term in the equation (default=+1.0)

QA= YES quits the output area if it already exists
NO does not quit the output area (default)

SCALE= prod/o prod/hi britle brithi

SCALE= prodlo prodhi britlo brithi
minimum and maximum product and brightness values
for the calibration (default=none for the product values;
0-255 for the brightness counts)

SIGN= P plus the band values relative to their offsets for each term in the equation (default)

M minus the band values relative to their offsets

ULMT= upper limit thresholds, inclusive, for each term in the equation (no default)

UNIT= calibration types for each term in the equation (default=BRIT)

ZERO= DATA assigns zero pixel values as data and includes
them in the analysis
MISS assigns zero pixel values as missing and excludes
them from the analysis (default)

a nonzero numeric value identifies that pixel value to represent the missing value flag

Remarks

IMGPRO has no line limit, but has a 4000 element maximum.

This program assumes all areas have equivalent navigation. If this is not the case, use the REMAP or AA command.

Zero pixel values can be treated as missing value codes or as real data values. Nonzero numeric values can be substituted to specify a different missing value code other than zero.

The equation formats are:

Output = Constant + FORMat [ Coef \* (Off+Sign\*Band) \* \* Pow ]
Output = FUNCtion [ Output ]

Example

# IMGPRO 2048 2049 BAND=8 10 COEF=+1 -1 SCALE=-10 +10 NAME=DIFF UNIT=TEMP

This entry calculates the difference between 11 and 6.7 micron GOES brightness temperatures from the multibanded area 2048, storing the temperature difference in area 2049 with a linear stretch between 0 and 255 brightness counts for the temperature range -10 to +10 degK, and naming it DIFF.

## **ISENT**

Calculates theta surface levels for all RAOB stations.

**Format** 

ISENT smdf dmdf day time btha etha inctha [keyword]

Default

ISENT smdf dmdf

This entry calculates the theta surface levels for all data in smdf and stores the results in dmdf.

**Parameters** 

smdf source MD file (default=current mandatory RAOB file)

dmdf destination MD file; must not exist before running ISENT

(no default)

day year and day of the RAOB data, YYDDD (default=current)

time time of the RAOB observation, HHMM (default=0Z if the

current time is less than 13:30Z, else 12Z)

btha beginning theta value (default=280 K)

etha ending theta value (default=350 K)

increment of the theta value (default=10 K)

Keyword

SIG=

history MD file for significant data

Remarks

A maximum of 18 theta levels can be calculated. Theta levels contain pressure, missing ratio, u and v components, delta pressure, Montgomery streamfunction and the theta value.

When using history data, the significant data file should follow the mandatory data file or be specified by keyword SIG.

To view data from the created MD file, use command MDX with a sort condition like the following: SORT=TIME 12 THA 300. This sort condition is for data at 12Z; the isentropic surface is 300K. See MDX for more information.

Example

ISENT X 1000 X 0 290 340

This entry calculates the theta surface levels between 290 and 340 for 0Z on the current day, and files this information into MD file 1000.

J

Toggles graphics frames to and from the loop control system.

#### Remarks

To toggle graphics frames to and from the loop control system on tower workstations,

Press: Alt J

or

Type: J

Press: Enter

A maximum of 18 that a levels and be calculated. That's levels as

The loop control system consists of the A, B, L, J, Y and LB commands.

You can connect or disconnect graphics frames from the loop control keys independently of the image frames.

# K

## Toggles image frames on and off.

Remarks

To toggle image frames on and off,

Press: Alt K

or

Type: K Press: Enter

On VGA workstations, this is simulated by setting the thirteen image levels (0 and 4 to 15) to black.

See Also

Command W toggles the graphics frame on and off.

L

## Toggles frame looping on and off.

#### Remarks

To start automatic frame looping in a forward mode,

Press: Alt L

or

Type: L

Press: Enter

Pressing L a second time stops the looping at the first frame of the loop.

The L command works only if the loop control system is connected to the frame system.

#### See Also

The Y command connects the loop controls to the image frame system.

The J command connects the graphics frames.

Refer to the Introduction section of this manual for more information about the McIDAS-OS2 Loop Control System.

# LA

### Lists the digital area directory.

**Format** 

LA barea larea [keywords]

Default

LA barea larea

This entry lists a single line directory for all areas between the

beginning and last areas.

**Parameters** 

barea the beginning area directory to list

larea the last area directory to list (default=barea)

Keywords

DAY= lists the area for the current day and year only, YYDDD

or YY/MM/DD; if DDD=0, all days for YY are listed

FORM= ALL lists the entire area directory

AUDIT lists the entire directory with its audit trail EXP lists an expanded version of the area directory

SS= lists the areas with this sensor source only

TIME = lists the areas with this time only, HH:MM:SS

Remarks

If you use FORM=ALL with POES, be sure to check the MEMO line in the directory information. The signal will be HRPT (LAC or GAC). The product will be MULT (multiple) or SIG (single) band. The ground station will be Wallops Island (W) or Gilmore Creek (G). The A or D in the line represents Ascending or Descending display. If D

appears on the line, the image is upside down.

**Examples** 

LA 101 120 TIME=21:01

This entry lists the areas between 101 and 120 with time 2101 GMT.

LA 101

This entry lists area 101 only.

# LB

Sets image or graphics frame loop bounds.

**Formats** 

LB bframe eframe
LB G bframe eframe

Default

LB

This entry lists the current loop bounds.

**Parameters** 

bframe beginning frame of the loop (no default)

eframe

ending frame of the loop; this number must be larger than bframe (default=half the highest frame number on the terminal for image frames; the highest frame number on the terminal for graphics frames)

MAX is the highest frame number on the terminal

G

sets the graphics loop bounds; not entering a parameter sets the image frame loop bounds (not valid on VGA workstations)

Remarks

When you log on to McIDAS, image frame loop bounds are set at a lower bound of 1, with the upper bound being half the highest frame number on your terminal. Use the F, L, Y and J keys to manipulate the loop control system. F lists the loop bound status, L loops the frames, Y locks and unlocks the image frames (tower workstations only), and J locks and unlocks the graphics frames (tower workstations only).

See Also

See command LS for information about random frame looping.

Refer to the Introduction section of this manual for more information about the McIDAS-OS2 Loop Control System.

**Examples** 

LB 1 6

This entry sets images to loop from frames 1 through 6.

LB G 8 11

This entry sets graphics to loop from frames 8 through 11.

LB 6 MAX

This entry sets the image frame loop bounds beginning on frame 6 and ending on the highest frame number.

# LF

## Lists an image frame directory.

Format LF bframe eframe [keyword]

Default LF

This entry lists the current image frame directory on the CRT.

Parameters beginning image frame number to list (default=current)

ALL lists all the image frames

eframe ending image frame number to list (default=bframe)

Keyword FORM= ALL lists an expanded directory

STN lists the standard directory (default)

Examples LF 2 6

This entry lists the image frame directory for frames 2 through 6.

LF 5 FORM=ALL

This entry lists an expanded image frame directory for frame 5.

# **LOGOFF**

Logs you off the system and workstation.

Remarks

This command logs you off the host and PC.

# LOGON

Logs you onto the system.

**Formats** 

LOGON initials project I

LOGON initials project string PC

LOGON initials project string password

Default

LOGON initials project

This entry logs you onto the PC and mainframe host. It resets the loop bounds to one and one-half the maximum image frame number, sets the image and graphics frames to one, and leaves the rest of the workstation in its current state.

**Parameters** 

initials your initials

project your 4-digit project number

string name of the PC and host string table and string to execute,

if any; PC strings are executed first, followed by host strings

password password as required by sites; appears as dashes (---) on

the screen as you type it

I initializes the workstation

PC logs on to the PC workstation only, if specified

Remarks

When you log on to a host, one of two things may happen depending on the SETUP of your workstation. First, the LOGON command may attempt to connect you to a host via dialup or TCP. This is not true for ProNET-connected workstations. Second, the LOGON command will send the text of the LOGON command to the host along with important information about the configuration of the workstation.

When you log on to McIDAS, the workstation is initialized. It lists:

- · your workstation identification
- the message of the day
- the + LOGON COMPLETE + message
- a MAIL WAITING message (when applicable)

If there is no response, type the LOGON command again.

If a Communications Timeout, Comm Link Error or ProNET Contact Lost message appears on the screen, it means your workstation is down. Contact your computer operator. To view the logon message during a work session,

Type: . SEE LOGON

McIDAS has several logon procedures. Review the six procedures below and select one that is suitable for you.

1. To initialize your workstation,

Type: LOGON initials project I Example: LOGON ABC 1234 I

#### This entry:

- · clears the string table
- · sets the current MD file number
- displays image and graphics frames one on tower workstations
- sets image frame loop bounds 1-1/2 times the number of image frames on the terminal; EGA/VGA workstations are set to the maximum
- connects image frame looping
- sets graphics frame loop bounds to one and the total number of graphics frames on your terminal
- disconnects graphics frame looping
- sets image and graphics frame dwell rates to 9/15 second for the first frame and 6/15 second for the remaining frames
- sets the graphics line width to one pixel
- initializes graphics color levels
- displays a red 30 x 30 pixel crosshair cursor (tower workstation only)
- unlocks the cursor control
- sets the enhancement table with command:
   EU MAKE 0 255 0 255 0 255
- turns off the pictel interlace switch (N key)

2. To leave your workstation in its current state,

Type: LOGON initials project Example: LOGON ABC 1234

This entry leaves your workstation in its present state, except it checks for valid loop bounds, resetting to one and one-half the total image frame number, if necessary. It also sets the image/graphics frames to the lowest loop bound frame

3. To load a string table in the host mode,

Type: LOGON initials project. Example: LOGON ABC 1234.

This example initializes the workstation and loads the string table named with your initials on the PC and host. It loads the PC string table and executes its strings prior to the host's. After the PC string table named ABC is loaded, any string name beginning with ABC (e.g., ABCXXXX, ABCYYYY) is executed. In the PC mode, the PC string table named ABC is loaded. Any string beginning with ABC in the PC string table is executed.

To load a PC string table while in the host mode,

Type: LOGON initials project string Example: LOGON ABC 1234 STR

This example initializes the workstation and loads the string table named STR in the host. It also loads the PC string table STR in the PC. Any string in the table beginning with STR (e.g., STRCOLOR, STRERASE) is executed. The same procedure is followed for a host string table named STR. In the PC mode, only the PC string table named STR is loaded. Any string beginning with STR in the PC string table will be executed.

To log on with a password to a host,

Type: LOGON initials project X password Example: LOGON ABC 1234 X PASSWORD

Because passwords are displayed as dashes on the screen when you type them, the example line will look like this:

LOGON ABC 1234 X -----

# LS

Creates random loop sequences for image and graphics frames.

**Formats** 

LS frame1 frame2 frame3 ... framen [keywords]
LS G frame1 frame2 frame3 ... framen [keywords]

LS O frame1 frame2 frame3 ... framen [keywords]

Default

LS

This entry lists the current loop sequences.

**Parameters** 

frame1 ... n frame numbers to include in the loop

G sets the graphics frame loop sequence; it is not valid

on VGA workstations

O sets the opposite frame loop sequence

**Keywords** 

DIR= B steps through the frame list backward

F steps through the frame list forward (default)

UPDATE=

automatically updates the loop when a new frame

is displayed using command DF

N doesn't update the loop (default)

Remarks

Use frame-frame for a sequential range of frames. See the examples.

When you set the frame loop, the opposite frame loop is automatically set in the following manner. If frame N is less than or equal to (max frames)/2, it corresponds to the opposite frame N+(max frames)/2. If frame N is greater than (max frames)/2, it corresponds to the opposite frame N-(max frame)/2.

To override the opposite frame loop default, use the LS O command.

Refer to the Introduction section of this manual for more information about the McIDAS-OS2 Loop Control System.

#### **Examples**

LS 1 4 2 5

This entry loops from image frames 1 to 4, to 2 to 5.

LS 1-16

This entry loops frames 1 through 16.

LS 1 16

This entry loops frames 1 and 16 only.

LS O 1-4 8 9 3-1

This entry loops opposite frames 1, 2, 3, 4, 8, 9, 3, 2, 1.

LS G 1-5 5-1

This entry loops through graphics frames 1 to 5, then 5 to 1.

# **LSCHE**

Lists an MD file schema.

**Formats** 

LSCHE schema version HED

LSCHE FIND key

Default

LSCHE

schema

This entry lists all registered MD file schemas.

**Parameters** 

name of an MD file schema to list; the name is system

dependent

ALL lists all file schemas (default)

version

schema version number to list

ALL lists all schema version numbers (default=latest

version)

key

name of a schema key; a schema entry point descriptor

HED

lists the file header only (default=lists header and keys)

FIND

lists the schemas that contain the specified key

Remarks

Before using command LSCHE, initialize the MD files using the

SCHE command.

Use LSCHE to list the schema header and keys.

**Examples** 

LSCHE IRAB

This entry lists the IRAB file schema.

LSCHE ISFC ALL

This entry lists all versions of the ISFC file schema.

LSCHE ISHP X HED

This entry lists the file header only for the ISHP file schema.

LSCHE FIND IDN

This entry lists all schemas that contain the key IDN (station ID

number).

# LVF

Lists virtual frame files.

#### Remarks

Command LVF lists the VGA workstation virtual frame files saved with the SVF command. Files are saved in the \MCIDAS\DATA subdirectory with extension .VIF.

# **LWTODOS**

Converts LW format files to DOS format files.

Format LWTODOS sfile dfile R

Default No default; you must specify the files.

Parameters sfile source LW file name

dfile destination DOS file name; it must be different than sfile

R replaces the destination file if it already exists

Remarks The LW file format is an 80-character card image, blank padded as

needed, with no carriage returns.

Example LWTODOS SFCPLT SFCPLT.TXT

This entry converts the LW file named SFCPLT to a DOS file named

SFCPLT.TXT.

# LWU

#### LW file utility.

**Formats** 

LWU COPY sfile dfile

LWU DEL file

LWU LIST file first last

LWU MAKE file

Default

No default; you must specify the parameters.

**Parameters** 

COPY copies a file

DEL deletes a file

LIST li

lists words, the range is 0-8 million (default=0-39)

MAKE

creates a file

sfile

source file name

dfile

destination file name

file

name of the file

first

first word number to list

last

last word number to list (default=next 39 words)

Remarks

LW files reside in the \MCIDAS\DATA subdirectory.

Use DMAP to determine the size of your file before transferring it to a

diskette.

**Examples** 

LWU MAKE CLOUDS

This entry creates an LW file named CLOUDS.

LWU COPY CLOUDS NEWONE

This entry copies LW file CLOUDS into file NEWONE.

LWU DEL CLOUDS

This entry deletes LW file CLOUDS.

# MA

# Modifies a digital area.

Format	MA sare	a darea frame option p1 p2 p3 p4 [keyword]		
Default	No defaul	o default; you must specify a group of parameters.		
Parameters	sarea	source area number		
	darea	destination area number		
	frame	image frame number for the modified area; you may use zero for no TV display		
		A automatic enhancement C contrast stretching E lookup table enhancement F data fill G gradient H high pass filter L low pass filter S digital stretching ADD adds a parameter to the data BAD removes buffer flakes and bad lines; places the average in all bad lines CLN removes buffer flakes and bad lines; places zeros in the bad lines FLX converts the IR counts to flux in W/M*M/2 LIN converts the square root digitization to a linear scale SCA scales the data TEM converts the IR counts to Kelvin - 100		
	p1 - p4	these parameters vary with the selected <i>option</i> ; see the Remarks below		
Keywords	BAND=	band number to process; if it is a single band image it defaults to the single band; if you use multiband data, place keyword BAND at the end of the MA command sequence to clarify the desired band		

DBAND= destination band number in darea (default=BAND)

3-88

#### Remarks

MA modifies the brightness values in a digital area by applying a data operator, transferring the result to another digital area, and displaying the data on an image frame. sarea specifies the input area; darea specifies the output area. If darea=0, the modified area is written into sarea. frame specifies the frame number if the digital area is displayed following modification; otherwise, frame=0.

The maximum number of elements in a line is 5000.

option indicates one of the data operators which may require the use of p1 to p4 for control parameters. Below is a further explanation of each option.

Option	Description		
A stad of and the stad of a security and a security at the sec	A means automatic enhancement. It makes a histogram of the occurrence of the values for the input area. The output area is an enhancement of the input area where the range of digital values is proportional to the occurrence of the histogram values, i.e., if there are many digital values in a small brightness range on the area input, they are stretched to a wider range of brightnesses in the enhanced output. Values p1 and p2 are ignored.		
ADD	This option adds the constant $p1$ to the digital data. $J(I) = J(I) + p1$ . The overflow is set to 255; the underflow is set to 0. $p1$ =constant added to the data; - 255 $< p1 < 255$ (no default)		
BAD	This option locates bad lines and replaces them with the average of the lines on either side. It also removes buffer flakes with a shot noise filter. The program find bad lines by correlating each line with the last good line. Lines with averages of 255 or 0 are automatically defined as bad.  p1=shot noise window; 0 < p1 < 255 (default=40)  p2=first good line of the area (default=1)  p3=last line to be cleaned up (default=last line)  p4=correlation criteria between lines (default=20)		
C hill add a live and a side of the residence of the resi	C is an enhancement that stretches the values between p1 and p2 to range between 0 and 255.  p1=lower digital value (default=8)  p2=upper digital value (default=240)  positive stretch negative stretch (p1=255, p2=0)		

- compress stretch (*p1*=-300, *p2*=600) - real numbers (*p1*=26.8, *p2*=150.2)

Option	Description
CLN	CLN performs the same function as the BAD option except that zeros replace the bad lines if there is more
	than one bad line in a row. The maximum number of elements in a line is 1680.
	p1=shot noise window; $0 < p1 < 255$ (default=40) p2=first good line (default=1)
	p3=last line to clean up (default=last line)
	p4=correlation criteria between lines (default=20)
E manage	This option applies the enhancement from the video
	lookup tables to the digital data.
	p1=B (blue), G (green) or R (red) lookup table (default=B)
Feogeria	This option fills in the holes along a remapped data
	line. The holes have values between $p1$ and $p2$ . The
	average value of the data on either side of the hole is placed in the hole.
	p1=lower value that defines the hole; $0 < p1 < 255$
	(default=0)
	p2=upper value that defines the hole; $0 < p2 < 255$
	(default=0)
FLX	FLX converts the infrared image into an image of
	longwave flux divided by 2 in units of watts/m <sup>2</sup> . The formula is $J(I) = 0.543*(5.66 \times 10^{-8})*J(I)^4 + 44.538$ .
	10rmula is 3(1) = 0.345 (3.00 x 10 ) 3(1) = 44.356.
G	This option applies a gradient operator
	(IABS $[J(I)]$ - $J[I+1]$ ) along each line. $p1$ and $p2$ are not used.
Hanned M	This option applies a high pass filter (suppressing a
	low frequency of broad features) along a line.
	0-61 66 1 1 0 1100 (1 0 1 100)
	p2=filter efficiency; $1 < p2 < 100$ (default=100%)
$\mathbf{L}_{10}$ $> 0$ gwa	
	4 61. 11 4 4 4 5 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6
	0 41. 44 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4
LIN	This option converts the SMS square root digitization
tue of the control of	to a linear scale in which the visible image brightness
	values are proportional to the radiance measured by
	the satellite. $J(I)=p2*(J[I]*J[I]/16-p1/4)/3969$
	p1=calibration offset; space view (default=8)
	p2=scaling factor (default=200)

Option	Description
N	This option applies a shot noise filter to remove spikes along a data line. The shot noise pixel is replaced by the average value of the pixels, one to the left and two to the right.
	p1=shot noise window (default=40 pixels)
S emag s	This option takes an enhancement of the digital area which throws away the lower $p1\%$ and $p2\%$ of the data and stretches the remaining data to fit between 0 and 255.
	p1=lower cutoff percentage; $1 < p1 < 100$ (default=3) $p2$ =upper cutoff percentage; $1 < p2 < 100$ (default=3)
SCA	This option scales the data by multiplying by $p1$ . The $J(I) * p1$ overflow is set to 255.
	p1=multiplying factor; it can be an integer or real number (default=1)
ТЕМ	This option converts the infrared counts into an image of temperature - 100 (in Kelvin - 100). pland p2 are not used.

#### **Examples**

#### MA 6512 6513 2 CLN

This entry cleans up the data in area 6512, places the new data in area 6513 and displays the new image on frame 2.

#### MA 6513 6514 10 C 150 200

This entry contrast stretches area 6513 into area 6514 and displays the image on frame 10. It stretches the digital values 150 to 200 between 0 and 255.

#### MA 1000 2500 X ADD 100

This entry adds the constant 100 to each digital value in area 1000. The destination area is 2500. It does not display the image. Any new values greater than 255 become 255.

#### MA 8011 8010 BAD BAND=4 DBAND=6

This entry removes bad lines and buffer flakes from area 8011 band 4 and stores the result in area 8010 band 6.

# **MAKMNU**

Creates a menu file from text orders.

**Format** 

MAKMNU file [keywords]

NO

Default

No default; you must specify the file name.

**Parameter** 

file file name where the text orders exist

Keywords

INIT= YES initializes the menu file before adding a specified

menu; does not merge menus (default)

does not initialize the menu file; use to merge menus

LIST=

YES lists the input file text as it's processed

NO does not list the input file text (default)

TYPE=

NEW input file is written using the new character format

(default)

OLD input file is written using the old character format

Remarks

The file containing text orders must reside in the \MCIDAS\DATA subdirectory. See the McIDAS-OS2 F Key Menu System chapter in this manual for further details.

If you do not specify an extension for the file name, the system assumes the .MNU extension.

If you no longer want a menu on your system,

Type: LWU DEL MENU

Press: Enter

No menu will come up automatically when you enter McIDAS or press the Escape key.

Example

#### MAKMNU SFCTR TYPE=OLD

This entry creates the menu file SFCTR from the text orders specified using the old character format.

# MAP

Outlines map and latitude/longitude lines on a graphics frame.

Format

MAP map color1 LALO color2 [keywords]

Default

MAP

This entry draws a map on a satellite image.

**Parameters** 

map DEF

draws a map in Mercator projection with

latitude/longitude ranges that you specify; the map file is selected as in SAT below

EURB Europe's political boundaries;

latitude=20 80, longitude= - 60 30; map

file OUTLHPOL

EURO Europe; latitude=20 80, longitude=- 60 30;

map file OUTLSUPW

H North America; medium resolution; map

file OUTLUSAM

L world coastal outlines; used with satellite

projection; map file OUTLSUPW

LALO no map; latitude/longitude lines only

MID Midwest; latitude=34 50, longitude=83 104;

map file OUTLUSAM

NA North America; latitude=25 80.

longitude=55 179; map file OUTLUSAM

OUTLHPOL world political outlines

OUTLHRES world coastal outlines; high resolution continental USA; high resolution

OUTLSUPW world coastal outlines; medium resolution

OUTLUSAM North America; medium resolution PO Abbreviation Post Office abbreviation; map file

**OUTLUSAM** 

POLI world political boundaries; map file

OUTLHPOL

PRC China; latitude=15 55, longitude=-145 -65;

map file OUTLSUPW

PRCB China's political boundaries; latitude=15 55;

longitude= -145 - 65; map file OUTLHPOL

SAT draws a map in satellite projection using

the OUTLUSAM map file for North America

and OUTLSUPW for all other areas (default)

USA continental USA; latitude=23 56,

longitude=66 126; map file OUTLUSAM

Revised 9/91

VHcontinental USA; high resolution; map file OUTLSUPU WORL world coastal outlines; used with Mercator projection; map file OUTLSUPW WIS Wisconsin; latitude=41 48, longitude=85 95; map file OUTLUSAM color1 graphics color level for the map; the range is 1-7 (default=1) LALO draws latitude/longitude lines with a map (default=does not draw lines) color2 graphics color level for latitude/longitude lines; the range is 1-7 (default=2) Keywords ACC= accuracy for the latitude/longitude lines; the range is 1-10 (default=4) BOX= YES color draws a box around a graphics panel in a specified color (default for all except SAT; default color=1) does not draw a box (default for SAT projection) ELE= TV element extents (default taken from min max User Common) GRA= graphics frame number (default=current) IMA= image frame number (default=current) INT= lat lon intervals for latitude/longitude lines (default=computed) LABEL= NO does not add a label YES clat clon adds latitude/longitude line labels (default) specify the color levels for latitude and longitude (default for both is level 3); see the Labels information latitudes of the points at the lower-right LAT= and upper-left corners of the TV screen LIN= min max TV line extents (default from User Common)

LON= lon1 lon2 longitudes of the points at the lower-right and upper-left corners of the TV screen; if you choose a CONF projection and specify SCALE, the map is centered at the specified coordinates if only lat1 and lon1 are entered; in other cases, the point with coordinate lat2, lon2 is placed in the upper-left corner of the TV screen; the other point is shifted on the screen (or removed from it) to create a map with a given scale; defaults for SAT projections are the range taken from the image or map geographical limits; for CONF and MERC projections, defaults are latitude -90 to +90, longitude -180 to +180

NAME = map file name; it overwrites the default map file

PAN= panel number; the range is 0-4 (default=0, whole screen)

PRO= CONF conformal projection; see the Projections information below

MERC Mercator projection (default for all maps

except H, VH, L or LALO)

satellite projection (default if map and projection are not specified, or map is H, VH, L or LALO and the projection is not specified)

SCALE= map scale for a CONF projection; scale values in the range up to 1000 are multiplied by 1,000,000 (default=no scale)

SLAT= standard latitude(s) for a CONF projection only; one value for a polar stereographic projection (default=60°) two values for a general Lambert conformal projection

SLON= standard longitude for a CONF projection only (default is computed)

Remarks

To plot a map on a satellite image, use L, H, VH or SAT (or X, since SAT is the default) as the map parameter.

When plotting a map on a satellite image on a VGA display, use color levels 1-7 if no image is displayed on the current frame. Use only color levels 1-3 if an image is displayed.

#### **Projections**

The MERC (pseudo-Mercator) projection has equidistant latitude lines. Otherwise it is the same as a true Mercator projection. The CONF (Lambert conformal) projection includes polar stereographic projection as a special case. If you enter only one positive SLAT value or if you accept the default of 60°, the projection is polar stereographic with the North Pole as the origin of projection. If you enter only one negative value for SLAT, the origin of the polar stereographic projection is the South Pole. You must enter two SLAT values to obtain a general Lambert conformal projection.

If SLAT1 + SLAT2 > 0, the North Pole is the origin of projection.

If SLAT1 + SLAT2 < 0, the South Pole is the origin of projection.

For some values of keywords LAT, LON, SLON and SLAT, the area defined cannot be found. If this happens, an error message is displayed and the program aborts. Use SLON for CONF projections only. The default value is computed by assuming that the standard meridian is located in the middle of a box set by two points and is parallel to the left and right edges of the TV screen. If a map is centered, the default SLON is equal to LON.

#### Labels

In some cases, labels overlap. You can usually fix this by changing the latitude/longitude line intervals and/or the accuracy.

#### Examples

The examples below are divided into four groups that include satellite projection, Mercator projection, polar stereographic and general Lambert conformal projection. Command lines that won't fit on one line have a second line that is indented.

#### Satellite Projection

#### MAP X 5 LALO 6 INT=5 10

This entry draws a map on a satellite image in color level 5. It draws latitude/longitude lines in color level 6 and labels them. The interval for latitude lines is 5°. The interval for longitude lines is 10°.

#### MAP VH X LALO LABEL=NO

This entry draws a high resolution USA map and latitude/longitude lines without labels.

#### **Mercator Projection**

#### MAP AK X LALO

This entry draws a map of Alaska and latitude/longitude lines with labels.

#### MAP EURO 2; MAP EURB X LALO

This entry draws a map of Europe with coastal and political boundaries.

#### Polar Stereographic

#### MAP WI PRO=CONF

This entry draws a Wisconsin map in conformal projection.

#### MAP LALO PRO=CONF LAT=0 70 LON=90 - 90

This entry draws latitude/longitude lines and labels for the specified North American region.

#### MAP OUTLSUPU X LALO PRO=CONF LAT=30 45 LON=90 110 SLON=100

This entry draws a map and latitude/longitude lines for a region with the specified latitude/longitude range and standard longitude. The map is taken from the OUTLSUPU high resolution map file. In this case, the map file name can be abbreviated as VH.

#### MAP X X LALO PRO=CONF LAT=- 20 - 20 LON=0 180

This entry draws a map of the northern hemisphere with the North Pole as the origin of projection.

# MAP X X LALO PRO=CONF LAT=20 20 LON=0 180 SLAT=-60

This entry draws a map of the southern hemisphere with the South Pole as the origin of projection.

# MAP X X LALO PRO=CONF LAT=-10 60 LON=-10 20 SCALE=20

This entry draws a map of the latitude/longitude range specified in 1:20000000 scale. The point with latitude 60 and longitude 20 is located in the upper-left corner of the TV screen.

#### MAP PRO=CONF LAT=-90 LON=0 SLAT=-60 SCALE=35

This entry draws a map centered at the South Pole, with the origin of the projection at the South Pole and a standard latitude of 60°. The point with latitude -90 and longitude 0 is in the middle of the TV screen. The standard longitude is 0° and the scale is 1:35000000.

# MAP X X LALO PRO=CONF LAT=-5 - 35 LON=-115 -170 SLAT=-60

This entry draws a map of Australia with latitude/longitude lines and labels in the projection centered at the South Pole.

#### MAP X X LALO PRO=CONF LAT=0 -60 LON=-145 -70 SLAT=-60 SLON=-40

This entry is the same as the one above but with the South Pole at the left of the TV screen.

#### MAP X X LALO PRO=CONF LAT=-60 0 LON=-70 -145 SLAT=-60 SLON=-40

This entry produces the same map of Australia but rotates it by 180°, with the South Pole at the right of the screen.

#### **Lambert Conformal**

MAP PRO=CONF LAT=20 60 LON=70 165 SLAT=40 60 This entry draws a Lambert conformal map of the United States.

MAP X X LALO PRO=CONF LAT=40 70 LON=150 - 150 SLAT=40 60

This entry draws a map of the Alaska region. In the Lambert conformal projection, the map splits but the information is complete.

MAP X X LALO PRO=CONF LAT=-15 LON=-135 SLON=180 SCALE=25 SLAT=-60 - 40

This entry draws a map of Australia with latitude/longitude lines.

MAP X X LALO PRO=CONF LAT=-80 LON=15 SLON=10 SLAT=-70 10 SCALE=40

This entry draws a map of Antarctica.

# MC

Combines two areas to produce a new output area.

Format MC sarea1 sarea2

MC sarea1 sarea2 darea option p1 p2 p3 p4 p5 [keywords]

Default

No default; you must specify a group of parameters.

**Parameters** 

sarea1-2 source area numbers to combine

darea destination area number to store the combined results

option AVE averages the brightness values

CLD clouds
COR cloud cores
DIS discriminate

DIV divides images by a constant

MAX saves the maximum brightness values
MIN saves the minimum brightness values
MPY multiplies the images by a constant

RAT ratio

RMS root mean square

SPL generates a split screen image SUB subtracts brightness values

WAV weighted average

p1 - p5 these parameters vary with the selected option; see the

Remarks below

Keywords

BAND= a1-a2 band numbers corresponding to the area

numbers

IMA= image frame number; displays darea

Remarks

Command MC does a pixel-by-pixel combination of two areas to produce a new output area. The focal point of the areas must be aligned. The output area is given an area directory equal to the directory for the first input area, plus the appropriate message code. All areas must be the same size. The functions presently available are listed in the table below.

Option	n Description	Function	
AVE	Averages 2 areas.	$\frac{darea = a1 + a2}{number of areas}$	
	en ten ancera en produce a	p1 and $p2$ are threshold limits. A pixel is included in the average if $p1 < a < p2$ . (default=0 for $p1$ ) 255 for $p2$ )	
CLD	Creates an area of only clouds (using the minimum brightness composite from the MIN option) in sarea2 as background brightness.	darea=a1 (if $a1 > a2 + p1$ ) Otherwise, darea= $p2$ . (default=0 for both $p1$ and $p2$ )	
	p1 defines the brightness threshold.		
COR	Selects cloud cores by comparing the brightness values defined by $p1$ and $p2$ and placing the results in darea.	If brightness $a1 > p1$ and brightness $a2 < p2$ , then $darea=p3$ . Otherwise, $darea=p4$ .	
DIS	Discriminates the values of one area against the values in a second area.	darea=a1 if $p1 < a1 < p2$ and $p3 < a2 < p4$ . Otherwise, darea=p5. (default=0 for p5)	
DIV	Normalizes the area ratio of two areas and, if desired, changes the brightness value. p2 cannot equal zero.	darea=100 * (a1/a2) * p1/100+p2 p1=normalization factor p2=factor to increase or decrease the baseline brightness	
MAX	Selects the maximum brightness value from 2 areas.	darea=MIN (MAX (a1, a2), p1) (default=255 for p1)	
MIN	Selects the minimum brightness value from 2 areas.	darea=MAX (MIN (a1, a2), p1) (default=0 for p1)	
MPY	Multiplies two areas together.	$\frac{darea=(a1 * a2) + p1}{(256)}$	
		(default=0 for p1)	

Option	n Description	Function
RAT	Creates the color ratios of two areas.	$\frac{darea = (p1*a1 - p2*a2)}{a1 \text{ and } a2}*p3+p4$
		(default=100 for $p1$ , $p2$ and $p3$ ; 0 for $p4$ )
RMS	Provides the root mean square of two areas.	$\frac{darea=(a1^2+a2^2=\ldots)}{(number\ of\ areas)} \frac{1}{2}$
		p1 and $p2$ are threshold limits. A pixel is included in the average if $p1 < a_i < p2$ . (default=0 for $p1$ ; 255 for $p2$ )
SPL	Combines 2 areas to create a split image. For 2 vertically spli images, enter:	
AMI ( AMI ( Ami o	MC sarea1 sarea2	darea SPL p1 p2
	sarea1 and sarea2	the area numbers to combine
	darea	destination area of the split image
	combines areas 6512 at 1q area is 6590. The image is ereas are all less than 1000	integer whose value exceeds the number of lines in sarea1 and sarea2
	p2	TV element where the split occu
		p2

Notice that the left side of sarea1 and the left side of sarea2 comprise the final image. You may need to do several AA commands to obtain the desired result. For two horizontally split images, p1 defines the line number where the split occurs and p2 must be larger than either area's line number.

darea

sarea2

sarea1

Revised 9/91

Option Description		Function	
SUB	Subtracts two areas. You may change the base level and range.	darea = p1 * (a1 - a2 + p2) (default=1 for $p1$ ; 0 for $p2$ )	
WAV	WAV is the weighted average of two areas. p1 must be greater than zero.	N $darea=\Sigma$ $a1 * p1$ $a1=1$ $N$ $\Sigma$ $p1$ $a1=1$	
		N=2 (default=1 for p1)	

#### **Examples**

#### MC 9 10 16 AVE IMA=5

This entry averages areas 9 and 10. It places the average in area 16 and displays it on image frame 5.

#### MC 13 6 2 SUB 10

This entry subtracts area 6 from area 13 and stores the results in area 2. The new image is not displayed. The brightness range is stretched using p1=10.

#### MC 6512 6513 6520 SPL 1000 300 IMA=10

This entry combines areas 6512 and 6513 into a vertically split image. The output area is 6520. The image is displayed on frame 10. Since the source areas are all less than 1000 lines, the image is vertically split on TV pictel 300.



### MDE

#### Edits MD files.

**Formats** 

MDE mdfile KEYS=LIST

MDE mdfile KEYS=DEL conditions MDE mdfile KEYS=REST conditions

MDE mdfile KEYS= UNIT= VALU= conditions

Default

No default; you must specify a group of parameters.

**Parameter** 

MD file number to edit (default is set by MDU SET or by the previously executed MDU or MDE command)

Keywords

KEYS= keys in the MD file to edit

DEL deletes the records that meet the search conditions LIST lists the keywords in the MD file schema by row and column headers and data

REST restores a deleted record; specify ROW= and COL= (see the conditions below)

UNIT=

mdfile

units in which the new key values are entered; specify this keyword if the units are different from those native to the MD file

VALU=

new value for the keys

MISS enters missing data values

conditions search conditions to meet when searching for a record to edit; use any or all of the following options:

ROW= min max

row number or range of numbers

COL= min max

column number or range of numbers

schema keyword=low high units

range and units of the schema keyword that you are searching for; units are necessary if the range is specified in units other than those

native to the MD file

Remarks

Use command MDE to edit or restore MD files. Before you edit system MD files, move them into your assigned file numbers with command MDU COPY.

If you delete a record accidentally, you can recover it with KEYS=REST provided you have not repacked the file.

#### Example

In the following example you will edit a ship observation in MD file 31. Before editing the data, move MD file 31 into your assigned file numbers (file 6512 in this example).

1. MDU SET 6512

This entry sets the MD file pointer to 6512. All subsequent MD file commands will be performed on MD file 6512.

- 2. MDE KEYS=T UNIT=C VALU=20 ID=KWPR TIME=12
  The search conditions are ID=KWPR and TIME=12. MDE will locate ship ID KWPR at 12 GMT and change its temperature to 20° C.
- MDE KEYS=DEL ROW=5 COL=10 15
   This entry deletes the records at row 5 and columns 10 to 15.
- 4. MDE KEYS=REST ROW=5 COL=10
  This entry restores the record at row 5 and column 10.

#### More Examples

MDE KEYS=DEL ROW=1 5 COL=15 20 This entry deletes columns 15 to 20 in rows 1 through 5.

MDE 6514 KEYS=LIST

This entry lists the keys for MD file 6514.

MDE KEYS=T TD VALU=MISS ID=MSN TIME=12 This entry flags the temperature (T) and dew point (TD) as missing for Madison, WI, at 12 GMT.

#### Lists the MD file data.

**Format** MDL mdfile ALL INI SAVE KEYS= UNIT= conditions

Default MDL This entry lists the first record of the current MD file on the CRT.

**Parameters** mdfile MD file number (default is set by MDU SET or by the previously executed MDL or MDE command)

> lists all occurrences of the search conditions ALL (default=the first occurrence)

INI initializes the string table entries used by MDL (default=does not initialize)

SAVE saves the MDL keywords in the string table (default=does not save)

KEYS= keys to list from the MD file schema

> LIST lists the keys in the MD file schema; the keys are listed as row and/or column header keys and data keys

UNIT= units in which to list the value of the keys selected with keyword KEYS; specify this keyword if the units are different than those native to the MD file

conditions conditions to meet when searching for a record to list; use any or all of the following options:

> ROW= min max COL= min max schema keyword=low high units

row number or range of numbers column number or range of numbers

range and units of the schema keyword that you are searching for; units are necessary if the range is specified in units other than those native to the MD file

Keywords

#### Remarks

Position the parameters for keyword UNIT in the same order as those listed in keyword KEYS. Use the letter X as a place holder to list a key in its default unit. You may store keys, units and search conditions in your string table (see parameters INI and SAVE). It is not necessary to type them for each MDL command.

#### **Examples**

MDL 3 KEYS=ID TIME T TD ID=MSN TIME=12
This entry lists the station ID, time, temperature and dew point for Madison, WI, at 12 GMT from MD file 3.

## MDL 33 ALL KEYS=ID T TD TIME LAT LON T=20 21 C UNIT=X C C TIME=12

This entry lists the station ID, temperature, dew point, time, latitude and longitude from all reports in MD file 33 meeting the conditions TIME=12 GMT and the temperature is between 20° and 21° C.

## MDL INI SAVE KEYS=Z T TD DIR SPD UNIT=FT F F X KT ROW=1 COL=5

This entry lists the height (FT), temperature (F), dew point (F), wind direction and wind speed (KT) for row 1, column 5.

### MDU

#### MD file utility.

**Formats** 

MDU COPY smdfile dmdfile

MDU DEL bmdfile emdfile

MDU DIR mdfile id "comments

MDU LIST bmdfile emdfile [keyword]

MDU MAKE mdfile schema version nrows ncols id "comments

MDU SET mdfile

Default

No default; you must specify a group of parameters.

**Parameters** 

COPY

copies the contents of the MD file

DEL

deletes an MD file

DIR

changes a file identification number and comments

LIST

lists the file directory headers

MAKE

makes a new MD file

SET

sets the current MD file number

smdfile

source MD file number

dmdfile

destination MD file number

bmdfile

beginning MD file number

emdfile

ending MD file number (default=bmdfile)

mdfile

MD file number

id

identification number, YYDDD (default=current)

"comments

comments added to the file; quotes are mandatory

schema

MD file schema name, e.g., IRAB, VRET

version

version number; 0 or X to use schema defaults

nrows

number of rows; 0 or X to use schema defaults

ncols

number of columns; 0 or X to use schema defaults

Revised 2/92

Keyword

DAY= Julian day to list, YYDDD

**Examples** 

MDU COPY 1 10

This entry copies MD file 1 into MD file 10.

MDU DEL 26

This entry deletes MD files 2 through 6.

MDU DIR 1 91290 "SHIP AND BUOY DATA

This entry changes the directory of MD file 1 so the ID is 91290 and the comment is SHIP AND BUOY DATA.

MDU LIST 1 40

This entry lists the MD file directory headers from MD files 1 to 40.

MDU MAKE 1 ISHP 2 X X 91300 "SHIP DATA

MD file number

This entry creates MD file 1 of schema ISHP, version 2. It uses row and column defaults. It also uses the ID of 91300 labeled SHIP DATA.

MDU SET 5

This entry sets the current MD file number to 5. All subsequent MD file commands are performed on MD file 5.

### MDX

Plots or grids data from MD files or grids.

**Formats** 

MDX option PREFIX = MDX parm [keywords]

Default

**MDX** 

This entry executes the current information in the context table with PREFIX=\$.

**Parameters** 

option CLE clears the MDX context file and sets the defaults
LIST lists the MDX context table

PLT plots more than one parameter

The only valid keyword is PREFIX= (default=\$).

parm

any parameter in an MD file, e.g., ABV, STR, SPD, VOR, DVG, ADV, THAE, THA, MIX, WNV, WIN (see the examples); command MDL lists the parameters

Keywords

Because command MDX displays data from any MD file, there are many keywords you can use to fetch and display data. Consequently, the keywords are divided into five groups for discussion.

- PARAMETER keywords control the display characteristics for individual parameters, e.g., color, size, units, scaling.
- OUTPUT device keywords control the size of the display and set the output device.
- GRID/CONTOUR keywords change the grid size, smoothing and contour interval.
- MAP keywords specify maps and projections.
- MISCELLANEOUS keywords perform various functions.

Parameter Keywords

COLOR= color level of the plotted data graphics; use keyword

GCOLOR for contours (default=3)

DIVIDE divides the data values before plotting; to multiply, use

a number from 0 to 1 (default=1)

FORMAT= FORTRAN format specification for the output

(default=I12; character data default=A4)

LSIZE= label height in pixels; if LSIZE=5, all data is plotted; the numbers are allowed to overwrite each other (default=8)

u v if parameter WNV is specified, a negative LSIZE plots vectors of constant length; if parameter WIN is specified, a positive LSIZE defines a relative length of the wind barb; specify

u and v lengths with the same value

MISS= missing data code (default=Z80808080)

OFFSET= operates on the data before output (default is DIVIDE=1, OFFSET=0); value = (data - OFFSET)/DIVIDE; the UNIT keyword

uses the DIVIDE and OFFSET

PLACE= place to plot the data relative to the actual station location; the station is located at 41 in a 9 x 9 matrix starting at 1 in the upper-left corner, increasing along a row; use PLACE= when plotting more than one

parameter (default=41)

UNIT= units to plot the parameter (default=the MD file original units); the possible conversions are:

K to C, F MB to INHG

MPS, MPH, KT (any)

KM, M, CM, MM, MI, NMI, YD, FT, IN (any) SYMB plots weather symbols (default=CHAR)

Output Keywords DEV= C displays the output on the CRT (default is device dependent)

G displays output on the graphics
P displays output on the line printer

GELE= beg end graphics element extents (default=20 620)

GLINE= beg end graphics line extents (default=20 430)

GRA= graphics frame number (default=current)

IMA= image frame number (default=current)

OUT= PLO plot (default)
CON grid and contour

PANEL= graphics panel quadrant, the range is 0-4 (default=0, full screen)

beg end CRT/printer element extents (default=160) for the CRT; 1 120 for the printer) PLIN= beg end CRT/printer line extents (default=1 19 for the CRT; 1 60 for the printer) Grid/Contour CINT= grid contour interval (default=2) Keywords DER= WNV plots wind vectors from the grid file data DRAW= YES draws contours after gridding (default for graphics terminals) NO does not draw contours (default for all other terminals) GCOLOR= contour graphics color level (default=2) GRIDF= destination grid file to store grids (default from IGU SET) **GUESS=** grid to use as first guess (default=none) INC= grid increment in degrees (default=1.0) SMOOTH= smoothing parameter (default=40) Map Keywords LAT= min max minimum and maximum latitude extents LON= min max minimum and maximum longitude extents MAP= NA North America USA USA Midwest USA  $\mathbf{MID}$ Post Office Abbreviation MCHAR= map character for the CRT/printer output (default=...) MCOLOR= graphics map color level (default=1) 0 for no map CONF PRO= conformal projection for polar stereographic or Lambert conformal MERC Mercator projection (default) SAT satellite projection map scale ration for PRO=CONF (default=not true to scale)

SLAT= lat1 lat2 standard latitude(s); for polar stereographics

specify lat1; for Lambert conformal specify

lat1 lat2 (default=60, polar projection)

SLON= lon normal longitude; for polar stereographic

specify lon1 and keyword PRO=CONF (default=centers the longitude of the map

limits)

Miscellaneous Keywords

DERIVE=

use DERIVE=temp dewpoint pressure (elevation) if THAE, THA or MIX is displayed when the parameter does not appear in the MD file (it will be calculated); use elevation with sea level pressure; for an SVCA file use: DERIVE=T TD PSL ZS

for an SVCA file use: DERIVE=T TD PSL ZS for a RAOB or VRET file use: DERIVE=T TD P

GRIDF= grid file number to read (default is from IGU SET)

MDF= MD file number to read (default is from MDU SET); you can combine up to six MD files using keyword

**PREFIX** 

PREFIX= MDX stores options and defaults in the system context

file with a special prefix at the beginning of the string name; the prefix can be any character except numeric

or # (default=\$)

If you set up two context files using keyword PREFIX, you can execute these arithmetic operations:

subtract

\* multiply

+ add

/ divide

: catenate

For all operations, except catenate, the MD file must have the same schema; if LAT/LON is not contained in the column header, only one row can be operated on,

for example: PREFIX=\$ -!

SORT=

of the form keyword 1 loval 1 [hival 1] keyword 2, etc., selects data from the MD file that meets its conditions; in the SORT= keyword list, do not use an equals sign (=) between keywords and loval, hival; hival is optional if loval is numeric; do not specify hival if loval is alphabetic; keyword is any parameter from an MD file or a ROW and COL number

(e.g.,: SORT=TIME 12 13 ST WI)

SOU= MDF data source is an MD file (default)
GRID data source is a grid file

Remarks

When the plus sign (+) is the last positional parameter, the information is filed but not plotted.

The most basic command to display data is:

MDX parameter

where parameter is any parameter found in an MD file. The command plots all of this parameter from the current MD file (from MDU SET) on the current graphics frame on a map as determined by the limits of the data. To do anything more with MDX, you must know something about the type of data in the MD file. For example, if you want to plot 500 mb heights for day 84190 at 12Z over the Midwest, you must know that the height, day and time are referenced through parameters Z, DAY and TIME in the MD file.

The command to enter (with RAOB data in MD file 5000) is:

#### MDX Z MAP=MID MDF=5000 SORT=P 500 DAY 84190 TIME 12

Keyword SORT provides a way of limiting the data to a specific subset of interest. This is probably the most used keyword with a map specification keyword (MAP= or LAT= LON=) not far behind.

MDX is the general MD file plotter/gridder. It is intended for use in macros, not entered directly.

Keywords LAT and LON default to limits which guarantee complete coverage of the data distribution, rounded to the nearest whole degree.

Example

Before using this example, enter MDX CLE to clear and initialize the string entries that MDX uses. The example below is numbered as it requires you to follow a specific order.

1. To plot the weather data from MD file 4000 at 18 GMT, enter:

#### MDX WX1 MDF=4000 SORT=TIME 18

2. Contour the temperature advection from MD file 3020 over the Midwest at 15 GMT:

#### MDX T ADV MDF=3020 MAP=MID OUT=CON SORT=TIME 15

3. Plot T in degrees Fahrenheit for MD file 4050, for Wisconsin:

#### MDX T + MDF=4050 UNIT=F MAP=WI

This command does not plot because the + is inserted as the last positional parameter. Now plot in color 2 (MDF, UNIT and MAP remain the same):

#### MDX T COLOR=2

4. Plot the temperature from the current SVCA data for 15Z for a lat/lon box. The MD file is the last digit of the Julian day (if zero, MD=10); today is 83242:

#### MDX T MDF=2 LAT=30 50 LON=90 105 SORT=TIME 15

We forgot to specify only the hourlies (no specials) and degrees C. When MDX is done plotting, enter:

#### EG; MDX T SORT=TIME 15 TYPE 0 UNIT=C

5. To plot 1000-500 mb thickness over the USA, 12Z, MD file 1030, enter the following command sequences:

MDX CLEAR
MDX Z + SORT=P 500 TIME 12 MAP=USA MDF=1030
PREFIX=\$
MDX CLEAR PREFIX=!
MDX Z + SORT=P 1000 TIME 12 MAP=USA MDF=1030
PREFIX=!
MDX PREFIX=\$-!

Take the winds from MD files 2020 and 2045 and grid them for streamlines:

MDX STR + MDF=2020 PREFIX=\$
MDX STR + MDF=2045 PREFIX=\$
MDX PREFIX=\$:!

7. Use THAE, THA and MIX. It is easier to use the macros (SP, UP, etc.) to display these derived parameters. When using MDX, an extra keyword, DERIVE, is necessary:

#### MDX MIX MDF=3 MAP=MID DERIVE=T TD PSL ZS SORT=TIME 17 DAY 84170 TYPE 0

This entry plots a mixing ratio from an SVCA file.

8. Plot the grid points on the graphics for grid 10, grid file 6512, which contains temperature data:

#### MDX 10 SOU=GRID GRIDF=6512 MAP=MID UNIT=C

9. Plot the wind flags at the grid points for u grid 1 and v grid 2 at 12 GMT:

#### MDX PLT 1 2 SOU=GRID PRO=SAT SORT=TIME 12

10. Plot parameters T and TD from MD file 4000 at 12Z over Wisconsin. Position the temperature above the dew points with the PLACE keyword. First, set it up with no plot:

MDX T TD + MDF=4000 SORT=TIME 12 MAP=WI PLACE=41 50

Now use plot:

MDX PLT

11. Plot the u and v component vectors on the graphics from grids 1 and 2:

MDX PLT 1 2 SOU=GRID DER=WNV MAP=MID

12. To plot the weather symbols for day 88101:

MDX WX1 UNIT=SYMB MDF=1 MAP=MID SORT=TIME 18 TYPE 0 DAY 88101

Revised 2/92

### MG

#### Plots a 24-hour surface meteorogram.

**Format** 

MG station time day [keywords]

Default

MG station

This entry plots a surface meteorogram using the current day and time. It initializes the color levels and erases the graphics before plotting.

**Parameters** 

station 3-letter station ID

time hour of the last data plotted on the graph; the range is 0-23

(default=current)

day

year and day, YYDDD (default=current)

Keywords

GRA= graphics frame number

INIT= initializes the graphics colors (default) YES

> NO does not initialize the graphics colors

MDF= history MD file number; specify parameter day with this

keyword (default=real-time MD file)

SF= YES displays the graphics frame when completed

> NO does not display the graphics frame (default)

Remarks

A meteorogram plots temperature, dew point, pressure, wind speed and direction, weather, and cloud cover for a 24-hour period of the specified station. Cloud cover symbols include: scattered (1 small cloud), broken (2 clouds), overcast (1 large cloud) and clear (no clouds). Wind speed and direction indicators are: direction (short barb with angle), speed (length of the barb) and calm (diamond shaped symbol). Pressure range labels depend on the minimum and

maximum pressure for a given day and time period.

Examples

MG MSN

This entry plots data for the past 24 hours for Madison, WI. The day and time default to the current data.

MG MSN X 85131

This entry plots data from 85130 0 GMT to 85131 0 GMT for

Madison, WI.

### MOVIE

Displays a sequence of loops.

**Format** 

MOVIE 11 d1 12 d2 ... ln dn [keyword]

Default

MOVIE

This entry cancels the active movie on the specified channel.

**Parameters** 

l1,l2.. ln the loop to display; the range for the main display on a McIDAS-OS2 workstation is 1-79; the range for channel 2 on a WWW is 1-9 (no default)

d1,d2..dn the number of minutes to display the loop (default=.1 minute)

Keyword

CH= 1 displays the loop on the main display (default) 2 displays the loop on WWW channel 2

Remarks

To cancel an active movie process on channel 1, which is the main display, enter command MOVIE with no parameters. Use MOVIE CH=2 to cancel an active movie process on channel 2.

To stop the looping after the movie process is canceled, use the L command for channel 1, or press the 0 (zero) key on the ASCII keypad for channel 2.

Example

MOVIE 2 0.5 1 1 3 2

This entry displays loop 2 for one-half minute, loop 1 for 1 minute, loop 3 for 2 minutes and then repeats the sequence. This movie sequence runs continuously on the main display until you enter another MOVIE command to cancel it.

### MOVIT

Copies areas and updates an image frame loop.

**Formats** 

MOVIT bsarea esarea bdarea edarea f1 f2 locate y-coord x-coord mag line ele [keywords]

MOVIT bsarea esarea bdarea edarea f1 f2 locate station mag

line ele [keywords]

Default

MOVIT bsarea esarea bdarea edarea

This entry searches bsarea through esarea for the most recent time and copies the most recent image into the area following the latest

time in bdarea to edarea; it does not display the image.

**Parameters** 

bsarea beginning source area number of the data searched

esarea ending source area number of the data searched

bdarea beginning destination area number searched; must be

different than bsarea

edarea ending destination area number of the data searched

f1 first image frame number searched

0 does not display the images

f2 last image frame number searched

0 does not display the images

locate

type of coordinate the area transfers and TV load use as a

reference point; use one of these coordinate systems:

A area

E earth

I image

T TV

followed by one of these locations:

C centered

D lower-right corner

U upper-left corner

(default=AU)

y-coord y-axis coordinate (default=upper-left corner)

x-coord x-axis coordinate (default=upper-left corner)

station 3-letter station ID; must be preceded by EU, EC or ED

mag image resolution blowup (positive numbers) or blowdown (negative numbers); blowups repeat data values while blowdowns sample data (default=1)

line number dimension defining bdarea and edarea (default=500)

element number dimension defining bdarea and edarea (default=640)

Keywords

ASIZE = ALL moves an entire area including all bands

BAND= band number to move

line

ele

IR= 1 moves IR or sounder imagery documentation

MOVE= ALL moves all areas
TEST lists the AA commands generated to update the sequence

MOVIT locates and displays the area in the range bsarea to esarea with the most recent time and copies it into bdarea. It moves areas with the AA command. To sort bsarea through esarea by time, copying all areas, attach the keyword MOVE=ALL to the command. Keyword MOVE=TEST displays the AA commands without executing them.

The size of one TV frame is 500 lines by 640 elements.

Location Reference	Y-coord	X-coord	Format
A	line	element	0 to 3 digits
E	latitude	longitude	DDD:MM:SS
I	line	element	0 to 5 digits
T	raster	pictel	0 to 3 digits

#### **Examples**

#### MOVIT 1000 1010 3300 3310 MOVE=TEST

This entry displays the AA commands for copying the area with the most recent time between the range of 3300 to 3310.

#### MOVIT 1000 1010 3300 3310 10 20

This entry locates the most recent time in areas 1000 to 1010 and copies it into the area following the latest time in 3300 to 3310. It also displays the image after the latest image frame from 10 to 20.

### MSL

Lists information from the international master weather station list.

**Formats** 

MSL station [keywords]

MSL [keywords] "matchstring

Default

MSL station

This entry lists the station location information from the master

station list.

**Parameters** 

station 3- or 4-character station ID

5- or 6-digit station ID

"matchstring an alphanumeric string to match; maximum of

20 characters

ALL

Keywords

CO=

2-letter country code

FORM=

lists all information about a station

LAT=

min max latitude bounds to search

LON=

min max longitude bounds to search

ST=

2-letter state (PO abbreviation) or international

regional code

TYPE=

RADAR

lists radar stations

RAOB

lists RAOB stations

SURF

lists surface hourly stations

SYNOP lists synoptic stations

Remarks

The MSL command searches the international master weather station list for station identifications, latitude, longitude, station elevation, type of station and regional areas. Station and runway elevations are given in meters.

The codes under DATA TYPE in the output from MSL are:

Code	Meaning	
A	TAF forecast	
В	coastal/SMARS	

Code	Meaning	
$\overline{\mathbf{C}}$	short range terminal forecast	
D	radar	
I	3-hourly synoptic	
L	PLATF forecast	
M	6-hourly synoptic	
N	off-hour synoptic	
0	AERO	
P	PIBAL	
R	RAOB	
T	METAR	
W	service airways	

#### **Examples**

#### MSL TAP

This entry lists the location information for Tapachula, Mexico.

#### MSL ST=WI

This entry lists all stations in Wisconsin.

#### MSL ST=WI TYPE=RADAR

This entry lists all radar stations in Wisconsin.

#### MSL CO=US "AFB

This entry lists all Air Force bases in the United States.

#### MSL LAT=-40 -10 LON=-160 -110 TYPE=RAOB

This entry lists all RAOB stations between 40° S and 10° S latitude, and 160° E and 110° E longitude, i.e., the Australian continent.

#### MSL CO=SP "AIRPORT

This entry lists all airport stations in Spain.

### N

Toggles the dual channel enhancement in and out of the video refresh data path.

Remarks

To use the N command,

Press: Alt N

or

Type: N
Press: Enter

The N command works only on tower and WIDE WORD workstations.

When the system moves the pseudocoloring table in and out of the video refresh data path, the current and opposite frame images are combined pixel by pixel. The combination is displayed on the TV monitor.

### 0

Switches the image frame position to the opposite frame.

#### Remarks

Since graphics frames have no opposites, their frame numbers do not change.

To use the O command,

Press: Alt O

or

Type: O

Press: Enter

Constraint Cill lists blocks of data by "sets" and "parts." A set in by m

#### See Also

Use command LS to assign opposite frame numbers.

### OD

Lists the digital area inside the cursor.

**Format** 

OD mode data a b c [keyword]

Default

OD

This entry lists the data for the area inside the cursor. The data type is the type stored in the area and depends on the sensor source.

**Parameters** 

mode C contours data

E enhances data (levels 0-63)

F data frequency distribution

I data interval percentage

L lists data (default)

S lists data by sensor source; GOES visible only

data

A values stored in an area (default)

B gray scale brightness conversion (levels 0-255)

R VAS or AVHRR radiance

T temperature conversion, Kelvin x 10

a, b, c

for mode I, specify a and b as the data range; for mode C, specify a as the contour interval, and b and c as the horizontal and vertical replicators

Keyword

BAND= band number (default=from the frame directory)

Remarks

The output is the same resolution as the digital area. Use keyword DEV to send output to the line printer.

Use command CUR or the left mouse button to set the cursor size. It is limited to  $51 \times 51$ , except for the L (list) mode.

Use the D key to determine the available data types in the area.

Command OD lists blocks of data by "sets" and "parts." A set is 50 or less lines of data. A part is the amount of data that fits on one line of the text screen or printer. This number varies depending on the data's field width and the output device. The set and part numbers are the x and y coordinates, respectively, of the data blocks in relation to the upper-left corner of the cursor. See the last example.

The default data parameter is the calibration type. To determine the calibration type, use: LA area FORM=ALL.

#### **Examples**

#### OD F

This entry lists a histogram of the data inside the cursor. It is linearly scaled so that a small peak in the distribution is less than one level on the graph. Consequently, the peak is not displayed.

Suppose you've displayed a GOES VIS image and you want to list the default values in the cursor area. To do this, enter:

#### OD L

This entry lists the digital brightness values in the cursor area on the image, as the default calibration type for a GOES VIS image is BRIT.

#### OD L T

This entry lists the data for the area inside the cursor on the CRT, converting it to Kelvin. Use this entry with IR data.

#### OD L B 100 150

This entry lists the digital brightness values inside the cursor. The values are on a scale from 100 to 150.

Suppose you've displayed a GOES IR area at full resolution (4 km). If the cursor size is 115 lines by 15 elements and you want to list digital radiance data on the text screen, enter:

#### OD L R

This entry lists 6 blocks of data, for a 115 x 15 pixels cursor, by sets and parts like this:

Block	Set, Part
1	1, 1
2	1, 2
3	2, 1
4	2, 2
5	3, 1
6	3, 2

Since there are 115 lines of data to list, OD breaks the data into 3 sets. Sets 1 and 2 have 50 lines each; set 3 has 15 lines. Because there are 15 radiance values to list per line and the screen can only display 9, OD displays each set in 2 parts. Part 1 shows the first 9 values; part 2 shows the last 6 values.

To determine where the data blocks lie in relation to the cursor, paste the parts together sequentially from left to right for each set. Then paste the sets together sequentially from top to bottom. The result looks like this:

	Part 1	Part 2
Set 1	Block 1	Block 2
Set 2	Block 3	Block 4
Set 3	Block 5	Block 6

### OS

### Sends a command to the OS/2 operating system.

**Format** 

OS "command

Default

No default; you must specify the command.

**Parameter** 

"command

OS/2 command to be performed

Remarks

The command string should include the correct path, if needed. It should not invoke a program that attempts to take control of the screen group, since McIDAS-OS2 assumes it is in control.

Example

OS "COPY A:STUFF.DAT C:\MCIDAS\DATA

This entry copies the file STUFF.DAT from the A drive to the

\McIDAS\DATA subdirectory.

### P

Locks and unlocks the cursor in its present position.

#### Remarks

The P key engages and disengages the mouse as a cursor position control.

Press: Alt P

or

Type: P
Press: Enter

Some commands, like PC, move the cursor and lock its position. When the cursor is locked, the letter P appears on the status line.

Revised 2/92

## PC

Positions the cursor at a desired point on the frame.

Formats	PC C	
	PC L s	tation
	PC E U	at lon
	PC I la	ine ele
	PC T n	aster pictel
Default	No defaul	t; you must specify a group of parameters.
Parameters	$\mathbf{c}$	positions the cursor at the center of the frame
losic ta positions.	L	positions the cursor at the station ID or synoptic ID
on Use status Side.	E	positions the cursor at the latitude and longitude earth coordinates
	I	positions the cursor at the line and element image coordinates
	T	positions the cursor at the raster and pictel TV coordinates
	station	station ID or synoptic ID
	lat	latitude of the location
	lon	longitude of the location
	line	image or graphics line of the location
	ele	image or graphics element of the location
	raster	TV raster of the location
	pictel	TV pictel of the location

Remarks

When you execute command PC, it disconnects the mouse from the cursor control. Use command P to regain cursor control.

#### **Examples**

PC E 36 - 98

This entry positions the cursor at 36° North and 98° East.

PC I 3300 1200

This entry positions the cursor at image coordinate line 3300 and element 1200.

PC L MSN

This entry positions the cursor over station MSN (Madison, WI).

PC T 100 356

This entry positions the cursor at TV raster 100, pictel 356.

### PID

Lists the names and Process IDs for each task running in McIDAS-OS2.

#### Remarks

The OS/2 operating system assigns a unique Process ID (PID) to each active task. Because some McIDAS-OS2 commands invoke other commands, the question mark (?) command does not always list all programs running. Rather, "?" returns the PIDs for tasks started directly from the keyboard.

To list all PIDs,

Type: PID
Press: Enter

You can use the Process ID with the slash (/) command to stop an active program. Any process appearing with an asterisk by its name should NEVER be terminated with the slash command. These are system programs that are required when running McIDAS-OS2.

## **PROMPT**

Edits command text and then executes it.

**Format** 

PROMPT "command

Default

No default; you must specify the command.

**Parameter** 

"command

the command text to edit and execute; quotes are

mandatory

Remarks

Use normal command line keyboard characters for editing.

Command PROMPT is commonly used in string tables.

PROMPT executed through a mainframe string table returns Xs in

place of the default parameters. Ignore them.

PROMPT in a mainframe string table automatically appends a period.

Example

TE A "PROMPT "MDU LIST

This entry places PROMPT "MDU LIST in the string table under #A.

Typing #A prompts you with MDU LIST.

## **PSB**

Displays a PLEASE STAND BY message on the text window.

**Format** 

PSB window

Default

No default; you must specify a window number.

**Parameter** 

window

the text window number on which to display the message;

the range is 5-9 (default=8)

Remarks

Command PSB is useful when the system invokes a McIDAS

command that takes a long time to run and does not give you any apparent feedback.

Example

PSB 5

This entry displays a PLEASE STAND BY message on text window 5.

### QA

### Deletes digital areas.

**Format** 

QA barea larea

Default

QA area

This entry deletes area only.

**Parameters** 

barea beginning area to delete

larea last area to delete (default=barea)

Remarks

Store areas in the C:\MCIDAS\DATA subdirectory so that other

McIDAS commands can access them.

**Examples** 

QA 101 120

This entry deletes areas 101 to 120.

**QA 101** 

This entry deletes area 101 only.

### REDIRECT

Writes the LW file path redirection memory block.

Formats REDIRECT ADD file "path

REDIRECT CLEAR type
REDIRECT LIST type

REDIRECT MAKE

REDIRECT REST rfile

REDIRECT SAVE rfile

Default REDIRECT

This entry places the redirected files and paths from LWPATH.NAM

into dynamic memory.

Parameters ADD adds a redirection entry to the active redirection file

(LWPATH.NAM) and dynamic memory

CLEAR clears the redirection entries

LIST lists the file redirection entries

MAKE writes the redirection entries from LWPATH.NAM into

dynamic memory (default)

REST restores a saved redirection file into file LWPATH.NAM

and dynamic memory

SAVE saves a redirection file

type FILE the file LWPATH.NAM

MEM the dynamic memory (default for the LIST

parameter)

ALL both LWPATH.NAM and dynamic memory; use

this option with CLEAR only (default for CLEAR)

file file to redirect, e.g., MDXX3074, AREA011\*; maximum of

12 characters including the extension

"path desired path; the quote is mandatory; maximum of 19

characters

rfile redirection file name with extension, e.g., TSTVL1.NAM,

TSTVL2.PTH; contains the files and paths that are

redirected (default extension=.NAM)

#### Remarks

REDIRECT can be used to redirect files such as MD, grid, area and virtual graphics. See Appendix G for more information.

#### Caution!

Redirection of these files will cause problems with your system. Do not redirect the files listed below.

ALLOC.WWW	NUM.FRM
CONTEXT.SLT	REDIRECT
EXPORT	SKEDFILE
FRAMED	STARTUP.SYS
FRAMENAV	STRTABLE
HELP.DAT	SYSIMAGE.VIF
HOST.PTR	VERSION.TXT
MENU	WINQUFIL

Do not redirect files with the extensions .MNU and .TAB. Also, the DOSTOLW command cannot be redirected.

Use an editor to add a comment line to a redirection file. Start the line with a quote, e.g., "This is a comment line.

The maximum length of a redirection path is 32 characters (12 character maximum for the file name and 19 character maximum for the path redirection). Two examples are:

AREA0001 A:\TEST\VOL1
IMAGES90.VIF A:\VOLUME\MDXX\SUBD

If your workstation is hung and you suspect file redirection is causing it, first EXIT McIDAS, then delete the file LWPATH.NAM in C:\MCIDAS\DATA. Now boot your system. If McIDAS doesn't come up, you may have redirected a McIDAS system file. In this case, you may need to reinstall McIDAS.

#### **Examples**

#### REDIRECT LIST FILE

This entry lists the redirections that are in the file LWPATH.NAM.

#### REDIRECT CLEAR

This entry clears the file LWPATH.NAM and the dynamic memory.

# REDIRECT ADD AREA137\* "A:\VOLUME\AREAS This entry adds redirection path A:\VOLUME\AREAS\AREA137\*

to the LWPATH.NAM and the dynamic memory.

#### REDIRECT REST TSTVL1

This entry brings file TSTVL1.NAM into both the dynamic memory and the redirection file LWPATH.NAM.

### REMAP

Remaps an area into a different projection.

**Format** 

REMAP sarea darea spline [keywords]

Default

REMAP sarea darea

This entry remaps sarea into the darea projection.

**Parameters** 

sarea

source area number to remap

darea

destination area number for the remapped image; darea

contains the projection that sarea is remapped into

spline

spline function (default=20 pixels)

Keywords

BAND=

band number (default=lowest band number)

MERGE= YES

merges the data in sarea with the data in darea

NO overwrites the data in darea (default)

SMO=

YES smooths the image

NO

does not smooth the image (default)

Remarks

Navigation must be on disk before you can remap images. Display

the new image with command DF.

The default for REMAP zeros out the destination area before remapping the source area into the new projection. The MERGE=YES keyword does not zero out the destination area. In this case, the source area data overwrites the destination area data.

Example

REMAP 1 2

This entry remaps area 1 into area 2 where area 1 is a GOES East image and area 2 is a GOES West image. After execution, area 2 contains the remapped GOES East image.

REMAP 710 6000 MERGE=Y BAND=4

This entry remaps the POES data in area 710, band 4, into area 6000, overwriting the area coverage that overlaps.

### REPEAT

Repeats a McIDAS-OS2 command using a string table.

**Format** 

REPEAT string start TO end BY inc start BY inc ... start BY inc [keyword]

**Default** 

No default; you must specify the parameters.

**Parameters** 

string string table prefix of the command(s) to execute; 1 to 12 characters

start

starting parameter value

end

ending parameter value

inc

values of the command parameters which are incremented during the execution of REPEAT

то

mandatory parameter indicating the range between start

and end

BY

mandatory parameter indicating the increment between

start and end (default=1)

Keyword

MAXN= maximum number of commands to execute (default=200)

Remarks

Before executing command REPEAT, set up your string table using ! number for each parameter to be incremented. number must begin at 1 and increment by 1.

An exclamation point (!) followed by an integer in a string will increment the parameter on each execution. Parameters may be decremented using a minus sign (-).

REPEAT is a PC command; command DUO repeats host commands.

Example

If the string table contains the following string:

LOAD: = DF !1 !2 EC 45 90

Then entering the command,

REPEAT LOAD 2000 TO 2010 BY 2 1 TO 6

will load area 2000 to frame 1, 2002 to frame 2, 2004 to frame 3...

and 2010 to frame 6.

### **ROUTE**

#### Routing table utility.

**Formats** 

ROUTE INIT

ROUTE ADD code type beg end file [keyword] "text

ROUTE DEL code1...coden ROUTE LIST code1...coden ROUTE REL code1...coden ROUTE SUS code1...coden

Default

ROUTE

This entry lists all routing table entries.

**Parameters** 

INIT initializes a routing table

ADD adds an entry to capture area, MD, grid or text data

DEL deletes routing table entries

LIST lists routing table entries (default)

REL releases routing table entries; begins capturing product

SUS suspends routing table entries; stops capturing product

code (1...n) product code or the first letter of the product code; you

must use a 2-letter code with the ADD option, as using a single-letter code will match all product codes that

start with that letter

type AREA captures area data

MD captures MD data
GRID captures grid data
TEXT captures text data

beg beginning area, MD, grid or text file number to store

the captured data

end ending area, MD, grid or text file number to store the

captured data

file file name to store captured data; it cannot include an

extension; use only with the TEXT option

"text text describing the data

Keyword

PP= posts a process batch file to run after the product is captured

Remarks

The INIT option initializes and creates the product file. You must run it before adding any entries to the routing table.

To receive a current list of UNIDATA product codes, contact SSEC operations.

**Examples** 

#### ROUTE INIT

This entry initializes the routing table.

ROUTE ADD U3 AREA 400 405 "MDR Radar Areas This entry routes the UNIDATA MDR radar areas with the product code U3 to areas 400 to 405 on the workstation, adding the description "MDR Radar Areas" to the entry listing.

ROUTE ADD RM MD 20 29 "Upper-Air - Mandatory Levels This entry routes the UNIDATA mandatory upper-air MD files with the product code RM to MD files 20 to 29 on the workstation.

#### ROUTE DEL U3

This entry deletes from the routing table the entry that captures product code U3.

#### ROUTE DEL U

This entry deletes from the routing table all entries that capture product codes beginning with the letter U.

#### ROUTE LIST

This entry lists all entries in the routing table.

#### ROUTE LIST R

This entry lists all entries that capture product codes beginning with the letter R.

#### ROUTE SUS U3

This entry suspends the entry in the routing table that captures product code U3.

#### ROUTE SUS U3 RM

This entry suspends the entries in the routing table that capture product codes U3 and RM.

#### ROUTE REL M

This entry releases all entries in the routing table that capture product codes beginning with the letter M.

### RUN

### Runs a McBASI program.

**Formats** 

RUN p1...pn FILE= [keywords] 'filename p1...pn [keywords]

RUN "statement

'"statement

Default

No default; you must specify a filename to run or a statement to execute.

**Parameters** 

p1...pn positional parameters read by the INPUT statement

filename name of the McBASI program to run; the extension

defaults to .MCB

statement

McBASI statement to execute immediately

Keywords

CLEAR= YES resets the values of the variables to zero or null

before starting the program (default)

NO variables retain the values from the previous RUN

FILE=

name of the McBASI program to run; the extension defaults to .MCB. This keyword is required when using RUN, but is invalid when using the single quote format (').

VAR=

name of the LW file to store the variable values in after running a program; the file contents are used to initialize the variables unless CLEAR=Y is specified

(default=BASICVV00)

Remarks

RUN will execute a tiny BASIC language program prepared using an ASCII editor. The BASIC reserved words are: KEYIN, PRINT, INPUT, LET, GOTO, GOSUB, RETURN, STOP, IF, LPRINT, OPEN, CLOSE, REM, LOCATE, PTABLE and POKE.

These are the available functions and pseudofunctions: CHR\$, SIN, COS, TAN, ASIN, ACOS, ATAN, EXP, LOG, LOG10, INDEX, LEN, VAL, STR\$, MID\$(STRING, BEG, NUMBR), TIME\$, DATE\$, EOF\$, TFILE\$, TAB, TFILD\$, TFILEC\$, TFILB\$, TFILA\$, MOD, NINT, INT, SORT, PEEK, PEEK\$, KSYS\$, KSYS and TABLE\$.

The arithmetic operators are: +, -, \*, /, \*\*

#### See Also

See Appendix H, McBASI Interpreter for McIDAS-OS2 in this manual for more information on McBASI interpreter commands, functions and sample programs.

#### **Examples**

#### RUN ".? SQRT (5.7)

This entry calculates and prints the value of the square root of 5.7. The question mark (?) is a substitute for PRINT.

#### 'MYPROG 27 #H

This entry runs the program in \MCIDAS\DATA\MYPROG.MCB and passes the value 27 and the current time (the string #H) to the INPUT statement(s) in the program.

#### RUN 27 #H FILE=MYPROG

This entry performs the same function as the previous one. Use this format for programs started from the system scheduler.

#### 'MYPROG CLEAR=NO VAR=MYVARS.VAR

This entry runs the program in \MCIDAS\DATA\MYPROG.MCB but recovers the values for all variables from the file MYVARS.VAR. The values are written back to this file when the program terminates.

#### RUN VAR=MYVARS.VAR FILE=MYPROG

This entry runs MYPROG.MCB, initializes all variables to zero, and writes the values of the variables into the file MYVARS.VAR when the program stops.

## RVF

Restores virtual frames saved with command SVF.

Format RVF bframe eframe name [keyword]

Default No default; you must specify the parameters.

Parameters beginning virtual frame number to load (default=1)

eframe ending virtual frame number to load (default=bframe)

name the name and extension used to save the frames with

the SVF command

Keyword FORMAT = OLD old format; no NAV or frame directory

NEW new format; saved with NAV and frame

directory (default)

Remark Use command RVF with VGA workstations only.

Example RVF 1 5 PICTURE FORMAT=NEW

This entry reloads frames 1 through 5 starting from file

PICTURE.VIF.

# SC

#### Grids and contours surface data.

**Format** 

SC parm map time [keywords] SC p1-p2 map t1-t2 [keywords]

Default

SC parm map

This entry contours parm on map in graphics color level 2 using the current day and time.

**Parameters** 

ABV absolute vorticity parm ADV advection divergence (10<sup>-6</sup> sec<sup>-1</sup>) DVG GUS wind gust (meters/second) MIX mixing ratio (g/kg) PCP precipitation (inches) PSL pressure at sea level SNO snow cover (inches) SPD wind speed (meters/second) STR streamline T temperature (° C) TD dew point (°C) THA theta (K) THAE theta E (K) VIS visibility (miles) vorticity (10<sup>-6</sup> sec<sup>-1</sup>) VOR ZCH height of the second cloud deck (100 feet) ZCL height of the ceiling (100 feet) **ZCM** height of the first cloud deck (100 feet) ZS station elevation (meters)

map

MID Midwest USA
NA North America
SAT satellite projection
USA USA
Post Office abbreviation

time

hour or HH:MM:SS; *time* defaults to the previous hour if the current time is less than 10 minutes past the hour (default=current)

- p1 p2 parameter difference used in contouring; subtract p2 from p1
- t1 t2 time difference used in contouring; subtract t2 from t1

#### **Keywords**

CINT= contour interval (default is parameter dependent)

COLOR= graphics color level; the range is -1 to -7 for dashed lines, 1-7 for solid lines (default=2)

DAY= d1 d2 year and day; use two values when contouring differences, YYDDD (default=current)

GRA= graphics frame number

GRIDF= grid file number (default=current grid file)

LAT= min max minimum and maximum latitude extents

LON= min max minimum and maximum longitude extents

MDF= f1 f2 surface history file number; use two values when contouring differences (default=last digit of the current Julian day)

UNIT= A plots values in American units
M plots values in metric units

This keyword only works for temperature and dew point.

#### Remarks

If you do not specify keywords COLOR, CINT, LAT, LON and MDF in the command, the string table is searched for the keywords. If the results are unexpected, use command TL to list the string table. The grid file is generated and the pointer is set the same as the terminal number.

Parameter advection (ADV) or divergence (DVG) is done by appending ADV or DVG, e.g., TADV, PSLDVG.

The day and time default to the current day and time, not the last available data on the PC.

#### Examples

#### SC STR SAT 12 MDF=1000

This entry contours streamlines at 12Z from history file 1000 in a satellite projection.

#### SC T MID

This entry contours the temperature over the Midwest for the current day and time.

#### SC PCP GRA=5 COLOR=7 LAT=20 40 LON=85 105

This entry contours precipitation in color level 7 on graphics frame 5. It uses a map with latitudes of 20° and 40° N and longitudes of 85° and 105° W.

SC PSL MID 18-18 MDF=7500-7501 DAY=90010-90009 This entry contours the 24-hour sea level pressure change from 18 GMT, day 009, to 18 GMT, day 010, 1990.

To generate derived parameters such as vorticity advection (VORADV), first create a vorticity grid as follows:

SC VOR USA

Watch the text screen for the location of the U and VOR grids, then enter:

IGG MAKE u-grid ADV vor-grid

substituting the correct grid numbers for u-grid and vor-grid.

Revised 2/92

# SCHE

#### Adds a schema to the schema file.

**Format** 

SCHE name

Default

No default; you must specify name.

**Parameter** 

name

the member name of the schema LW file

Remarks

To see an example of a schema file, enter LSCHE name on the host. New schema files for the PC should have the same format. You can create them on a word processor and then place them in the \MCIDAS\DATA subdirectory.

Before registering the new schema, use command DOSTOLW to create an LW file containing the schema text. Then use command SCHE to register the new schema in the PC schema file.

See "Registering MD File Schemas" in the Installation Procedure section of this manual for more information.

**Examples** 

#### SCHE DCISFC

This entry adds schema ISFC, which is the schema named in LW file DCISFC, to the PC schema file. The current version of this schema is included with each McIDAS-OS2 upgrade.

#### SCHE MYSC

This entry adds the schema named in the LW file MYSC to the PC schema file.

# **SCRDMP**

Writes graphics frames to a graphics printer.

Format	SCRDMP	mode	
Default	No default	t; you n	nust specify the mode.
Parameter	mode	0 1 -1 OKI	provides tiny, quick output of a VGA display on an HP Think Jet printer produces double height, quick output of a VGA display on an HP Think Jet printer prints good proportion, slow output of a VGA display on an HP Think Jet printer sends the current graphics frame to an OKIDATA printer (VGA display)
	i (seelmalais)	OKS	sends the current graphics frame to an OKIDATA printer for a sideways/expanded output (VGA display)
to salette vista legacine di saleta (1 saleta	control this strict this strict this strict the strict this strict the strict this strict	PJ EPJ SPJ	sends the current graphics frame to an HP Paint Jet printer; it takes 1 minute to print sends the current graphics frame to an expanded HP Paint Jet printer; it takes 3 minutes to print; 6 gray levels are available sends the current graphics frame to a sideways HP Paint Jet printer; it takes 10 minutes to print; 16 gray levels are available

Remarks

This command only works with HP Think Jet, HP Paint Jet and OKIDATA graphics printers.

Make sure the image frame is blank before you display the graphics to be printed. To erase the image frame, enter the command: EG I.

Example

#### SCRDMP OKI

This entry sends the current graphics frame to an OKIDATA printer.

# SEE

Lists the text in an LW file.

**Format** 

SEE file nchars [keywords]

Default

SEE file

This entry lists the contents of the named LW file on the screen.

**Parameters** 

file name of the LW file to list

nchars number of characters per card image (default=80)

Keywords

BEGIN= first line number to list; if negative, the number of the first

word to list (default=0)

LAST= number of lines from the end of the file to list (default=ALL)

NCA= number of lines to list (default=ALL)

STEP= number of lines skipped between the lines listed; if

negative, it steps backwards; this keyword only works on

80-character ASCII LW files (default=1)

Remarks

Command SEE attempts to list both LW files (80-character records with no carriage returns) and text format (up to 80 characters with imbedded carriage returns). As a result, keyword LAST may not

work properly with the text format.

**Examples** 

SEE LOGON

This entry lists file LOGON starting at card image zero (i.e., the beginning) stepping forward 1 card image until it reaches the end of the file.

SEE MYFILE BEGIN=25

This entry lists the text in LW file MYFILE beginning with line 25.

SEE SCHEMA BEGIN=99 NCA=15 STEP=-1

This entry lists file SCHEMA starting at card image 99, stepping backwards by 1 card image for 15 card images.

# SENAA

Copies digital data from McIDAS-OS2 to McIDAS-MVS.

Formats SENAA sarea darea locate y-coord x-coord mag line ele [keywords]

SENAA sarea darea locate station mag line ele [keywords]

Default SENAA sarea darea locate station

This entry copies the digital data from sarea to McIDAS-MVS darea

using the locate coordinate type.

Parameters sarea source area number of the data (no default)

darea destination area number (no default)

locate coordinate type used to load images; use one of these

coordinate systems:

E earth I image

followed by one of these locations:

U upper-left corner

C centered

D lower-right corner

y-coord y-axis coordinate (default=first element)

x-coord x-axis coordinate (default=first line)

station 3-letter station ID; must be preceded by EU, EC or ED

mag blowup or blowdown factor of the image (default=1)

line number of lines in darea (default=500)

ele number of elements in darea (default=640)

Keywords ASIZE= ALL moves the entire area including all bands; specify only sarea and darea when using ASIZE=ALL

ALL moves all bands

BAND= band number to move (default=8 for VAS, 4 for AVHRR)

DODF= frame number for automatic TV loads on PC workstations

EMAG= element only blowup or blowdown factor (default=1)

LMAG= line only blowup or blowdown factor (default=1)

MODE= PACK sends data in compressed form (default for async connections unless sending 2-byte data; otherwise, default=UNPACK)

UNPACK sends data in uncompressed form

PAKSIZ= number of bits per pixel to send when packing data, 6 or 8; see the Remarks (default=8)

PROD= sends a 2-character product code to the PC

STYPE= VISR reduces 2-byte data to 1-byte; see the Remarks

#### Remarks

The Z column in the area directory indicates the number of bytes per pixel in the area. Visible data is 1-byte, while most IR data is 2-byte. The 2-byte data is usually a raw value which can be operated on with calibration coefficients to convert the data to radiance, temperature or brightness. Keyword STYPE=VISR converts the original data to brightness data.

SENAA can extract single bands from multibanded data and retain full calibration when the area is being sent to the mainframe. The PC must be running version 5.0 or later. Note that multibyte data can only be sent in uncompressed form (MODE=UNPACK).

When sending visible data, you can reduce the transmission time by specifying PAKSIZ=6. SENAA ignores the two bits that are not useful for image display. IR data requires all eight bits of data.

#### **Examples**

#### SENAA 1 101 EC MSN X 500 640

This entry transfers area 1 from the PC to mainframe area 101. The image, with earth coordinates, is centered on Madison, WI. It is 500 lines by 640 elements.

#### SENAA 2 109 EC 43 89 X 350 640 STYPE=VISR

This entry transfers area 2 from the PC to mainframe area 109. The image, with earth coordinates, is centered over Madison, WI., and is 350 lines by 640 elements. STYPE=VISR reduces the 2-byte data to 1-byte data. This speeds up the transfer, but the resulting area will not contain radiance information from the PC area.

# **SENGRD**

Sends grids to the mainframe.

**Formats** 

SENGRD sgridf ALL dgridf dgrid

SENGRD sgridf bgrid egrid dgridf dgrid

Default

SENGRD sgridf ALL dgridf

This entry sends all the grids in the PC grid file sgridf to the

mainframe grid file dgridf.

**Parameters** 

sgridf source grid file number (no default)

ALL sends all grids in the grid file

bgrid beginning grid to send (no default)

egrid ending grid to send (default=bgrid)

dgridf destination grid file number on the mainframe (no default)

dgrid destination grid number in the mainframe grid file

(default=first available)

Remarks

This command sends grids from a PC grid file to a mainframe grid file. If the destination grid file already exists, it adds the grids to this grid file. If no grid file exits, it creates one with the same specifications as the source grid file.

Check the maximum number of grids allowed in the mainframe's grid file before using SENGRD. The default maximum is 159 grids, but no practical limit exists. Use IGU MAKE to create large grid files before transferring data.

Examples

SENGRD 1 ALL 7200

This entry sends all the grids in PC grid file 1 to the mainframe grid file 7200. If grid file 7200 exists, it appends the grids to the file. If the grid file does not exist, it creates one before sending the grids.

SENGRD 1200 20 X 1205 30

This entry sends grid 20 from the PC grid file 1200 to the mainframe grid file 1205, grid 30.

# SENLW

Sends an LW file to the host.

**Format** 

SENLW slwfile dlwfile [keywords]

Default

No default; you must specify the parameters.

Parameters

name of the source LW file on the PC, up to 12 characters for drive+path+name; use drive name: dfile to send a file from the specified drive to the host, e.g., A:MYFILE

(default=drive C)

slwfile

dlwfile name of the destination LW file on the host

Keywords

BEGIN= begins sending at the specified word; do not use this

keyword with keywords RANGE and PAGE

FLIP=

YES flips bytes of 32-bit words

NO does not flip bytes (default)

RANGE= beg end

beginning and ending pages to send; they must

be LW file page numbers; 1024 words per page

translates ASCII to EBCDIC; the source LW file

must contain only ASCII characters

Remarks

On the PC, the term 'LW file' ordinarily means a file in the

C:\MCIDAS\DATA subdirectory.

To send an LW file from the host to the PC while in the PC mode,

precede SENLW with a period (.).

Example

SENLW PCFILE HOSTFILE

This entry sends the LW file PCFILE to the host, renaming it

HOSTFILE.

# **SENST**

Sends the current string table to the host.

**Format** 

SENST HOST name initials

Default

No default; you must specify the parameters.

**Parameters** 

name

name on the mainframe

initials

HOST

author's initials (default=current initials)

Remarks

The current string table is the default string table on a workstation.

string table destination; you must enter HOST (no default)

Use the command .TU REST to restore the string table once it is on

the host.

Use host command SENST to send string tables to the PC.

Example

SENST HOST DEMO

This entry sends the current string table to the mainframe and stores

it with the name DEMO under the current user's initials.

# SF

## Displays an image frame.

**Format** 

SF frame

Default

 $\mathbf{SF}$ 

This entry displays image frame one.

**Parameter** 

frame

the image frame number to display (default=1)

Remarks

Press the F key to list the current frame number. On EGA and VGA workstations, this changes to the frame number regardless of content

as there is no distinction between images and graphics.

Example

SF 12

This entry displays image frame 12.

# SG

## Displays a graphics frame.

**Format** 

SG frame

Default

SG

This entry displays graphics frame one.

**Parameter** 

frame

the graphics frame number to display (default=1)

Remarks

Use command SG on tower and WIDE WORD workstations only. On EGA and VGA workstations, use the SF command to display a different frame. Press the F key to list the current frame number.

Example

SG 4

This entry displays graphics frame 4.

# **SHOMNU**

A debugging tool for the F Key Menu System.

Format SHOMNU menu

Default No default; you must specify the menu number.

Parameter menu number to debug (default=0)

Remarks Window 9 displays the user menu. Window 8 displays the command

strings. Windows 7, 6 and 5 (in this sequence) display the command

strings if extra space is needed.

See the McIDAS-OS2 F Key Menu System chapter in this document

for further details.

Example SHOMNU 1

This entry displays the interface screen for menu 1 in window 9.

Window 8 displays the command string.

# **SHOWVG**

Displays virtual graphics.

**Format** 

SHOWVG virt bframe eframe [keywords]

Default

No default; you must specify a set of parameters.

**Parameters** 

virt

virtual graphics number; the range is 1-9999

bframe

beginning graphics frame number

eframe

ending graphics frame number (default=bframe)

Keywords

ELE=

offsets the graphic by the specified number of elements

(default=0)

LINE=

offsets the graphic by the specified number of lines

(default=0)

Remarks

Command SHOWVG restores a virtual graphic saved on the PC. You create virtual graphics by appending keyword VIRT to any program that creates graphical output.

To list the virtual graphics saved on the PC, use PC command DMAP. DMAP VIRT lists all the virtual graphics files saved on the PC. Virtual graphics files are named VIRTnnnn where nnnn is the virtual graphics number.

Use keywords LINE and ELE to reposition the graphic. The specified values are constants that are added to the line and element coordinates when displaying the graphic.

**Examples** 

SHOWVG 1000 1 2

This entry displays virtual graphic 1000 on frames 1 and 2.

SHOWVG 1000 1 2 LINE=80 ELE=100

This entry is the same as the one above except it displays the virtual graphic 80 lines lower and 100 elements to the right of the original position.

Revised 9/91

# SKE

Enters a McIDAS-OS2 command in the system command scheduler.

**Format** 

SKE day time repeat interval [keywords] "command

Default

SKE day "command

This entry executes the McIDAS-OS2 command on the day specified. The start time is 0Z; the repetition is 1; the interval is 1 hour.

**Parameters** 

day day to initiate the command, YYDDD

time to initiate the command, HH:MM:SS; use colons

when specifying the time (default=1 hour)

repeat number of command executions; if you enter 999999,

the word MANY replaces it in the header (default=1)

interval time interval between command executions,

DDDHH:MM:SS; use colons when specifying the time; for one day enter 24:00:00 or 100:00:00 (default=1 hour)

"command

command to execute; the command length may be up to 160 characters (including spaces) minus the preceding positional parameters; to run the command on the host,

precede it with a period (.)

Keywords

ID= 4-di

4-digit number to identify the command in the scheduler (default=system assigned number)

NAME=

user ID to use for host commands

PROJ=

project number charged when you execute the command

(default=current)

TOL=

late tolerance, HH:MM:SS; if the PC is down or too busy for the command to run, the late tolerance determines how much time can pass before the command is skipped; if 10 to 24 hours are specified, the word BIG appears in the header; three seconds (:00:03) is the minimum

acceptable time (default=1 hour)

#### Remarks

Keyword ID must be a 4-digit number (or omitted). Use it to refer to a schedule entry for listing, suspension and deletion.

To enter a # command from the PC string table,

Type: "##command

Press: Enter

To enter a # command from the host string table,

Type: ".#### command

Press: Enter

If you schedule a command from the host, schedule a LOGON first or the command will not execute.

Place a period (.) in front of any command run from the host.

#### Examples

SKE 82340 13:30: 2 24:00: ID=3003 "LA 1 10 This entry runs PC command LA at 1330 GMT on each of two consecutive days (82340, 82341). The assigned ID for reference is 3003.

SKE 85100 00:00:01 999999 PROJ=7777 'DF 101 1 EC MSN This entry runs command DF once an hour every day (999999 is listed as MANY by SKL), beginning with day 85100 at one second after 0 GMT.

SKE 89137 14:40 1 ".SENAA 109 5 X X X 1 350 640 This entry runs command SENAA from the host at 1440 GMT on 89137. The computer time is charged to the default project number, which is the one used in the LOGON command scheduled just prior to the execution of this command.

## SKEWT

Plots a sounding on a skew T thermodynamic diagram.

Formats SKEWT station time [keywords]

SKEWT OUTL [keywords]

Default SKEWT station

This entry plots a skew T of station for the current day and time,

erasing the graphics before plotting.

Parameters station 5-digit station identification number (e.g., 72645 is

Green Bay) or a sequence number in a satellite

retrieval file

time RAOB time; enter 0, 03, 06, 09, 12, 15, 18 or 21 GMT

(default=0 or 12)

OUTL displays a skew T diagram without sounding

Keywords COLOR= color level of the skew T diagram/overlay; the range

is 1-7

DAY= year and Julian day, YYDDD (default=current)

GRA= graphics frame number (default=current)

MDF= MD file number for RAOB (default=current)

MIX= NO omits mixing ratio lines

OLAY= YES 1 draws an overlay on an existing skew T diagram

in yellow

YES 2 draws an overlay on an existing skew T diagram

in blue

NO does not draw an overlay; erases the plot first

(default)

PTOP= top pressure level on the diagram rounded to multiples

of 50 mb

RANGE= min max minimum and maximum Centigrade

temperature range of the diagram

ROW= row number of the data in the RAWI schema

(default=first occurrence of the data)

SIG= significant MD file number (default=current)

TYPE= RAWI uses rawinsonde schema

VAS uses VAS created data

UNIT= FT plots height in feet on the left axis

M plots height in meters on the left axis

MB plots pressure in millibars on the left axis

(default)

VDEV= YES displays an error message

NO does not display an error message (default)

#### Remarks

Graphics are automatically erased before each plot.

Heights are recomputed for hydrostatic consistency.

Any number of overlays may be plotted, but successive wind barbs and headers will overwrite the previous overlay's wind barbs and headers due to space limitations.

Dew point temperature is not plotted when dew point depression (temperature minus dew point temperature) rounds to a whole number that exceeds 30.

#### **Examples**

#### SKEWT 72645 12 PTOP=300

This entry plots a skew T diagram for station 72645 at 12Z. The highest pressure plotted is 300 mb.

#### SKEWT OUTL RANGE=-40 25

This entry plots a skew T diagram without the station plot, from -40° to 25° Centigrade.

To plot two soundings on one diagram, enter these two commands:

#### SKEWT 72655

This entry plots a skew T diagram for station 72655 at the current time.

#### SKEWT 72655 3 OLAY=Y COLOR=5

This entry plots a skew T diagram for station 72655 at 3 GMT on the same diagram in red.

# SKL

Lists the entries in the command scheduler file.

Format	SKL bid	eid [keyu	words] "matchstring
Default	SKL This entry	v lists all the	e schedule entries for your terminal.
cimeseago (doiault)			D. S.
Parameters	bid	The second secon	ning ID number to list; the range is 1-9999 lt=lists all entries)
.yours	eid	ending	g ID number to list (default=bid)
	"matchstr		nly the entries containing this string; racters maximum (default=no match performed)
Keywords	FORM=	ALL	uses as many lines of output as needed to list the entire command
	PROJ=	min max	project number or range of numbers in the scheduler to list (default=1000 9999)
	SORT=	ID PROJ RAW	sorts entries by ID number (default) sorts entries by project number lists in the order of occurrence in the schedule
"Ol-men Joseph Jacobs	git directly w	TIME	(unsorted) lists entries and sorts times in ascending order

Remarks

If you omit the beginning and ending ID numbers, all entries are listed. The output is described below.

Column	Output	Description
a for stated;	Title Thready o	terminal number
2	ID	command identification number
3	X/S	S suspends the scheduled command; X disables the terminal's schedule
4	Next Executn	next day and time to execute a command
5	#REM	number of remaining commands; if SKE repetitions is a 6-digit number, this will say MANY

Column	Output	Description
6	Interval	day and time interval between executions; the format is DDHH:MM:SS, entered by SKE interval where interval
		is 1 hour; if <i>interval</i> is 24, this output is listed as 1000000 (1 day)
7	TOL	late tolerance time, HH:MM:SS; any entry over 9 hours is listed as BIG
8	NAME:	initials used to log on
9	PROJ:	project number used to log on
10	Command:	command string to execute

#### Example

#### SKL 420 430 PROJ=7000

This entry lists the scheduled commands on the current terminal for project 7000 between 420 and 430.

Revised 9/91

# SKU

## Command scheduler utility function.

Formats SKU option bid eid [keywords]

SKU MSG device

SKU CHA bid eid [keywords] "command

SKU DOIT bid eid

SKU ON SKU OFF

Default SKU option bid

This entry performs option on bid, affecting the current terminal

number only.

Parameters option DEL deletes the entry for the schedule

REL releases the entry so the command executes at

the next scheduled time

SUS suspends the entry so the command will not

execute; this does not delete the entry from the

scheduler

MSG device specified for the scheduler text output

CHA changes the entry; it depends on the keyword used

DOIT executes a schedule entry without decrementing the

counters

ON turns the scheduler on

OFF turns the scheduler off

bid beginning ID number

eid ending ID number (default=bid)

device C sends output to the CRT

N does not list the output

"command new command or text to replace the current command

**Keywords** 

NAME = old new changes the old user ID to the new user ID

PROJ= old new replaces the old project number with the new

project number

Remarks

To change a schedule entry, you must be logged on to the project number listed in the entry.

Use parameter DOIT to test the schedule entries.

**Examples** 

SKU SUS 1001 1009

This entry suspends the schedule entries with IDs 1001 to 1009.

SKU CHA 1001 1009 PROJ=7000 5630

This entry changes the schedule entries with IDs 1001 to 1009 running at your terminal under project 7000 to run under project 5630.

SKU DOIT 5

This entry executes the command scheduled in ID number 5. It does not change the execution time or decrease the counter.

Revised 9/91

# SL

#### Lists surface station data.

**Formats** 

SL units station blime etime inc [keywords]

SL btime etime inc

SL btime etime

SL SET MDF= DAY=

SL RESET

Default

SL

This entry lists the current time's data availability.

**Parameters** 

units A lists values in American units

M lists values in metric units (default); if you enter A, American units will be listed until you reenter M; the

value is stored in the string table

station 3-letter identification or state Post Office abbreviation;

this can be one or more stations

btime beginning observation time of the listed station

(default=current)

or, the beginning time of the available data information listed (default=lists the current time's data availability)

etime ending observation time of the listed station, or the ending

time of the available data information listed (default=btime)

inc time increment for the time range, HH (default=1)

SET directs all listings to a history MD file

RESET resets the MD file to the terminal number MD file; do this

after using a history MD file

Keywords

CCH= high cloud coverage

CCL= low cloud coverage

CCM= middle cloud coverage

DAY= year and Julian day, YYDDD (default=current)

DIR= wind direction

GUS= wind gusts

MDF= surface history MD file number (default=current)

PCP= 6-hour precipitation total

PSL= surface pressure

SNO= snow cover

SPD= wind speed

T= temperature

TD= dew point

VIS= visibility

WX= weather, 1 to 8 characters

ZCH= high cloud height

ZCL= low cloud height

ZCM= middle cloud height

#### Remarks

If command SL does not work on your terminal, clear your string table by entering: TD ALL or MDX CLE.

To obtain information on history files and output, enter: SL HELP.

The day and time default to the current day and time, not the last available data on the PC. If you are not sure that your data is still current, use the time parameters.

Real-time surface files on the PC are the same as on the mainframe (1-10), with the last digit of the Julian day corresponding to the MD file.

The output units of the parameters are shown below.

Parameters	American	Metric	
wind speed	knots	m/s	
wind gusts	knots	m/s	
visibility	miles	km	
cloud height	feet	meters	
precipitation, snow	inches	cm.	
temperature	degrees F	C	
dew point	degrees F	C	

#### **Examples**

#### SL MSN 12 18 2

This entry lists surface station data for Madison, WI, from 12 to 18Z at 2-hour increments.

#### SL SET MDF=1000 DAY=91300

This entry points to history MD file 1000 and lists its data for day 91300.

#### SL RESET

When the above process is finished, this entry prompts the system to reset the MD file number to the terminal default.

#### SL ORD 15 10 DAY=92001 92002

This entry lists surface data from 15 GMT on day 92001 to 10 GMT on day 92002.

#### SL A WI 0

This entry lists surface data in American units for all Wisconsin stations for 0 GMT.

#### SL 12 23 WX=TRW

This entry lists all stations for the current day with thunderstorms between 12 and 23 GMT.

#### SL M MSN DSM 12 15

This entry lists the reports for Madison and Des Moines between 12 and 15 GMT in metric units.

#### SL 12 15

This entry lists surface data availability from 12 to 15 GMT.

#### SL 6:

This entry lists surface data availability from 6 GMT to the current time.

# SP

## Plots surface data.

Formats			time [keywords] t1-t2 [keywords]				
	SF pi	-pz map	ti-tz [keywords]				
Default	SP pa	rm map					
	This en	This entry plots parm on map in graphics color level 3 using the					
	current	day and	time.				
Parameters	parm	CLD	cloud cover; the range is 0 (clear) to 3 (ov	ercast)			
	onemitib no	GUS	wind gust (meters/second)				
		ID	station identification				
		MIX	mixing ratio (g/kg)				
		PCP	precipitation (inches)				
		PLOT	plots station model in the format: T	PSL			
			wx *				
				CLD			
		PSL	pressure at sea level				
		SNO	snow cover (inches)				
		T	temperature (° C)				
		TD	dew point (° C)				
		THA	theta (K)				
		THAE	theta E (K)				
		VIS	visibility (miles)				
		WIN	wind, DDFF, FF (m/s) meteorological flag	gs			
			Barb = $5 \text{ ms}^{-1}$ (~ 10 kts)				
		11777	$Flag = 25 \text{ ms}^{-1} (\sim 50 \text{ kts})$				
		WX	weather text				
		WXS	weather symbols				
		ZCH	height of high clouds (feet)				
		ZCL	height of low clouds (feet)				
		ZCM	height of middle clouds (feet)				
		ZS	station elevation (meters)				
		MID	Midwest USA				
	_	NA	North America				
		SAT	satellite projection				
		BAI	salemie projection				

hour or HH:MM:SS; time defaults to the previous hour if the time current time is less than 10 minutes past the hour (default=current)

Revised 9/91 3-167

USA Post Office abbreviation

**ÚSA** 

	p1 - p2	parameter difference used in plotting; subtract $p2$ from $p1$
	t1 - t2	time difference used in plotting; subtract $t2$ from $t1$
Keywords	COLOR=	graphics color level, the range is 1-7 (default=3)
	DAY=	d1 - d2 year and day; use two values when plotting differences, YYDDD (default=current)
	GRA=	graphics frame number (default=current)
	LAT=	min max minimum and maximum latitude extents
	LON=	min max minimum and maximum longitude extents
(total (constitut))	MDF=	surface history file number; use two values when plotting differences (default=last digit of the current Julian day)
	UNIT=	A displays values in American units M displays values in metric units (only works for temperature and dew point)

#### Remarks

If you do not specify keywords COLOR, LAT, LON and MDF, the string table is searched for the keywords. If the results are unexpected, use command TL to list the string table or TD ALL to delete it.

Day and time default to the current day and time, not the last available data on the PC.

#### Examples

#### SP T MID

This entry plots temperatures over the Midwest for the current day and time. Specify the time if you have not just downloaded the current data.

#### SP WIN LAT=20 40 LON=80 100 COLOR=1

This entry plots winds in color level 1 with latitude bounds 20° to 40° North and longitude bounds 80° to 100° West for the current day and time.

#### SP PLOT SAT 18 DAY=84300

This entry plots a station model over a satellite projection at 18 GMT, day 300, 1984.

#### SP T-TD WI

This entry plots the current dew point depression for Wisconsin.

SP T WI 12-12 MDF=2-1 DAY=88102-88101 UNIT=A This entry plots the 24-hour temperature change in degrees Fahrenheit from 12 GMT, day 101, to 12 GMT, day 102, 1988.

Revised 9/91 3-169

# SU

inhi

## Image data stretching utility.

Formats  APTER A REPORT OF A R	SU INI SU MAI SU MAI SU LIST	name ty KE name KE name	pe unit [keywords] inlo inhi blo bhi inlo inhi LEV=	
Default		SU LIST This entry lists the stretch tables saved on the PC.		
Parameters	INI	calibrati	es the stretch table defining the type of calibration, on units and initial breakpoint settings; must be making a new stretch table	
	MAKE	enters br levels	reakpoints in the table using VGA or brightness	
	LIST	lists the stretch tables saved on the PC		
	TABLE	lists the breakpoints stored in a stretch table		
	name	name of	the stretch table; 8 characters maximum	
	type	AAA TIRO MSAT VISR (default=	uses 2-byte GOES data calibration for the input table uses POES data calibration uses METEOSAT data calibration uses 1-byte GOES data calibration suse on any calibration type)	
	unit	RAW BRIT RAD ALB TEMP user defin	raw data calibration units of the input data brightness radiance albedo temperature ned units; use D to list all possible units for a mage	
	inlo	low value	e of the breakpoint for input values; specify in	

units input with the unit parameter (no default)

units input with the unit parameter (no default)

high value of the breakpoint for input values; specify in

blo low value of the breakpoint for output brightness

values; the range is 0-255 (no default)

bhi high value of the breakpoint for output brightness

values; the range is 0-255 (no default)

Keywords BAND= band number for the input data calibration type

(default=none)

LEV= levlo levhi low and high VGA levels of the breakpoint

output value; range is 0-15; use with the MAKE option only; do not use reserved

graphics levels unless NLEV>13

NLEV= number of output levels to use on a VGA workstation;

maximum of 16 (default=13)

RANGE= min max minimum and maximum values of the

input data; these values define the boundary of input values that can later

be stretched; the range is 0-255

Remarks

Use SU to make the tables that are specified with the SU= keyword in command DF. The SU command sets up tables to stretch raw, radiance, temperature, albedo or brightness values (depending on calibration) to a user-defined brightness value or VGA level. Then you can use command EU (or GU on a VGA) to color the brightness ranges known to correspond with the new values.

When you specify the keyword RANGE=, all input values less than or equal to min are assigned an output value of zero; all input values greater than or equal to max are assigned an output value of 255. Any additional breakpoints specified with the MAKE option that fall outside of min and max are assigned 0 or 255, accordingly. If you don't specify RANGE=, the stretches' slope previous to the first breakpoint is a continuation of the line formed by the first two breakpoints. Likewise, the slope following the last breakpoint is a continuation of the line formed by the last two breakpoints.

Normally, to display an image on a VGA workstation, you will stretch values between 20 and 240 evenly over the number of VGA levels (usually 13). Brightness values less than 20 are displayed as level zero; brightness values greater than 240 are displayed as level 15. For 13 levels, level zero contains brightness values 0-37, level 4 contains brightness values 37-58, etc.

Stretch tables are general structures that can be used on any workstation. They can be transferred to the mainframe using the SENLW command or to another workstation from the mainframe with .SENLW., or by diskette.

#### **Examples**

#### SU INI TIRORAD3 TIRO RAD BAND=3

This entry initializes the table TIRORAD3 to be used on the radiance values of TIROS band 3 images. Each new stretch table must be initialized.

#### SU MAKE TIRORAD3 0 1.2 20 220

This entry sets the breakpoint values in the above table TIRORAD3. Input zero corresponds to output 20; input 1.2 corresponds to output 220.

#### SU TAB TIRORAD3

This entry lists the breakpoints in table TIRORAD3, along with information on BAND, calibration type and units.

# SU INI MSATEMP1 MSAT TEMP BAND=1 NLEV=14 This entry initializes the table MSATEMP1 to contain breakpoints in temperature for METEOSAT band 1 data. Fourteen gray scale levels are displayed on a VGA; use LEVELS=14 in the DF command to display an image.

#### SU MAKE MSATEMP1 240 260 LEV=3 12

This entry stretches the temperature values from 240 to 260 in table MSATEMP1, over levels 3 to 12.

#### SU INI GENBRIT X BRIT RANGE=100 200

This entry initializes the table GENBRIT to be used on any calibration type with brightness units. The brightness values from 100 to 200 are stretched to brightness values 0 to 255. Brightness values entered with SU MAKE that are less than 100 or over 200 are assigned 0 or 255, respectively.

## **SVF**

Saves VGA workstation virtual frames that can be restored with command RVF.

Format SVF bframe eframe file

Default No default; you must specify the parameters.

Parameters beginning frame number to save (default=1)

eframe ending frame number to save (default=bframe)

file the file name in which to save the frames, 12 characters;

if you don't specify an extension, extension .VIF is

automatically appended (no default)

Remarks Use command SVF on VGA workstations only.

SVF saves the frames, NAV and frame directory in the specified file

in the \MCIDAS\DATA subdirectory.

Example SVF 1 5 PICTURE

This entry saves frames 1 through 5 in file PICTURE.VIF.

# **SYSKEY**

Sets system values for local McIDAS workstation networks.

**Format** 

SYSKEY name

Default

SYSKEY

This entry sets the system values to the defaults in SYSKEY.DOC.

**Parameter** 

name of the text file in the \MCIDAS\DATA subdirectory containing the values used to create the SYSKEY.TAB file (default=SYSKEY.DOC)

Remarks

#### Caution!

Creating or changing SYSKEY.TAB impacts the entire McIDAS workstation network. SYSKEY should be used by the network administrator only.

This command reads the values from text file SYSKEY.DOC into the LW file SYSKEY.TAB. The parameters defined for local McIDAS workstation networks are stored in SYSKEY.TAB. These parameters contain alphanumeric and integer values needed by workstations in the network. Words 2100-2499 are reserved for parameters unique to your network.

If your workstation is not part of a local McIDAS workstation network, SYSKEY.TAB should not be utilized. Workstation specific values should be accessed through User Common.

The SYSKEY.DOC file must be in DOS text format, i.e., lines end with a carriage return or carriage return/linefeed. To change SYSKEY.DOC, it is best to use a text editor as most text editors place a carriage return or carriage return/linefeed at the end of each line.

SYSKEY.TAB alphanumeric values are limited to 4 characters; integer values are limited to 10 characters.

Use command SYSVAL to list values directly from SYSKEY.TAB.

SYSKEY.TAB values can be placed directly into local command entries by using #SYS(word) to replace a parameter or keyword value. For example, LA 1 #SYS(2100) will list areas 1 to the value stored in SYSKEY.TAB word 2100.

## **SYSVAL**

SYSKEY utility.

**Formats** 

SYSVAL LIST bword eword SYSVAL CHANGE word value

Default

No default; you must specify the parameters.

**Parameters** 

LIST lists the values stored in the LW file SYSKEY.TAB

CHANGE cha

changes the value of a SYSKEY word

bword

beginning word number to list (default=1)

eword

ending word number to list (default=bword)

word

SYSKEY word number

value

new value to place in SYSKEY; must be numeric

#### Remarks

#### Caution!

Creating or changing SYSKEY.TAB impacts the entire McIDAS workstation network. The SYSVAL CHANGE option should be used by the network administrator only.

The parameters defined for local McIDAS workstation networks are stored in SYSKEY.TAB. These parameters contain alphanumeric and integer values needed by workstations in the network. Words 2100-2499 are reserved for parameters unique to your network. For a description of SYSKEY.TAB, see the file SYSKEY.DOC. This file should be updated regularly by the network administrator.

If your workstation is not part of a local McIDAS workstation network, SYSKEY.TAB should not be utilized. Workstation specific values should be accessed through User Common. SYSKEY.TAB values can be placed directly into local command entries by using #SYS(word) to replace a parameter or keyword value. For example, LA 1 #SYS(2100) will list areas 1 to the value stored in SYSKEY.TAB word 2100.

### Example

### SYSVAL LIST 2000 2010

This entry lists the contents of SYSKEY.TAB words 2000-2010.

## TD

Deletes one or more strings from the current string table.

**Formats** 

TD name

TD PREFIX prefix

TD ALL

TD ALL GLOB

Default

No default; you must specify the parameters.

**Parameters** 

name

a single string name to delete

prefix

deletes all strings that begin with the given prefix

PREFIX

searches for the string prefix

ALL

clears the system table, except for global strings

**GLOB** 

deletes all strings, including global strings

Remarks

A string name whose first character is a question mark (?) is defined as global. Global strings remain in the table unless you delete them by entering: TD ALL GLOB.

See Also

Command TL lists strings. Command TE edits strings. Command TU is the string utility that saves the current string table.

Command SENST sends string tables to the host.

**Examples** 

TD 9

This entry deletes the string named 9.

TD PREFIX CH

This entry deletes all strings that begin with CH.

TD ALL

This entry deletes all strings except those preceded by a question mark (?).

TD ALL GLOB

This entry deletes all string tables, including those preceded with a question mark.

## TE

## Enters a string in the string table.

**Format** 

TE string "text

Default

TE string

This entry assigns blanks to the string name.

**Parameters** 

string an alphanumeric string name, 1 to 12 characters; only the first character can be numeric (no default)

"text the value, command, or text defining the string; the text may be preceded with a pound (#) sign; two #s enter a PC string named #string; use four #s to name this string on the host; quotes are mandatory

Remarks

When #string appears in a command, it is replaced by its definition from the string table. When #SYS(word) or #UC(word) appears in a command, it is replaced by the value stored in the specified SYSKEY.TAB or User Common word, respectively. See the SYSVAL and UCU commands for more information.

The string name may contain numerals. An executable string name can have a number only as its first character. A non-executable or text string can have numbers in any position.

To execute a command entered under a string name, type #string. See the examples on the next page. If #string1 is included in another string (e.g., #string2), the value of #string1 is used when #string2 is executed.

A string name whose first character is a question mark (?) is defined as global. Global strings remain in the table unless you delete them by entering: TD ALL GLOB.

Note

You cannot use X as a string name since McIDAS interprets the letter X as a place holder for default values. Likewise, if you have a series of strings beginning with X (e.g., XMAP), you cannot delete these strings with TD PREFIX X nor execute them with REPEAT X 1 TO 1.

See Also

Use command TEDIT to edit a string. Command TL lists string tables; command TD deletes them; command TU is the string table utility.

### **Examples**

## TE LOAD "SEQ 105 108 1 4 EC MSN

This entry places an SEQ command in string LOAD. To execute the command, type: #LOAD.

# TE NOTE "MAP OF NORTH AMERICA IN SATELLITE PROJECTION

This entry stores the text MAP OF NORTH AMERICA IN SATELLITE PROJECTION in string NOTE.

#### TE MAPS "MAP NA

This entry stores the command MAP NA under string MAPS. To execute the command, type: #MAPS.

## TE AAA 'TERM L ON

This entry stores the command TERM LON under string AAA.

#### TE ABQ "SL A ABQ

This entry places string ABQ in the string table. To execute the SL A ABQ command, type: #ABQ.

In the compound string example below, remember to define the string that replaces the # value before defining the string that uses it.

#### TE A '120

The replacement string is #A.

### TE LIST 'LA 100// #A

The actual string stored under LIST is LIST=LA 100 120.

To vary the value in #A, insert two # signs in string LIST: TE LIST 'LA 100 ##A
The actual string stored is LIST=LA 100 #A.

If you change string A now, the new value will be used when LIST is executed. For example, if you entered the following change:

TE A '150

The system would use LA 100 150 the next time #LIST was executed.

Assume the following string commands exist on the system.

TE LIST "LA 100 120; # # TVLOAD

TE TVLOAD 'DF 101 1 ED MSN

When #LIST is executed, the following commands are executed. LA 100 120

**DF 101 1 ED MSN** 

## **TEDIT**

Edits a string in the string table.

**Format** 

TEDIT string

Default

No default; you must specify the string name.

**Parameter** 

string

name of the string to edit

Remarks

The specified string is displayed on the command line at the bottom of your screen. Edit the string with the standard command line keys (e.g., right arrow, Insert, Delete, etc.). When you finish editing, press the Enter key to execute the new TE command.

Example

TEDIT LIST

In this example the command:

TE LIST "LA 101 10000

is echoed on the command line. Change 10000 to 105 and press the Enter key to change the string named LIST.

## **TERM**

Sets the state of the J, K, L, N, O, P, V, W, Y and Z toggles.

**Format** 

TERM toggle state

Default

No default; you must specify the parameters.

**Parameters** 

toggle

one of the letters J, K, L, N, O, P, V, W, Y or Z

state

ON

switches the toggle on (default)

OFF

switches the toggle off

Remarks

You will typically use command TERM when your workstation is not in a known state. For example, if you cannot predict the state of your graphics and you want them on, execute TERM W ON to guarantee they are on. TERM is commonly used in string tables, McBASI programs and macros. The valid commands and their toggles are:

Command	Function	Toggle ON	Toggle OFF
Joi ognado	Toggles graphics to the	connect	disconnect
Theirpages	loop control system		
K	Toggles the image frame on/off	visible	blank
L	Toggles frame looping on/off	start	stop
N	Toggles the N key on/off	on	off
0	Displays the opposite image frame	opposite	base
P	Toggles the joystick or mouse control on/off	connect	disconnect
V	Toggles the velocity cursor on/off	on	off
W	Toggles the graphics frame on/off	visible	blank
Y	Toggles image frames to the loop control system	connect	disconnect
Z	Toggles the WWW zoom on/off	on	off

**Examples** 

TERM L ON

This entry starts the frames looping.

TERM L OFF

This entry stops the frames looping.

## **TFILE**

Sends text output to a disk file.

**Format** 

TFILE mode window "file

Default

No default; you must specify the parameters.

**Parameters** 

mode OPEN

opens the file for saving text

CLOSE

closes the file (default)

**DUMP** 

dumps the contents of the text window to the

file

DO

dumps the current text window and then opens

the file

window

text window number; the range is 0-4 (default=current)

"file

file name to write into; quotes are mandatory

Remarks

The file name you specify must not be in use by another task, e. g., a word processor. It may be fully qualified up to 40 characters. The default path is C:\MCIDAS\DATA\.

When you activate a text file, the right end of the status line displays a yellow window number on a black background.

Example

### TFILE OPEN X "SAWI

This entry opens file SAWI and places any further output directed to the current window into that file.

## TL

## Lists the strings in a string table.

**Formats** 

TL ALL

TL OUT

TL [keyword]

TL prefix [keyword]

Default

TL

This entry lists the first 20 strings from the current string table.

**Parameters** 

ALL

lists the strings that begin with 0-9 or A-Z; the maximum

is 256

OUT

lists all strings, including global strings

prefix

lists the strings that begin with this prefix

Keyword

NUM=

number of strings to list (default=20)

Remarks

Strings in the string table are stored alphabetically with numbers 0 to

9 at the beginning of the table.

A string whose first character is a question mark (?) is called a global

string. It is listed with TL OUT or TL?.

You can list other strings that do not begin with 0-9 or A-Z with

TL OUT.

See Also

Use command TD to delete strings and TE to enter strings. Command

TU is the string table utility.

**Examples** 

TL CH

This entry lists the strings that begin with CH.

TL ALL

This entry lists all strings; the maximum is 256.

TL NUM=10

This entry lists the first 10 strings in the string table.

TL SORT NUM=15

This entry lists the first 15 strings following SORT.

## TU

## String table utility.

**Formats** 

TU SAVE name [keyword]

TU DEL name
TU LIST initials

TU REST name initials [keyword]

Default

TU

This entry lists all the string tables on the workstation.

**Parameters** 

SAVE

saves the string table

DEL

deletes the string table

LIST

lists the string tables on the workstation (default)

REST

restores a string table to your workstation and makes

it the current string table

name

1- to 12-character name identifying the string table

(default=the current user)

initials

1- to 4-character name identifying the user who saved

the table (default=logon initials)

ALL lists all tables (default=your initials)

Keyword

SAVEFILE= LW file name to store the table in or restore the table

from

Remarks

You may restore any table by entering the desired table name and author's initials. You cannot save over or delete another user's tables.

There is a maximum of 512 saved tables.

A string name whose first character is a question mark (?) is global and remains after each restore.

### **Examples**

#### TU SAVE DEMO

This entry saves the current string table under the name DEMO.

#### TU REST DEMO

This entry restores string table DEMO to the current foreground.

#### TU REST COLOR

This entry restores string COLOR in your workstation, making it the current string table.

### TU SAVE CLOUDS

This entry saves the current string table under the logged on initials and the name CLOUDS.

### TU REST CLOUDS KJB

This entry restores the string table named CLOUDS which is stored under initials KJB.

## TU DEL CLOUDS

This entry deletes the string table CLOUDS. The logged on initials must match the saved initials.

## UC

## Grids and contours RAOB data.

_					
_	_	-	-	-	ts
_	O	п	11		135

UC parm level map time [keywords] UC p1-p2 l1-l2 map t1-t2 [keywords]

Default

UC parm level map

This entry contours parameter for level on the current graphics. It contours over the map in color level 2 using the current day and time.

#### **Parameters**

ABV absolute vorticity parm DVG divergence (10<sup>-6</sup> sec<sup>-1</sup>) MIX mixing ratio (g/kg) P pressure (mb) SPD wind speed (m/s) STR streamline T temperature (° C) TD dew point (° C) THA theta (K) THAE theta E (K) VOR vorticity (10<sup>-6</sup> sec<sup>-1</sup>)

 $\mathbf{Z}$ height (meters)

zsstation elevation (meters); use only with SFC level

level

MAXW maximum wind SFC surface TRO1 tropopause 1 TRO2 tropopause 2

1000-100 mandatory levels in mb

map

MID Midwest USA NA North America SAT satellite projection USA

USA

Post Office abbreviation

hour or HH:MM:SS; time defaults to the previous RAOB time if the current time is less than 1-1/4 hours past the RAOB time (default=nearest RAOB time)

p1 - p2 parameter difference used in contouring; subtract p2 from p1

11 - 12 level difference used in contouring; subtract 12 from 11

t1 - t2time difference used in contouring; subtract t2 from t1

### **Keywords**

CINT= grid contour interval (default is parameter dependent)

COLOR=

graphics color level; the range is -1 to -7 for dashed lines,

1-7 for solid lines (default=2)

DAY=

d1 - d2

year and day; use two values to contour

differences, YYDDD (default=current)

GRA=

graphics frame number (default=current)

LAT=

min max minimum and maximum latitudes

LON=

min max minimum and maximum longitudes

MDF=

f1 - f2

RAOB history file number; use two

values to contour differences (default=last

digit of the current Julian day plus 10)

#### Remarks

If you do not specify keywords COLOR, CINT, LAT, LON and MDF in the command, the string table is searched for the keywords. If the results are unexpected, use command TL to list the string table. A grid file is generated and its pointer set to your terminal number. Parameter advection (ADV) or divergence (DVG) is done by appending the parameter with ADV or DVG (e. g., TADV, ZDVG). The day and time default to the current day and time, not the last available data on the PC.

### **Examples**

### UC STR 500 SAT 12 COLOR=1

This entry draws streamlines at 500 mb on a satellite projection at 12 GMT in color level 1.

#### UC T 850 MID

This entry contours 850 mb temperatures over the Midwest for the current day and time.

Below is an example of vorticity advection.

### UC VOR 500 USA 12

This entry draws contours of relative vorticity at 500 mb on a USA map for the current day at 12Z. Three grids (U, V and VOR) are filed into the current grid file. Assume U is in grid 1 and VOR is in grid 3. Enter the following two command sequences.

### IGG MAKE 1 ADV 3

This entry creates a fourth grid containing vorticity advection.

## IGTV 4 100 USA DASH=NEG

This entry draws vorticity advection contours on a USA map, with a contour interval of 100. Negative values are dashed.

## UCU

Inspects the User Common (UC) memory block.

**Formats** 

UCU PEEK word

UCU POKE word value

Default

No default; you must specify the parameters.

**Parameters** 

PEEK lists the current value in User Common

POKE places a value in User Common

word specific word number in User Common (default=0)

value new value to place in User Common (default=0)

Remarks

User Common consists of workstation information that resides in memory. Programs access User Common to obtain current workstation configuration and state data. Each User Common word stores a separate piece of information, i.e., cursor line and element position, current image and graphics frame, current logon initials and project number. For a list of User Common words, see UC.DOC in the \MCIDAS\TOOLS subdirectory.

User Common values can be placed directly into local command entries by using #UC(word) to replace a parameter or keyword value. For example, LB 1 #UC(13) sets the image loop bounds from 1 to the value stored in User Common word 13.

#### Caution!

Do not alter User Common. If you incorrectly modify a UC value, you may need to power down the workstation to reinitialize its state.

Example

UCU PEEK 1

This entry lists the contents of User Common 1 (project number).

## UL

### Lists RAOB data.

**Formats** 

UL AVA [keywords]

UL ANL station time [keywords]
UL LIST station time [keywords]
UL MAND station time [keywords]

Default

UL

This entry lists the available RAOB data for the entire day.

**Parameters** 

AVA lists the RAOB data availability (default)

ANL lists the stability indices for the station

LIST lists the mandatory and significant levels

MAND lists the mandatory levels

station 5-digit station ID

time hour or HH:MM:SS (default=nearest 0 or 12Z RAOB)

Keywords

DAY= year and day of the data, YYDDD (default=current)

MDF= MD file number containing the data (default=the last digit of the current Julian day plus 10)

OPT=

- 0 lists the mandatory levels with parcel analysis; does not recompute heights or perform interpolations
- 1 lists the mandatory and significant temperature levels; does not interpolate winds at significant temperature levels or perform parcel analysis
- 3 lists mandatory and significant temperature levels and significant wind levels; recomputes all heights and computes wind pressure; does not perform parcel analysis
- 5 lists mandatory and significant temperature levels; interpolates winds at significant temperature levels; does not perform parcel analysis

lists mandatory and significant temperature levels and significant wind levels; makes interpolations for missing data and recomputes heights; computes parcel analysis (default)

PTEMP= YES computes the potential temperature and mixing

ratio for each level

NO does not compute the potential temperature and

mixing ratio (default)

SIG= significant MD file number (default=file corresponding

to keyword MDF)

ZMAX= lists the data levels less than or equal to ZMAX; height

is in meters (default=all levels)

#### Remarks

The units for precipitable water are in millimeters.

Significant level winds and temperatures are never reported for the same level. Keyword OPT defaults to a full vertical interpolation. This means that when a significant level temperature is reported, the wind speed and direction at that level are interpreted. Conversely, when a significant level wind is reported, the temperature and dew point at the wind level are interpolated. For no interpolation, use OPT=3.

The three keys in the significant level MD file schema (RSIG) are P1, P2 and P3. They are used for significant wind and temperature reports. If a significant wind is reported, P1 is the direction, P2 is the speed and P3 is the height. If a significant temperature is reported, P1 is the temperature, P2 is the dew point and P3 is the pressure.

The day and time default to the current day and time, not the last available data on the PC.

### **Examples**

### UL LIST 72645 12 DAY=92010

This entry lists the mandatory and significant levels from day 92010, at 12 GMT, station 72645.

### UL AVA MDF=6512 DAY=90250

This entry lists the available RAOB data in MD file 6512, day 90250.

## UP

## Plots RAOB data.

F	0	r	n	18	a	ts	
•	_	•	••		_		

UP parm level map time [keywords]
UP p1-p2 l1-l2 map t1-t2 [keywords]

Default

UP parm level map

This entry plots parm for level over map in color level 3 using the current day and time.

**Parameters** 

parm IDN 5-digit station identification; the first 2 digits

are dropped in the PLOT option; IDs are plotted

only for the surface level

MIX mixing ratio (g/kg)
P pressure (mb)

PLOT plots station model in the format: T PSL

TD

T temperature (° C)
TD dew point (° C)
THA theta (K)
THAE theta E (K)

WIN wind, DDFF, FF (m/s) meteorological flags

Barb = 5 ms<sup>-1</sup> (~ 10 kts) Flag = 25 ms<sup>-1</sup> (~ 50 kts) surface height (meters) station elevation (meters)

level N

ZS

MAXW maximum wind SFC surface

TRO1 tropopause 1 TRO2 tropopause 2

1000-100 mandatory levels in mb

map

MID Midwest USA
NA North America
SAT satellite projection

USA USA

Post Office abbreviation

time

hour, HH:MM:SS; time defaults to the previous RAOB time if the current time is less than 1¼ hours past the RAOB time (default=nearest RAOB time)

p1 - p2 parameter difference used in plotting; subtract p2 from p1

11 - 12 level difference used in plotting; subtract 12 from 11

t1 - t2 time difference used in plotting; subtract t2 from t1

Keywords

COLOR= graphics color level; the range is 1-7 (default=3)

DAY= d1 - d2 year and day; use two values to plot differences,

YYDDD (default=current)

DECLUT=YES declutters the display by not plotting values

that overwrite another (default)

NO does not declutter the display; plots values that

overwrite each other

GRA= graphics frame number (default=current)

LAT= min max minimum and maximum latitudes

LON= min max minimum and maximum longitudes

MDF= f1 - f2 RAOB history file number; use two values to

plot differences (default=last digit of the current

Julian day plus 10)

Remarks

If you do not specify keywords COLOR, LAT, LON and MDF in the command, the string table is searched for the keywords. If the results are unexpected, use command TL to list the string table. The day and time default to the current day and time, not the last available data on the PC.

#### Examples

#### UP T 850 MID

This entry plots current temperatures at 850 mb over the Midwest.

## UP IDN SFC USA COLOR=5

This entry plots station numbers over the USA in color level 5.

UP WIN 850 X 0 MDF=6512 LAT=30 45 LON=80 100 This entry plots winds at 850 mb, 0 GMT in MD file 6512. The latitude range is 30° to 45° N; the longitude range is 80° to 100° W.

## UP Z 500-1000 USA

This entry plots the current 1000/500 mb thickness over the U.S.

#### UP T-TD 850 USA

This entry plots the current dew point depression over the U.S.

## UP Z 500 USA 12-12 MDF=15-14 DAY=92025-92024 This entry plots the 24-hour 500 mb height change from 12 GMT, day 92024 to 12 GMT, day 92025.

## ٧

Toggles the velocity cursor on/off when tracking cloud drift winds.

#### Remarks

The V key toggles the velocity cursor on/off. This establishes a fixed jump in the cursor for each frame in your loop bounds which helps track cloud features. You must be in a cloud tracking session to use V. When mainframe command MW is entered to start the session, the V command is turned off. A "V" is displayed on the text window status line when the velocity cursor is on.

To use this command,

Press: Alt V

or

Type: V

Press: Enter

lettende reinge is 30° to 45° N; the longitude range is 30° to 10

This turns the velocity cursor on. Set the velocity increment by aligning the cursor over a cloud target on the first frame of your loop. Advance to the second frame with the left mouse button (it functions like Alt A), then align the cursor over the similar cloud feature. Doing this on the first and second frames sets the increment for all frames in the loop.

If you don't use the velocity cursor, you will be manually selecting each target which can be quite tedious, but is advisable when doing single pixel cloud tracking.

## **VASTBL**

Creates calibration transforms for VAS (Mode AA) data.

### Remarks

You only need to run this program if you use AA VAS data on your PC. To use this command,

Type: VASTBL Press: Enter

This command generates a file called VASTBLS that is used with Mode AA VAS data. It takes several minutes to run and generate a file of about 6 megabytes.

Revised 9/91

## VV

## Computes the velocity vector.

**Format** 

VV [keywords]

**Parameters** 

none

**Keywords** 

COLOR= color level of the plotted velocity vector flags (default=3)

SIZE= relative size of the plotted velocity vector flags (default=10)

Remarks

You must set the image and graphics frame loop bounds before running command VV. The maximum number of images in a loop is 10.

For an image loop, choosing the cloud target positions manually from two images (manual lock by pressing the right mouse button) automatically calculates (auto lock) the target positions for the rest of the images. You can manually relock any of the auto lock targets to a different position without affecting the other target positions.

When you run VV, the following message appears on the screen.

Move mouse to position the cursor on the image frame.

Press the LEFT mouse button to advance one frame in the loop.

Press the RIGHT mouse button to lock the cursor on the frame.

Press BOTH mouse buttons to compute the velocity vector.

To exit VV, press both mouse buttons immediately after computing the velocity vector, i.e., double click both buttons.

Choosing a cloud target draws a default  $10 \times 10$  cross on the graphics frame. After the calculation, wind bars are drawn on all graphics frames starting from the second one. The calculated velocity is listed on the text screen. Speed value is in meters per second.

## W

Toggles the graphics frame on and off.

Remarks

To turn the graphics overlay frame on and off,

Press: Alt W

or

Type: W Press: Enter

This entry does not alter the contents of the graphics frame.

On VGA workstations this is simulated by setting the three graphics levels (1-3) to a dark gray.

See Also

Command K toggles image frames on and off.

## X

Tracks cloud drift wind targets with one keystroke.

#### Remarks

You can use the X key in place of the right mouse button when tracking cloud drift winds. It makes one wind measurement for each pair of frames in the loop bounds without stepping through the frames.

For example, in a loop of three images, you would press the right mouse button four times to make two wind measurements. The X key will make the same measurements by reading the cursor displacement on each frame without advancing through the frames; it's handled through the software so nothing mechanical is seen. This technique is useful if you find consistent flow in a large cluster of clouds.

To use this function,

Press: Alt X

or

Type: X

Press: Enter

## **XSECT**

Displays a vertical cross section.

**Format** 

XSECT bid eid [keywords] "text

**Default** 

XSECT bid eid

This entry displays a cross section of isentropes drawn from mandatory and significant level information contained in the current RAOB and RSIG system MD files. The reporting stations used lie within a 500 km wide corridor along the cross section axis between the beginning and ending station ID numbers.

**Parameters** 

bid beginning station ID number

eid ending station ID number

"text cross section title; up to 42 characters (default=day time)

Keywords

CINT= c1...cn contour interval (default=see table)

COLOR= 11... ln contour color level (default=see table)

DAY= MD file Julian day, YYDDD (default=current)

ERASE= NO does not automatically erase the graphics frame

YES automatically erases the graphics frame (default)

FORM= f1...fn see the table for the defaults

DIR reported wind directions, 0-360° clockwise from

the north

MIX derived mixing ratios, g/kg

SPD reported wind speeds, m/s

SPDE derived wind speed projected normal to the

cross section axis and enhanced by thermal information through the geostrophic wind

equation, m/s

SPDN derived wind speed normal to the cross section

axis, m/s; see the Remarks

SPDS derived wind speed tangential to the cross

section axis, m/s

SPDZ derived vertical wind speed shear, 1/s

T reported temperature, C

TD reported dew point temperature, C

THA derived isentropes, K

U derived u-component of the reported wind speed, m/s V derived v-component of the reported wind speed, m/s WIN wind barbs of the reported winds, kt  $\mathbf{Z}$ reported heights, m GCOLOR= background border and interior grid color (default=5) GRA= graphics frame (default=current) IDN= id1...25 station ID numbers for the cross section LABEL= YES displays parameter labels (default) NO does not display parameter labels LAT= end beg latitude limits for the cross section (default=eid bid) LDASH= draws dashed contours (default=see table) all values are dashed -1 only negative values are dashed 0 no dashing LINT= label interval of contours (default=see table) LON= end beg longititude limits for the cross section (default=eid bid) LSIZE= label size of contours (default=see table) MAP= NO does not plot a map showing the cross section location (default) YES plots a map showing the cross section location mand sig mandatory and significant level MD file numbers (default=current RAOB and RSIG). Set sig to 0 if only mandatory levels are needed. Giving sig a value is only valid when mand is specified. graphics quarter panel number: 0, 1, 2, 3, 4 (default=0) Specifying this keyword automatically sets the keyword ERASE to NO.

PBOT= bottom mandatory pressure level of the cross section (default=1050 mb)

PTOP= top mandatory pressure level of the cross section

(default=100 mb)

SMOOTH= smoothing factor (default=see table)

TCOLOR= title and ID label color (default=3)

TIME= MD file time, HH:MM:SS (default=most current)

UNIT= units of contours (default=see table)

WIDTH= corridor half width in kilometers (default=±250 km)

Remarks

- IN

The first station specified with bid or the IDN keyword is always on the left edge of the display; the last station specified is on the right edge. The stations selected with the LAT/LON keywords are displayed first on the left and last on the right, based on whether the longitudinal or latitudinal extent of the cross section is larger. Consequently, if you reverse the order for selecting stations, the orientation of the cross section will be affected. Altering the order may also impact the intermediate station selections as stations are included/excluded in order from first to last.

The maximum number of stations is 25. When two stations projected along the cross section axis lie too close to each other to allow a solution for the contouring algorithm, the station farthest from the beginning of the cross section is excluded.

If more than 25 stations are selected with the IDN keyword, the program will abort. If more than 25 stations are selected using the bid/eid parameters and the LAT/LON keywords, the program will not abort, but will use only the first 25 stations selected and appropriate error messages are listed.

If a station report is missing a surface pressure or reports less than three levels of information, it is excluded. If a station provides a partial report, the missing levels are not included in the contouring analysis and that area of the cross section display is left blank.

The MDF keyword has two parameters. The second parameter is only valid when the first parameter refers to a RAOB MD file. The second parameter is assumed to be its corresponding RSIG MD file. When only the mandatory RAOB levels are included in the vertical contouring, the second parameter must be set to zero.

You can specify the FORM keyword options in any combination and order. However, the sequence must be maintained when invoking any of the context specific keywords, i.e., CINT, LINT, COLOR, UNIT, LDASH, LSIZE or SMOOTH.

Graphics options conform to the IGTV standards.

If you use the PAN keyword, the keyword ERASE is set to NO.

The orientation for SPDN and SPDS with respect to the cross section axis is the positive tangential direction. This direction is along the cross section axis going from the last station towards the first station with the positive perpendicular (normal) direction following a right-hand rule, i.e., positive to the right relative to the positive tangential direction. This scheme results in the mathematically appropriate sign which is appropriate for the cross section orientation but may not be equivalent to the physically intuitive sign that you may anticipate. The SPDN and SPDS signs will vary with the cross section orientation although the contour patterns are very similar.

XSECT checks for missing values and obviously bad data, e.g., negative temperatures. If the cross section output seems incorrect, run command SKEWT or UL on the suspect station soundings to check the input values.

The table below defines the defaults for the keyword FORM.

FORM	CINT	COLOR	LDASH	LINT	LSIZE	SMOOTH	UNIT
DIR	90	1	-2	1	6	20	deg
MIX	2	4	-2	1	6	20	g/kg
SPD	5	2	0	1	6	20	MPS
SPDE	5	2	-1	1	6	40	MPS
SPDN	5	2	-1	1	6	20	MPS
SPDS	5	2	-1	1	6	20	MPS
SPDZ	5	2	-1	1	6	40	1/S
T	5	5	-1	2	6	20	Ċ
TD	5	4	-1	2	6	20	C
THA	5	5	-1	2	6	20	K
U	5	2	-1	1	6	20	MPS
V	5	2	-1	1	6	20	MPS
WIN	NA	7	NA	NA	8	NA	KT
Z	1000	1 .00138,0	-1	5	6	20	M

## **Examples**

### XSECT 72747 72203

This entry displays an isentropic cross section from station reports lying within a 250 km corridor along a cross section axis from station 72747 to station 72203.

## XSECT 72747 72203 MAP=Y

This entry is the same as the first example, but it also displays a map in the upper-right corner which indicates the location of the cross section axis and the included stations.

### XSECT 72747 72203 FORM=MIX THA SPD

This entry is the same as the first example, but it also overlays the mixing ratio, isentropic, and isotach cross sections.

#### XSECT 72747 72203 PTOP=400 WIDTH=150 FORM=MIX

This entry displays a mixing ratio cross section for a narrower corridor width along the same cross section axis as in the first example. It emphasizes the lower levels by limiting the top pressure level to 400 mb.

## XSECT 72747 72203 FORM=MIX THA SPD COLOR=1 2 3 CINT=X 5 10

This entry is the same as the second example, except the color level for the mixing ratio contours is set to 1, the isentropes to 2, and isotachs to 3. It uses the default contour interval for the mixing ratios. The isentropic contour interval is set at 5 degK, while the isotach contour interval is set at 10 m/s.

## XSECT LAT=30 55 LON=100 FORM=SPD WIN UNIT=KT PBOT=500 PTOP=100 MAP=Y

This entry displays a cross section of wind speed in knots from 500 to 100 mb along 100 W from 30° to 55° N. Wind barbs are also displayed. Station selection occurs automatically.

## XSECT FORM=SPDZ SMOOTH=100 COLOR=4 IDN=72694 72681 72576 72562 MAP=Y LSIZE=10

This entry draws a cross section of vertical wind speed shear from Salem, Oregon, to North Platte, Nebraska, using the IDN keyword to specify the stations to include. The graphic displays a small map of the cross section location. The contours are in color level 4; the label size for the contours is 10 pixels. This entry also smooths the analysis by a factor of 100.

Revised 9/91

Y

Toggles image frames to and from the loop control system.

#### Remarks

To toggle image frames to and from the loop control system,

Press: Alt Y

or

Type: Y
Press: Enter

commands.

The loop control system consists of the A, B, L, O, J and LB

You can connect or disconnect the image frames from the loop control keys independently of the graphics frames.

Use command Y on tower and WIDE WORD workstations only.

## Z

Toggles the zoom and roam functions on and off on a WWW.

### Remarks

To turn the zoom and roam function on and off,

Press: Alt Z

Ibis comy writes the text on the current for m color level 1, 10

Type: Z

or symbolic placed at the center of the coreor.

Press: Enter

The Z command provides a 2-times blowup of the currently displayed image that can be roamed by moving the mouse.

## See Also

See command ZM to set a zoom factor other than 2.

## ZA

Places an annotation on the current graphics frame at the cursor position.

_					_
F	1	-	m	15	٠.
	v	ш	ш	16	٠.

ZA color height justify [keywords] "text

## Default

ZA "text

This entry writes the *text* on the current frame in color level 1, 10 pixels high.

#### **Parameters**

color graphics color level; the range is 1-7 (default=1)

height letter height in pixels (default=10)

justify

- L left justify the text; the upper-left corner of the first letter of the text or symbol is placed at the center of the cursor (default)
- R right justify the text; the upper-right corner of the last letter of the text or symbol is placed at the center of the cursor
- C centers the text; the top of the center letter of the text or symbol is placed at the center of the cursor; consecutive letters are written below the previous letter
- V vertical justification of the text; the upper-left corner of the text or symbol is placed at the center of the cursor; consecutive letters are written below the previous letter
- M mouse; see the Remarks below
- N numerous plots of the same text or symbol; the center letter of the text or the center of the symbol is placed at the center of the cursor

"text to write on the graphics frame; you may use uppercase and/or lowercase letters; quotes are mandatory

"\$text displays weather symbols or arrows on the graphics; enter a dollar sign (\$) before any of the alphanumeric characters below to plot the corresponding weather symbols

T	thunderstorm	K	s	snow	*
w	rain shower	Ÿ	F	fog	=
X	snow shower	*	C	clear	$\Box$
R	rain	0	ရ	partly cloudy	1

В	mostly cloudy		1	$\Sigma$
0	overcast	$\oplus$	2	\$
D	drizzle		3	
Н	haze	$\infty$	4	$\hat{\mathbf{\Omega}}$
Z	freezing rain	00	5	$\stackrel{\sim}{\sim}$
\$\$	\$		6	$\Diamond$
0	<b></b>		7	以

### Keywords

GRA= graphics frame number (default=current)

ENCL= C draws a circle around the text in the N mode E draws an ellipse around the text

TC= color hemisphere

color plots a hurricane symbol with the

specified color level; the range is 1-7

X plots a tropical cyclone symbol determines the direction of spirals

S southern hemisphere (default)

N northern hemisphere

WID= line width

#### Remarks

Release the Caps Lock key on the keyboard to write lowercase letters. Remember to press it again before entering the next command. McIDAS does not accept lowercase input for any other command.

When you choose the M(ouse) option, the position of the mouse and the clicking of its buttons control the location of the cursor text. Clicking the left mouse button repositions the start of the text at the cursor location. Clicking the right mouse button repositions the end of the text at the cursor location. The height is scaled as needed.

Tropical cyclone and hurricane symbols are always plotted at the center of the cursor, regardless of the justification specified.

### **Examples**

### ZA 3 15 "MCIDAS

This entry writes the word MCIDAS in uppercase letters in color level 3 on the current graphics frame. The entry is 15 pixels high and left justified.

### ZA 2 20 C GRA=2 "streamlines

This entry writes the word streamlines in lowercase letters in color level 2 on graphics frame 2. The entry is 20 pixels high and centered under the cursor's center.

### ZA 5 7 V "Nevada

This entry writes the word Nevada vertically on the current graphics frame in color level 5. The upper-left corner of the N is at the cursor's center. The letters are 7 pixels high.

## ZLM

Permits freehand drawing using the mouse.

**Formats** 

ZLM BOX color

ZLM CIRCLE color

ZLM DRAW color [keyword]
ZLM FILL color height width

ZLM FREE color

Default

ZLM

This entry draws a line in color level 3.

**Parameters** 

BOX

draws a box the same size and shape as the cursor

CIRCLE

draws a circle or ellipse within the cursor

DRAW

permits smooth freehand drawing

FILL

draws and fills a box the same size and shape as the

cursor

FREE

permits straight-line freehand drawing (default)

color

graphics color level; the range is 1-7 (default=3)

0 erases the graphics within the cursor when used

with FILL

height

height of the area to erase, in pixels (default=cursor

height)

width

width of the area to erase, in pixels (default=cursor

width)

Keyword

SMOOTH=

number of samples to take for running the average;

use with the DRAW option; larger numbers produce

smoother lines; maximum is 50 (default=3)

**Examples** 

**ZLM** 

This entry displays the response below on the screen.

Move mouse to position the cursor on the image frame.

Press the LEFT mouse button to select point for option.

Press the RIGHT mouse button to end option.

Press BOTH mouse buttons to end ZLM.

### **ZLM BOX**

This entry displays the response below on the screen.

Move mouse to position the cursor on the image frame. Press the LEFT mouse button to size the cursor. Press the RIGHT mouse button to draw the box. Press BOTH mouse buttons to end ZLM.

#### ZLM DRAW 4 SMOOTH=10

This entry displays the response below on the screen.

Move mouse to position the cursor on the image frame.

Press the LEFT mouse button and hold, while
moving the cursor wherever on the screen you want to draw.

Press the RIGHT mouse button to end option.

Press BOTH mouse buttons to end ZLM.

Following the above directions produces a smooth line drawing in color level 4 with a running average of 10.

## ZM

## Sets the zoom factor for a WWW.

**Format** 

ZM zoom

**Default** 

ZM

This entry sets the zoom factor to one.

**Parameter** 

 ${\it zoom}$  the blowup factor for the currently displayed image; the range

is 1-16 (default=1)

Remarks

Command ZM provides up to a 16-times blowup of the currently

displayed image, which can be roamed using the mouse.

See Also

Alt Z toggles the zoom function on and off. For more information, see

the Z command.

Example

ZM 10

This entry blows up the image 10 times.

MS

Sees the room factor for a WWW

734 acon

Default

I his entry sets the moon factor to one.

nameter seem the blowup factor for the currently displayed image; the range

(1=11miep) at-1 Bt

Command ZM provides up to a 16-times blowup of the currently

displayed mage, which can be rouned using the mouse.

Alt E toggles the zoom function on and off. For more information, see

the Z command.

2M 10

runs entry nows up the image 1 or those.

3-210

## F Key Menu System

## Introduction

This chapter describes how to create and test a Menu template file. The Menu system in McIDAS-OS2 is useful for creating command execution menus to simplify the user interface. By creating a Menu template file, you can predefine function keys with user commands and format display screens with menus. An auxiliary command, ASK, allows the system to solicit information from you when necessary. See the ASK User Interface chapter that begins on page 5-1.

Menus are displayed in color text on the workstation's IBM EGA (Enhanced Graphics Adapter) or VGA (Video Graphics Array) screen. The text content, color and format are completely flexible. To select a menu item, simply press one of the function keys (F1 through F12) on the workstation keyboard. Use these 12 function keys alone or with one of the Ctrl, Shift or Alt keys, giving 48 combinations. You can also define the Esc key, allowing each menu to contain up to 48 items.

More than a thousand menus may be on line at one time. The only limitation is disk space. Only one menu is displayed at a time; window 9 of the McIDAS-OS2 text user interface displays the menu. Menus may be nested, displaying a different menu (a submenu) on the screen. Typically, a Main Menu refers to various submenus that deal with a cluster of related workstation functions.

To access the Main Menu, press the Esc key while in any other menu. You can redefine the Main Menu within a submenu. Once a menu is defined, you can invoke the menuing subsystem by pressing the Esc key after McIDAS has started.

To create menus, you must supply a series of "templates" for each menu. All Menu templates must reside in the C:\MCIDAS\DATA subdirectory and have .MNU as their file name extension. Use the operating system editor or another editor to modify or create a new menu.

A Menu template is an ordinary ASCII text file with a carriage return at the end of each line. The following section describes its format.

A sample Menu template is provided at the end of this chapter. You may find it helpful to refer to it while working through the Menu template file description that follows.

Revised 12/90

## Creating a Menu Template File

To create a menu, define both the menu text and the commands associated with the function key combinations. A file that defines a menu or set of menus is called a Menu template. It is an ASCII text file containing instructions for the McIDAS-OS2 Menu system. These instructions obey certain format rules, i.e., the instructions need specific character positions. The first character in an instruction line defines the type of instruction. These characters include the following.

Character	Instruction
M or W	Menu or Window defines the menu number
	described by subsequent instructions. M is the
	preferred character, but W is also allowed since it
	was used in the old menu definition.
I was and an in	Initialization defines a McIDAS-OS2 command
	sequence to run when the menu is accessed.
he function T	Text defines the screen row and column where a
	string of text begins, the color and the text itself.
F www.ca doses;	The function key defines a McIDAS-OS2 command
	or sequence of commands to execute when a
	specified function key is pressed.
A State of the same of the	Alt + Function key defines a McIDAS-OS2 command
	or sequence of commands to execute when you press
	Alt and the specified function key simultaneously.
C	Ctrl + Function key defines a McIDAS-OS2
	command or sequence of commands to execute when
	you simultaneously press Ctrl and the specified
	function key.
S	Shift + Function key defines a McIDAS-OS2
	command or sequence of commands to execute when
	you press Shift and the function key simultaneously.
or editor to U	User Common Pokes define values to poke into User
	Common whenever this menu is displayed.
ASCE text fi	+ means a line is continued from the previous line
	(for A, C, F, I and S characters only).

If the first character in an instruction line is not one of those listed above, the system treats the line as a comment line and ignores it. Each of the characters is described in more detail below.

#### Instruction Characters

Each of the following instruction character descriptions contains a character definition, its format, parameter descriptions and example. The old character formats are also listed as you may be using some menu templates previously created with these formats.

## M (or W)

M is the menu number described by the subsequent instructions.

**Format** 

M number

**Parameter** 

number

is the number of the menu being defined; the range

is 0-9999

Remarks

All Menu template file instructions following an M instruction refer to the specified menu (window) until the system encounters another M instruction or reaches the end of the template file. Always define menu zero in any Menu template file.

Since the W character was used in the previous menu definition, you may use it in place of the M character. However, M is the preferred character. See the following example.

**Examples** 

M 7

This entry defines menu 7 using all subsequent instructions up to the next M or W instruction.

W 7

This entry defines menu 7 using all subsequent instructions up to the next M or W instruction. W 7 functions identically to M 7 and was retained for compatibility with the previous version.

**Old Format** 

columns 2-5

the menu number; the range is 0-9999

Revised 9/90

ı

I means initialization. It defines the McIDAS-OS2 commands executed each time this menu is displayed.

**Format** 

I "commands

**Parameter** 

"commands

the series of McIDAS-OS2 commands to run when

the menu is invoked

Remarks

No more than one I line, with no more than one continuation (+) line, may occur in any single menu. The I line is usually placed at the beginning of the Menu definition.

**Examples** 

Below are some useful McIDAS-OS2 commands.

IGU SET 1

This entry sets the workstation's local grid file number to 1, which is

the default.

MDU SET 14

This entry sets the default MD file number to 14.

LB 1 4; DR 5 1 1 1

This entry sets the loop bounds to frames 1-4 and defines dwell rates.

To execute these three command lines each time this menu is

displayed, enter:

I "IGU SET 1; MDU SET 14; LB 1 4; DR 5 1 1 1

**Old Format** 

columns 2-80

the McIDAS-OS2 commands to execute separated

by semicolons

#### 1

T defines the row and column where a string of text will begin, the text color and the text itself.

#### **Format**

T row column color "text

#### **Parameters**

rowscreen row number; the range is 0-21columnscreen column number; the range is 0-79colorcolor number; the range is 0-15 (see below)"texttext to display starting at row and column

#### Remarks

Row and column numbers are zero based, i.e., the upper-left corner of the screen is row 0, column 0. The McIDAS-OS2 color numbers are:

Number	Color	
0	blue	
olice feet to go	black	
2	green	
3	cyan	
4	red	
5 osoo folses	magenta	
6	brown	
7 111 1000	gray	
8	dark gray	
9	bright blue	
10	bright green	
11	bright cyan	
12	bright red	
13	bright magenta	
14	yellow	
15	white	

Text is displayed as it appears in columns 8-80. Leading blanks are significant; trailing blanks aren't. Leave at least 1 character between columns 8-80. Blank lines are not allowed. Don't use rows 23-24.

#### Example

#### T 13 21 15 'Radar Loop

This entry displays the words Radar Loop on row 13, starting in column 21, with white characters.

#### **Old Format**

columns 2-3	screen row number; the range is 0-21
columns 4-5	screen column number; the range is 0-79
columns 6-7	color number; the range is 0-15
columns 8-80	text to display starting at the specified row/column

F

F is a function key definition that defines a McIDAS-OS2 command or sequence of commands to execute when you press a specified function key.

Format:

F key "command

**Parameters** 

key
"command

function key number; the range is 0-12 McIDAS-OS2 commands to execute separated by

semicolons, or a string in the form @nnn (which

means switch to window nnn)

Remarks

A function key definition pertains only to a given menu. Since you can redefine function key F1 in each menu window, the commands that are executed by pressing F1 depend on the currently displayed window. For example, if you press F1 when window 7 is displayed, the commands executed are those defined for F1 in window 7.

You can use two digits for the function key number.

McIDAS-OS2 commands must start in column 4.

The function key zero (00) is a special case, and actually refers to the Esc key. Use it only when redefining the Main Menu number. The default for the "F0" or Esc key is zero. If it is not defined, menu zero is displayed when you press the Esc key.

**Examples** 

#### F 1 'DF 127 2 EC MSN

This entry executes the command DF 127 2 EC MSN when you press F1.

#### F 0 ''@15

This entry displays menu 15 when you press the Esc key. Define the F0 key in each menu, as the default is zero. Menu 0 is displayed unless F0 is explicitly defined in the currently displayed menu.

**Old Format** 

columns 2-3 columns 4-80

function key number; the range is 00-12

McIDAS-OS2 commands to execute separated by semicolons, or a string in the form @nnn (which

means switch to window nnn)

#### A

A is the Alt + Function key definition. It defines a McIDAS-OS2 command or sequence of commands to execute when you press a specified function key and the Alt key simultaneously.

**Format** 

A key "command

**Parameters** 

key

function key number; the range is 1-12

"command

McIDAS-OS2 commands to execute separated by

semicolons

Example

A 4 "ASK1 10 10 5 STATE "Enter state ID:

This entry executes the ASK1 command when you press the F4 and

Alt keys simultaneously.

**Old Format** 

columns 2-3

function key number; the range is 1-12

columns 4-80

McIDAS-OS2 commands to execute separated by

semicolons

C

C is the Ctrl + Function key definition. It defines a McIDAS-OS2 command or sequence of commands to execute when you press a specified function key while pressing the Ctrl key.

**Format** 

C key "command

**Parameters** 

key

function key number; the range is 1-12

"command

McIDAS-OS2 commands to execute separated by

semicolons

Example

C 5 ''@83

This entry displays menu 83 when you press the F5 and Ctrl keys

simultaneously.

**Old Format** 

columns 2-3

function key number; the range is 1-12

columns 4-80

McIDAS-OS2 commands to execute separated by

semicolons

S

S is the Shift + Function key definition. It defines a McIDAS-OS2 command or sequence of commands to execute when you press a specified function key while pressing the Shift key.

**Format** 

S key "command

**Parameters** 

key

function key number; the range is 1-12

"command McIDAS-OS2 commands to execute separated by

semicolons

Example

S 3 ".SF 4; MG CLE

This entry sends the SF and MG commands from McIDAS-OS2 to the mainframe when you press the F3 and Shift keys simultaneously.

**Old Format** 

columns 2-3

function key number; the range is 1-12

columns 4-80

McIDAS-OS2 commands to execute separated by

semicolons

Hall with A. C. F. I and S

U defines the values to poke into User Common whenever this menu is displayed.

**Format** 

U number value

**Parameters** 

number

User Common word number

value

value to poke

Remarks

The maximum number of U commands allowed per menu is 36.

Example

U 200 1

This entry pokes the value 1 into User Common word 200 and displays user interface window one. This command execution is preferred over the UCU POKE MCIDAS command since it is performed directly by the menu subsystem and is more efficient. See the User Common documentation before using this option.

**Old Format** 

columns 2-4

User Common word number

columns 5-7

value to poke

+

+ continues text from the previous line. Use it with A, C, F, I and S character lines.

**Format** 

+ "text

**Parameter** 

"text

the text continued from the previous line

Remarks

The continuation line (starting in column 2) is concatenated to the previous line, following the last non-blank character of that line.

Be careful with McIDAS-OS2 commands and parameters that require blank spaces. See the first and second examples below.

Each command line can have only one continuation line. If you need more, create an ASCII text file in the C:\MCIDAS\DATA subdirectory. Enter the desired McIDAS commands (one command per line of text) in this text file and append the extension .RUN to it. Then convert the ASCII text file to an LW file format using command DOSTOLW, which is documented in the Commands section of this manual. Use the McIDAS-OS2 RUN command in the menus to fetch the commands from this text file. See the third example below.

#### **Examples**

#### F 3 'LB 1 5; SEQ 105 120 1 5 EC

+ "cle

This entry generates the McIDAS-OS2 commands LB 1 5 and SEQ 105 120 1 5 ECcle, which is an error, since ECcle is not a legal value. Instead, enter:

#### F 3 'LB 1 5; SEQ 105 120 1 5 EC

+" cle

This entry places a space between "and cle. Consequently, it generates LB 1 5 and SEQ 105 120 1 5 EC cle as desired.

#### F 3 'RUN MYSTUFF

This entry prompts the text from file C:\MCIDAS\DATA\MYSTUFF to execute as a sequence of McIDAS-OS2 commands when you press the F3 key.

**Old Format** 

columns 2-80

text continued from the previous line

## **Pseudo and Other Special Commands**

#### **Pseudocommands**

There are seven F Key pseudocommands:

- @nnnn switches to menu nnnn. See the examples on pages 4-6, 4-7, 4-13, 4-15 and 4-16.
- \*Snn saves the current loop state (bounds, rates, etc.) under the interface nn. See the example on page 4-13.
- \*Rnn recalls the loop state nn. See the example on page 4-13.
- \*G eee zzz simultaneously enables graphics bit plane eee and erases bit plane zzz on WIDE WORD workstations. See the example on pages 4-15 and 4-16.
- \*T mmm performs an exclusive-OR logical operation on the bit plane enable mask for WIDE WORD workstations.
- @EXIT prompts McIDAS to perform an EXIT command. It removes all McIDAS-OS2 resident programs from memory and leaves you at the OS/2 session level. Use this command on rare occasions only.
- @RET invokes the previous menu. For example, if menu 1 switches to menu 4 using the @4 command, and menu 4 switches to menu 23 using @23, then performing an @RET pseudocommand in menu 23 invokes menu 4 just as if an @4 was done. Consequently, performing an @RET in menu 4 invokes menu 1, not menu 23.

The pseudocommand syntax allows multiple commands on a line separated by semicolons (;). There are two restrictions:

- · @ must always be the last pseudocommand on the line
- \* pseudocommands must always precede other "normal" McIDAS commands in the line; for example,
   F7 "\*S02; \*R27; DF 101 1 ED MSN; @09

#### **PSB Command**

Command PSB displays a PLEASE STAND BY message on the text window. It is useful when the system invokes a McIDAS command that takes a long time to run and does not give any apparent feedback. See the PSB command in the Commands section of this manual for more information.

## **Defining Loops**

Use the F Key Menu System to define a sequence of frames with their dwell rates as a loop. Then you can invoke that loop using a function key. Use command DR to set the dwell rates; use command LS or LB to define the loop bounds including graphics and dwell rates. Have available an F Key Menu that contains the internal instruction \*Snn for one of the keys. This saves the state of the workstation under the label nn. You can do this for up to 99 loops, although there are only 48 possible combinations of F Keys.

To quickly recall the loop, define an F Key with the internal command \*Rnn. The only restriction is \*R or \*S must be the first command on a line.

An example of a predefined loop is provided on the adjacent page.

#### Example

```
\mathbf{M} 0
U 208 0
T 2 20 7 "McIDAS Loop control
T 4 10 7 "F1 - Go to Loop #1
T 6 10 7 "F2 - Go to Loop #2
T 8 10 7 "F3 - Go to Loop #3
T 20 10 7 "Press 0 on numeric keypad to return to Command Mode
F 1 "*R01; @01
F 2 "*R02; @02
F 3 "*R03; @03
M 1
T 2 20 7 "Current Loop is #1
T 4 10 7 "F1 - SAVE current context as Loop #1
T 6 10 7 "F2 - Go to Loop #2
T 8 10 7 "F3 - Go to Loop #3
T 20 10 7 "Press 0 on numeric keypad to return to Command Mode
F 0 "@01
F 1 "*S01
F 2 "*R02; @02
F 3 "*R03; @03
M 2
T 2 20 7 "Current Loop is #2
T 4 10 7 "F1 - Go to Loop #1
T 6 10 7 "F2 - SAVE current context as Loop #2
T 8 10 7 "F3 - Go to Loop #3
T 20 10 7 "Press 0 on numeric keypad to return to Command Mode
F 0 "@02
F 1 "*R01; @01
F 2 "*S02
F 3 "*R03; @03
M 3
T 2 20 7 "Current Loop is #3
T 4 10 7 "F1 - Go to Loop #1
T 6 10 7 "F2 - Go to Loop #2
T 8 10 7 "F3 - SAVE current context as Loop #3
T 20 10 7 "Press 0 on numeric keypad to return to Command Mode
F 0 "@03
F 1 "*R01; @01
F 2 "*R02; @02
F 3 "*S03
```

Revised 9/91

## **Testing a Menu Template File**

After creating or modifying a Menu template, check the appearance of the menu windows and verify that the McIDAS-OS2 commands associated with the function and control key combinations work properly. Use the instructions below to perform these procedures.

After using the text editor, switch to McIDAS-OS2. Be sure the template file resides in the \MCIDAS\DATA subdirectory. Then, depending on whether you're using the old or new character format, enter one of the following commands.

Type: MAKMNU file TYPE=NEW

Press: Enter

or

Type: MAKMNU file TYPE=OLD

Press: Enter

The system recreates its menu file. When it's done,

Type: SHOMNU menu

Press: Enter

where *menu* is the menu number to debug. The system displays the menu on User Interface Window 9; it displays a list of Initialization commands, User Common pokes and F Key commands starting on window 8. You can also use windows 7, 6 and 5. To make quick changes, switch to the operating system editor (or a word processor) in another partition by pressing Alt+Esc.

You can hang the system while developing a menu. For instance, if menu zero locks the keyboard and an error is encountered such that you cannot select the option that unlocks it, you are hung. Use Alt+Esc to enter OS/2. Delete the file \MCIDAS\DATA\MENU which was created when you ran MAKMNU. If this file is present when booting, the system automatically goes into the menu mode. Therefore, you must delete this file before booting.

## Example

Below is an example using the new format. Commands are on the left; comments are on the right. Blank lines are not part of the file.

M 0

Defines menu zero.

F 0 "@01

The Esc key is aimed at menu 1.

T 00 00 07 "Esc to enter menu system

Defines the display for line zero, column zero, using color level 7.

U 208 1

Pokes User Common word 208 to a value of 1 and locks out the keyboard except for the F keys.

M 1

Defines menu 1.

T 2 10 14 "F1

Displays F1 on line 2, starting in column 10 in color level 14.

T 2 14 7 "Receive latest satellite image

Displays this message after the F1 above.

T 4 10 14 "F2

T 4 14 7 "Receive current MG

T 6 10 14 "F3

T 6 14 7 "See satellite image

T 8 10 14 "F4

T 8 14 7 "See MG

T 10 10 7 "F9 - Show special graphic

T 12 10 14 "F5

T 12 14 7 "Return to window 0

F 0 ''@01

Redefines the Esc key to go to menu 1.

F 1 ".SEQ 101 104 1 1 EC 43 89

Command for F1. The period (.) must be used to send the command to the host.

F 2 ".MG MSN

Command for F2

F 3 "@2

F 4 "@3

F 5 "@4

F3 takes you to menu 2, etc.

worldow gers to show littles

F 9 "*G 254 004	
U 51 2	Sets the graphics loop bounds 2-2; sets the current frame to 2.
U 52 2	
U 53 2	
M 2	Defines menu 2.
T 10 10 7 "Esc to return to menu	
U 51 1 U 52 1 U 53 1	Sets the graphics to frame 1.
U 200 -1	Shows the image
200 1	(EGA/VGA only).
	(Edity Varionity).
F 0 "@01	Redefines the Esc key to go
	to menu 1.
M 3	Defines menu 3.
mile	
T 10 10 7 "Esc to return to menu	
U 51 2 U 52 2	
U 53 2 U 200 -1	Shows the image
0 200 -1	(EGA/VGA only).
	(Lary variomy).
F 0 "@01	Redefines the Esc key to go
	to menu 1.
M 4	Defines menu 4, returning
	to the normal user interface.
'SEQ 101 104 1 1 EG 43 89 Com	IN.
U 200 0	Shows window zero.
U 201 57	Denote the test seister or
0 201 57	Resets the text pointer on window zero to show lines
U 208 0	Unlocks the keyboard to
	allow normal entries.

## **ASK User Interface**

#### Introduction

This section of the manual describes the ASK user interface. ASK solicits F Key Menu responses from the keyboard and stores them in a string table, allowing any McIDAS-OS2 command to fetch them. This is how it works. First, the function key invokes the ASK command. Then ASK reads a user created text file containing instructions similar in form to the menu instructions. ASK uses these instructions to manipulate text on the screen, describe attributes of the text, and solicit a response from the keyboard. Each response is stored in the string table under the string name specified on the instruction line in the text file.

Suppose you want to create a McIDAS-OS2 menu interface to list surface hourly (SAO) station data for several regions of the United States. One of the instruction lines displayed on the screen could ask what stations to list. The ASK program would wait for your response from the keyboard and store it in the string table. Other responses, such as the beginning and ending time periods to list, could also be solicited. The instruction line containing the McIDAS-OS2 command would fetch the appropriate string(s) from the string table just updated. The final instruction could be a McIDAS-OS2 command or string of commands that uses the information stored in the string table.

A command sequence is executed either synchronously or asynchronously. You can use multiple command instruction lines appearing anywhere in a sequence of instruction lines.

ASK uses window 8 as its display screen. It contains 25 rows (0-24) and 80 columns (0-79). When ASK completes execution, window 8 is erased.

Text output produced by a McIDAS command initiated during an ASK session defaults its text display to window zero unless otherwise specified by keyword TWIN. Appending TWIN to a McIDAS command line displays the text output on one of the five (0-4) text scrolling windows. For example, appending TWIN=3 directs text output to window 3.

Revised 9/90 5-1

## **Invoking ASK**

To invoke the ASK user interface, use the McIDAS-OS2 ASK command or press a predefined F key (function key). Both methods are described below.

#### **ASK Command**

To invoke the ASK user interface with the McIDAS-OS2 ASK command,

Type: ASK file Press: Enter

file is the name of the instruction text file. It cannot be more than 12 characters long and must be specified. There is no default.

The text file must reside in the \McIDAS\DATA subdirectory. Use the operating system editor or another word processor to create this ASCII text file. The file name must contain an .ASK extension. You don't have to type the extension when entering the ASK command as the program automatically appends it.

#### **Function Key**

You can also invoke the ASK user interface by pressing a predefined F key. If you need information about the F Key Menu System, see Chapter 4.

The example below shows three ASK command lines in a sample F Key Menu file.

F 1 "ASK LIST.ASK

F 2 "ASK CONTOUR.ASK

F 3 "ASK IMAGES.ASK

In this example, function keys F1 - F3 are used for a particular window in the menu. Pressing F1 invokes the ASK command, which reads its instructions from the text file LIST.ASK. LIST.ASK may contain instructions to solicit responses for the station and time periods for the listing. Other text files contour gridded data and display satellite images using F Keys 2 and 3.

## **Terminating ASK**

Press the Esc key to terminate ASK. The main menu window 9 is displayed.

## Creating an .ASK Text File

Because the ASK program reads the .ASK text file one line at a time, posted text and command line sequences must be less than 80 characters per line. Each line must end with a carriage return. Since each line contains an instruction for ASK to perform, the first character must be one of the instruction characters listed below.

Character	Instruction	
D	describes text attributes	
w	determines the exit window	
V h) square	determines the string table value substitution toggle	
P	posts a line of text on the screen	
R	posts text on the screen and waits for a response	
E	posts text, waits for a response and echoes the response	
В	blanks out a line or lines of text on the screen	
S	runs a command or sequence of commands synchronously	
A	runs a command or sequence of commands asynchronously	

The purpose, format and parameter definitions for each instruction character are described beginning on the next page.

Revised 9/90

D

D describes the text attributes.

**Format** 

D tcolor pcolor rcolor prow pcol "prompt

**Parameters** 

tcolor color of the posted text (default=11)
pcolor color of the prompt message (default=15)
rcolor color of the response text (default=14)

prow row to position the

row to position the prompt message; the first row is

numbered 0 (default=24)

pcol

column to position the prompt message; the first column

is numbered 0 (default=0)

"prompt text for the prompt message (default=ENTER:)

W

W determines the exit window.

Format

W window

**Parameter** 

window

window number to display after exiting ASK (default=the

window where ASK was initiated or previously set)

V

V toggles the string table value substitution.

**Format** 

V switch

on

Parameter

switch

turns string substitutions on (default)

OFF turns string substitutions off

Remarks

You can substitute values from the string table in a text string using a pound sign (#) followed by the string name. For example, #XYZ in a text string will be substituted with the value in the string table for string XYZ.

.....

#### P

P posts a line of text on the screen.

**Format** 

P trow tcol "text

**Parameters** 

trow screen row number for the text, rows 0-24 (no default)
tcol screen column number for the text, columns 0-79
(default=centers text on the screen)
"text character string to display on the screen

R

R posts text on the screen and waits for a response.

Format

R trow tool string "text

**Parameters** 

trow screen row number for the text, rows 0-24 (no default)
tcol screen column number for the text, columns 0-79
(default=centers text on the screen)
string string name to hold the response
"text character string to display on the screen

E

E posts text on the screen, waits for a response and echoes the response.

**Format** 

E trow tcol string rrow rcol "text

**Parameters** 

Revised 9/90

B

B blanks out rows of text on the screen.

**Format** 

B brow erow

**Parameters** 

brow erow beginning row to erase (no default) ending row to erase (default=brow)

S

S runs a command or sequence of commands synchronously.

**Format** 

S command

**Parameter** 

command a McIDAS command or sequence of commands separated by semicolons

A

A runs a command or sequence of commands asynchronously.

**Format** 

A command

**Parameter** 

command any McIDAS command or sequence of commands separated by semicolons

## **Manipulating Text**

Use the keys below to manipulate text on the response line.

Key	Function
Space bar or Alt + Backspace	spaces forward with erase
Backspace	backspaces with erase
Right tab	tabs right to a blank character
Left tab	tabs left to a blank character
End	sends the cursor to the end of the text without erasing
Ctrl+End	erases from the cursor to the end of the text
Home	sends the cursor to the start of the line without erasing
Delete	deletes a character
Insert	inserts text at the cursor (toggle)
Esc	quits the ASK session

Revised 9/90 5-7

## **Example**

The bolded lines below are an example of an .ASK file. Following them is an explanation of what each instruction line does.

D 10 12 14 20 30 "ENTER HERE:

W 3

P 3 "ASK INTERFACE SEQUENCE TO LIST SAO DATA

R 5 X ABC "ENTER STATION ID CURRENT ID= #ABC

B 5

E 5 DEF 7 "ENTER BEGINNING OBSERVATION HOUR TO BE LISTED

R 11 20 GHI "ENTER ENDING HOUR

S CLEAR 3

S SL #ABC #DEF #GHI TWIN=3

Instruction line 1 sets the text attributes. The colors of the posted text, prompt message and response are 10, 12 and 14, respectively. The prompt message ENTER HERE: begins on line 20, column 30.

Instruction line 2 sets window 3 to be displayed when you exit the ASK session.

Instruction line 3 posts and centers the text on screen line 3.

Instruction line 4 posts and centers the text on screen line 5. A response is requested and stored in string ABC. Because positional parameters may be defaulted using an X, the *tcol* positional parameter centers the text string on line 5. String name ABC appears in the text string. If the string table value substitution toggle (instruction character V) is ON, the value in string ABC appears on the screen. To choose the current value for the response, press Enter. If a string contains no associated value, it is left blank.

Instruction line 5 blanks out line 5 on the screen.

Instruction line 6 posts the text on screen line 5. The system requests a response and stores it in string DEF. The response is also echoed on screen line 7.

Instruction line 7 posts and centers the text on screen line 11, again beginning at column 20. The response is stored in string GHI.

Instruction line 8 sets a command line to run CLEAR (a synchronous McIDAS-OS2 command) to clear window 3.

Instruction line 9 runs the McIDAS-OS2 SL command to fetch the numbers stored in strings ABC, DEF and GHI. Since this command produces text output, TWIN=3 is appended to the command.

## **Soft Tablet Interface**

#### Introduction

This section of the manual describes the McIDAS-OS2 Soft Tablet interface. The Soft Tablet is a dynamic video interface that maps McIDAS commands to regions of the text screen. The workstation's VGA (Video Graphics Array) screen displays the tablets in color. Moving the mouse positions the cursor on the text screen. When you place the cursor over a region and press the mouse button, the system executes the commands associated with the region.

You define the appearance and functionality of a Soft Tablet by creating a template file containing specific ASCII text instructions. The tablet compiler program (TABLET) interprets these instructions using the template file as input, and creates a compressed format file. This compressed file contains a description of the appearance of the tablet screen as well as the sets of commands associated with regions of the screen.

Template files are standard ASCII text files; each line contains up to 80 characters and ends with a carriage return.

This section of the manual describes how to:

- create a Soft Tablet template file using specific character positions in the instruction lines
- · compile a Soft Tablet template file with the TABLET command
- employ the Soft Tablet using commands specifically designed for the Soft Tablet interface

Revised 2/92 6-1

## **Creating a Soft Tablet Template File**

#### **Instruction Characters**

A Soft Tablet template file contains ASCII text that the tablet compiler uses to define the appearance and function of the tablet. These instructions obey certain format rules. In particular, the instructions need specific character positions. The first character in any instruction defines the type of instruction as follows.

Character	Instruction
e propins of the second of the	I means initialization. It defines a McIDAS-OS2 command sequence to run when the tablet is initialized.
R	R means region. It defines the region of the text screen to be assigned a command sequence.
La office of a	L means label. It defines the label field where a string of text begins, the color and the text itself.
M	M means McIDAS. It defines the McIDAS-OS2 commands to execute when the region is selected.
t taxt files; er riaga robum.	+ means continuation. This character continues text from the previous line and is used with the M and I instruction characters only.

The tablet compiler interprets all other text in a template file as a comment line and ignores it. These instruction characters are further defined beginning on page 6-4. Each description includes a character definition, its format, parameter definitions, pertinent remarks and example.

#### Instruction Sequence

The sequence of instructions in the file is very important. To associate a set of McIDAS commands with a specific region, each region instruction must be immediately followed by the McIDAS commands associated with the region. Furthermore, initialization instructions must precede the first region instruction. Label instructions may appear in any order in the file. Finally, use a blank or comment line to terminate the file.

The format of a template file is:

# INITIALIZATION initialization instruction

#### **REGION 1**

region instruction label instructions (if desired) command instructions

#### **REGION 2**

region instruction label instructions (if desired) command instructions

#### **REGION 3**

region instruction label instructions (if desired) command instructions

#### **REGION N**

region instruction label instructions (if desired) command instructions

Revised 2/92

Defines a sequence of McIDAS-OS2 commands to be executed as part of the tablet initialization.

**Format** 

I command

**Parameter** 

command.

McIDAS-OS2 command to execute

Remarks

Initialization lines must precede the first REGION instruction. To continue the initialization line on the next line, use the + instruction.

Example

I TU REST WXTAB

This entry restores WXTAB as the current string table.

R

Defines a region of the text screen for a McIDAS-OS2 command sequence.

**Format** 

R ulrow ulcol lrrow lrcol rcolor

**Parameters** 

ulrow	region's upper-left row number; the range is 1-25
ulcol	upper-left column number; the range is 1-80
lrrow	lower-right row number; the range is 1-25
lrcol lower-right column number; the range is 1-80	
rcolor	region color number; the range is 0-7 (see below)

Remarks

The region instruction precedes the McIDAS commands associated with the region. The region color numbers in McIDAS-OS2 are:

Number	Color	Number	Color	
0	black	4	red	
1	blue	5	magenta	
2	green	6	brown	
3	cyan	7	gray	

Example

R 10 10 20 20 4

This entry defines a red region for rows 10 to 20 and columns 10 to 20.

### Defines the label field displayed on a tablet.

**Format** 

L row col tcolor blink "text"

**Parameters** 

row row number to start the text col column number to start the text

tcolor text color; the range is 0-7 (see the color table on the

adjacent page)

blink text blink (0=NO, 1=YES)

"text" text to be displayed; it must be enclosed in double quotes

Remarks

Label instructions can appear anywhere in a template file.

Example

L 15 12 15 0 "Label"

This entry places the word Label starting at line 15, column 12, in white.

## M

Defines the McIDAS-OS2 command to execute when you select a region.

**Format** 

M command

**Parameter** 

command

McIDAS-OS2 command to execute when you select the

region

Remarks

You can enter only one command per instruction. If necessary, extend

the command to the next line using the + instruction.

Example

M .SL WI TWIN=1

This entry executes a mainframe SL command and places the output

on window 1.

+

Continues text from the previous line.

**Format** 

+ command

**Parameter** 

command

continuation of an I or M instruction

Remarks

You can have only one continuation line per M or I instruction.

Example

M MENU 1 10 10 30 30 15 7 0 STN=MSN MKE LNR

+ EAU LSE DBQ DEN MIA "SELECT 1"

In this example, the MENU command sequence continues on the next

line in the template file.

You can only one community per instruction. If necessary

## Compiling a Soft Tablet Template File

Once you've created a template file, compile the instructions using the TABLET command. Be sure the \MCIDAS\TOOLS subdirectory is displayed on the screen as shown below.

[C:\MCIDAS\TOOLS]

Then,

Type: TABLET Press: Enter

The system displays the following prompt on the screen.

[C:\MCIDAS\TOOLS]

McIDAS Soft Menu Compiler Version 1.1

Enter Source File Name-

The tablet compiler waits for you to enter the name of the compiled tablet file with its appropriate path.

Type: \MCIDAS\WORKING\WXTAB.TXT

Press: Enter

The system displays the following prompt on the screen.

[C:\MCIDAS\TOOLS]

McIDAS Soft Menu Compiler Version 1.1

Enter Source File Name= \MCIDAS\WORKING\WXTAB.TXT Enter Destination File Name=

Specify the name for the output file. Do not include an extension. In this example,

Type: WX Press: Enter

The compiler creates the new file with the name specified for the output file and appends the extension .TAB.

The compiled file contains an internal description of the Soft Tablet screen appearance and linked lists of commands for each region defined in the template. The address of the first node of each list is located in a lookup table that matches each screen element to a region, if one exists for that screen element.

The internal representation of a compiled tablet file is as follows.

lute Word I	Description
e	definition of the tablet screen (2000 INTEGER $x$ 2); each word defines the character and attributes for each element on a 25 $x$ 80 character screen.
f e r	command lookup table (2000 INTEGER x 2); each word defines the byte address divided by four to the first command associated with the corresponding element on a 25 x 80 screen. If a screen element region is not defined (that is, the element is not part of a region) the lookup table entry is zero.
- xxxx i	nitialization commands; each command cell is 80 bytes (45 words) long.
	egion commands; each command cell is 180 bytes 45 words) long.
- xxxx ii 1	nitialization commands; each command cell 80 bytes (45 words) long. egion commands; each command cell is 180

Command cells have the following format.

Relative Word	Description link to the next command cell; 0=end cell	
1		
2	synchronous/asynchronous flag (currently not implemented	
3-5	command name plus .EXE	
6 - 45	command text; one command per cell	

If the compiling process is successful, the tablet file will appear in the McIDAS-OS2 data directory \MCIDAS\DATA.

## **Entering the Soft Tablet Interface**

Press: Alt S (hold down the Alt key and press the S key)

The current tablet name is read from User Common (where it is stored in words 90-92) and displayed on window 7. If User Common does <u>not</u> contain a tablet name, the interface prompts you for one. Enter the tablet name followed by a carriage return.

## Selecting a Region

After you activate the Soft Tablet interface, use the mouse to position the text cursor over the desired region. Press either mouse button to select the region. If the cursor is positioned over a region with a command set, the commands are executed asynchronously. The cursor is frozen on the screen while the system executes the command set. The numeric keypad and single-letter commands retain their normal functions in the Soft Tablet interface. The keypad selects text windows and switches from video to text on VGA workstations. The single-letter commands perform their normal functions.

Pressing the mouse button prompts a variety of results, depending on the workstation's text display when the mouse is pressed. If the tablet is visible and the cursor is positioned over a region, pressing the mouse executes the commands associated with the region. If the cursor is not positioned over a region, a no-op occurs. Pressing the mouse with a text or graphics/image frame on the screen redisplays the tablet and executes the command on which the cursor lies.

## **Exiting the Soft Tablet**

To exit the Soft Tablet,

Type: S

Press: Enter

or

Press: Alt S

### **Soft Tablet Commands**

The McIDAS-OS2 commands described on the next few pages are designed to enhance the Soft Tablet interface.

## CLOCK

Places the current time and/or date on the display screen.

**Format** 

CLOCK switch row col color bck blk nchr

**Parameters** 

switch ON displays the clock
OFF turns off the display
row row number of the clock display
col

col column number of the first character of the display

color text color level; the range is 0-15

bck background (window) color level; the range is 0-7

blk 0 no text blink 1 text blink

nchr number of characters to display (default=8 which causes

only the time to appear)

Remarks

The format of the clock display is HH:MM:SS dd mmm yy, where HH is the current hour, MM is the current minute, SS is the current second, dd is the current day, mmm is the 3-letter abbreviation for the month, and yy is the last two digits of the year.

The CLOCK function updates the display about once per second when the tablet is idle. During busy times, e.g., when programs are started, there will be longer delays in the updating of the screen display.

Example

CLOCK ON 10 6 15 7 0 5

This entry turns on the clock display and shows the first 5 characters (HH:MM) starting on row 10 and column 6 of the display. The time characters are white (15); the background is gray (7).

## **ECHO**

Echoes the values from the current string table to the Soft Tablet interface.

#### **Format**

ECHO name1=row col color bck blk nchr..namen=row col color bck blk nchr

#### **Parameters**

name	string table value to retrieve		
row	row number of the text		
col	column number of the text		
color	text color level; the range is 0-15 (see the color table below)		
bck	window color level; the range is 0-7 (see the color table on page 6-4)		
blk	0 no text blink 1 text blink		
nchr	number of text characters to display		

#### Remarks

This command displays the current value of a string table entry on a tablet.

The text color numbers defined by McIDAS-OS2 are:

Number	Color	
0	blue	
1	black	
2	green	
3	cyan	
4	red	
5	magenta	
6	brown	
7	gray	
8	dark gray	
9	bright blue	
10	bright green	
11	bright cyan	
12	bright red	2017-6-1
13	bright magenta	
14	yellow	
15	white	
•		

#### Example

#### ECHO STN=10 10 15 7 0 4

This entry echoes 4 characters of the STN string table entry to the current tablet.

## IF

### Conditionally tests a string table entry.

#### **Formats**

IF name=value "command

IF cond name, value "command

IF cond name, value THEN command command

#### **ENDIF**

IF cond name, value THEN command command

#### **ELSE**

command command

#### **ENDIF**

#### **Parameters**

cond condition to test

EQ equal NE not equal

LT less than (numerical strings only)
GT greater than (numerical strings only)
LE less than/equal (numerical strings only)
GE greater than/equal (numerical strings only)

name string table entry name

value value to test

command McIDAS command to execute if the condition is

satisfied

#### Remarks

The IF/THEN--ENDIF blocks may be nested up to 10 levels deep.

#### **Examples**

## IF STN=MSN "ECHO STN=10 10 10 13 15 7 0 4

This entry echoes the string to the tablet if the value for STN in the string table equals MSN.

#### IF NE STN,MSN 'PC L MSN

This entry tests if the string table entry for STN is not equal to MSN. If this is the case, the PC command is executed.

IF LT LOOP,10 THEN LA #LOOP TWIN=3 WINDOW 3

**ENDIF** 

This entry tests if the numerical value of the string table entry for LOOP is less than 10. If so, all commands in the block are executed.

IF EQ MAG,YES THEN
DF 101 1 EC MSN 2
ELSE

**DF 101 1 EC MSN** 

**ENDIF** 

This entry tests if the string table entry for MAG equals YES. If so, the first DF command is executed. If MAG is not equal to YES, the second DF command is executed.

Revised 2/92

## MENU

Transfers a selected option to the string table for later use in an M command.

#### **Format**

MENU num ulrow ulcol lrrow lrcol col bck blk name=mnu1..
mnun VAL=val1..valn "title

#### **Parameters**

num	number of menu items to select from the menu list
ulrow	upper-left row number of the menu box; the range is 1-25
ulcol	upper-left column number of the menu box; the range is 1-80
lrrow	lower-right row number of the menu box; the range is 1-25
lrcol	lower-right column number of the menu box; the range is 1-80
col	text color level; the range is 0-15 (see the table on page 6-11)
bck	window color level; the range is 0-7 (see the table on page 6-4)
blk	0 no text blink
	1 text blink
name	name of the string table entry to set
mnu1n	items displayed when the menu is visible; if the VAL
	keyword is not used, these values are placed in the
	string table; if VAL is specified, the listed values are
	aliases for the values listed by the VAL keyword
VAL=	values specified for alias menu items (optional)
val1 n	values placed in the string table if keyword VAL is used
"title	menu title (optional); quotes are mandatory

#### Remarks

If mnun=?, you can enter a value not specified in the menu item list. If you select this item, you must enter the value from the keyboard. See the example below.

If num=1 and mnu1=?, the system is in an automatic keyboard entry mode.

When you press a mouse button, the selected value is illustrated in the first column of the menu window containing the menu pointer.

If the menu item list is longer than the menu window, you can scroll the window by moving the mouse up and down. If you specify a title, the first row of the menu window is that title.

If num=1, the selected menu items blink until you select the values.

#### **Examples**

#### MENU 1 10 10 10 18 MAP=?

This entry prompts you to enter a value for MAP in the string table via the keyboard.

# MENU 1 10 10 20 15 14 3 0 STN=MSN BOS MKE DEN MIA? "STN

This entry allows you to select the value for STN from the menu list. The menu window is 10 rows (10-20) by 5 columns (10-15). The menu has yellow text on a cyan background with no text blink. You can specify an alternate value by selecting the? menu item.

# MENU 1 10 10 12 20 RAOBTIME=0GMT 12GMT VAL=0 12 "RAOB time

This entry displays a menu 3 rows by 10 columns with white text on a black background. The values in the menu have aliases.

### QUIT

Exits the Soft Tablet interface.

#### Format

QUIT

## STRING

Writes a value into the string table.

**Formats** 

STRING name "value STRING name value

STRING name UC=number type

**Parameters** 

name

name of the string to write into the current string table

value

value to write

number

index into User Common

type

I integer C character

Remarks

The STRING command is far more efficient than the TE command since the logic for STRING is built into S and does not require a program load for TE.

Use the first form of the STRING command for any strings that cannot be represented as a character positional parameter, such as one that contains blanks or has more than 12 characters. The second format is suitable for strings that are 12 or fewer characters and do not contain blanks. The third format allows values in User Common to be put into strings.

If the third format is used, the value to be written into the *name* is taken from the designated word *number* in User Common. Because all string values are character, use *type* to insure proper conversion.

**Examples** 

#### STRING CITY "CLE BOS MSN LAX

This entry writes the string CLE BOS MSN LAX into the string named CITY.

#### STRING CITY CLE

This entry writes the string CLE into the string named CITY.

#### STRING MDNUMB UC=5 I

This entry fetches the value from User Common word 5, which is the current default MD file number, treats it as type INTEGER and puts the value into the string named MDNUMB.

## **TABLET**

Restores a soft tablet as the current tablet.

**Format** 

TABLET tname

**Parameter** 

tname

name of the soft tablet

Example

TABLET WX.TAB

This entry restores tablet WX.TAB as the current tablet.

## **VIDEO**

Switches from a text display to an image/graphics display.

**Format** 

**VIDEO** 

Remarks

If you have a VGA display, switch to the video display and connect the cursor control.

If you have a tower workstation, connect the cursor control.

## **WINDOW**

Switches to a McIDAS-OS2 text window.

**Format** 

WINDOW window

**Parameter** 

window

window number to display on the next screen refresh

Example

WINDOW 8

This entry switches from the current text window to window 8.

## Example

Below is an example of a soft tablet. Commands are on the left; the purpose/function of the command is explained on the right.

L 1 35 17 0 "WX TABLET"

Defines the label at the top of

the screen.

L 16 8 2 0 "TIME AND DATE" I CLOCK ON 14 6 15 7 0 19 Labels and initializes a clock on

the tablet.

I STRING ID "MSN

I STRING IDNUM "72645

I STRING STATE "WI

Initializes some strings used in

the tablet.

I TU REST WXTAB

Restores the string table WXTAB

as the current string table.

L 18 6 2 0 "Current Station ID" I ECHO ID=20 12 8 1 1 3 Defines the label and initialization to display the current string for

the station identifier.

R 3 2 3 19 4

Defines the size and color for a

region.

L 3 6 15 0 "ASYNC"

Provides the label for the above

region.

M ,ATDT 36597

Defines the McIDAS command

for the region.

The following regions are similar in format:

R 3 22 3 39 4

L 3 28 15 0 "LOGON"

M WINDOW 0

M LOGON

This region logs you onto the mainframe (add your initials and

password).

R 3 42 3 59 4

L 3 48 15 0 "LOGOFF"

M .LOGOFF

M WINDOW 0

This region logs you off.

R 3 62 3 79 4

L 3 65 15 0 "EXIT TABLET"

M QUIT

This region quits the tablet.

R 5 2 11 19 3

L 8 5 14 0 "SURFACE PLOT"

M .EG

This regions plots a current map of a region chosen from a list or a new one typed in.

M GU REST GRAPHICS

M .TD ALL

M MENU 1 14 30 21 50 15 3 0

+ STATE=WI MID VT TX ? "STATES/REGIONS

M .SP PLOT #STATE

M VIDEO

R 5 22 11 39 3

This region plots a current Skew-

This region displays the terminal

forecast for a chosen station.

L 8 27 14 0 "SKEW-T" T of a chosen station.

M MENU 1 14 30 21 50 15 2 0

+ IDNUM=72645 72518 74494 ? "STATION ID NUMBER

M EG; GU REST GRAPHICS

M .SKEWT #IDNUM

M VIDEO

R 5 42 11 59 3

L 8 47 14 0 "TERMINAL"

L 9 47 14 0 "FORECAST"

M MENU 1 14 55 21 78 14 5 0

+ ID=MSN GRB MKE 9B2 ? "STATION ID

M .FT #ID TWIN=3

M WINDOW 3

R 5 62 11 79 3

This region plots a meteorogram

L 8 67 14 0 "METEOROGRAM" of a chosen station.

M MENU 1 14 55 21 78 14 5 0

+ ID=MSN GRB MKE 9B2 ? "STATION ID

M EG; GU REST GRAPHICS

M .MG #ID

M VIDEO

# Appendix A WWW Frame Allocation

This appendix explains how to allocate the image and graphics frames on your WIDE WORD Workstation (WWW). The number and size of the frames depend on the amount of memory in your WWW. You must know the number of memory boards in your WWW before proceeding with the steps below. To calculate the memory a set of frames requires, multiply the number of lines times the number of elements times the total number of frames (image and graphics). Frames of similar size can be grouped together or made opposites.

1. Run the SETUP program according to the instructions in the Installation Procedure chapter of this manual. The following text will appear on the screen:

#### McIDAS-OS2 System Setup

(Press ENTER to accept default values)

Select OS/2 version 1.1 / 1.2 environment:

- 1. McIDAS-OS2 and Presentation Manager but no DOS mode
- 2. DOS mode is required and system has at least 5MB of memory

Enter number (1 or 2) corresponding to configuration	1
Is the data connection Async, ProNET, or None (A/P/N)?	Α
Baud rate (1-1200, 2-2400, 3-4800, 4-9600)?	4
Communications port for data connection?	COM1
Printer interface (1-parallel, 2-serial)?	2
Port to use for printer connection	COM2
Type of display (0-Tower, 1-WWW, 2-EGA, 3-VGA)?	1
How many fixed-disks and partitions do you have total?	1
Would you like auto logon when host is contacted? (Y/N)	N
Hours to be added to system clock for GMT	5

2. Choose appropriate responses for your workstation and press Enter. If you press Enter without changing the value, the previous response is used. Since you are allocating frames for a WWW, select 1 for the type of display. The prompt below is displayed on the screen.

					1	1

Issued 9/90

3. If you choose N, the previous frame allocation is retained. If you choose Y, the following prompt is displayed.

Enter the correct number of sets; check with your technician for the number.

4. Below is an example of selecting new frame sizes. Each selection builds on the previous request. The table shows the amount of memory used by each request. To calculate the memory a set of frames requires, multiply the number of lines times the number of elements times the total number of frames (image and graphics).

Image Frames	<b>Graphics Frames</b>	Lines	Elements	Bytes
20	20	480	640	12288000
5	1	1500	3200	28800000
5	1 1 Med annual)	760	1280	5836800
10	1	600	1344	8870400

Look at the sample frame allocations below; the first one begins with no frames allocated.

Allocated 0 image and 0 graphics frames. Memory remaining: 6710886
# of image frames in this group (Press ENTER to end)? 20
# of graphics frames in this group?
Number of lines per frame?
Number of elements per line?

This group of frames has 20 image frames and 20 graphics frames. All frames are 480 lines by 640 elements which is the default. There is no default for the number of image frames and graphics frames, but WWW diagnostics require the first six frames to be 480 lines by 640 elements.

The above set of frames consumes 12288000 bytes ( $480 \times 640 \times 40$ ). The number of lines in a frame must be divisible by 4 and the number of elements by 32.

Allocated 20 image and 20 graphics frames. Memory remaining: 54820	864
# of image frames in this group (Press ENTER to end)? 5	
# of graphics frames in this group?	
Number of lines per frame?	00
Number of elements per line?	:00

This group of frames has 5 image frames and 1 graphics frame. All frames are 1500 lines by 3200 elements.

Allocated 25 image and 21 graphics fra	m	05	3.	M	er	nc	ory	/ r	er	na	air	nir	ıg:	2	260	20864
# of image frames in this group (Pre	SS	E	EN	IT	EI	7	to	ө	nc	1)?	>					5
# of graphics frames in this group?																1
Number of lines per frame?																760
Number of elements per line?																1280

This group of frames has 5 image frames and 1 graphics frame. All frames are 760 lines by 1280 elements.

Allocated 30 image and 22 graphics frames. Memory remaining: 2018	34064
# of image frames in this group (Press ENTER to end)?	10
# of graphics frames in this group?	1
Number of lines per frame?	300
Number of elements per line?	1344

This group of frames has 10 image frames and 1 graphics frame. All frames are 600 lines by 1344 elements.

5. If you do not want to assign more image and graphics frames for the last group, press Enter in response to the prompt below. By doing so, you will have more memory space left. To assign more image or graphics frames, go to number 7 on the next page.

Allocated 40 image and 23 graphics frames. Memory remaining: 11313664 # of image frames in this group (Press ENTER to end)? . . . .

Pressing Enter displays the following prompt on the screen.

Allocate the remaining memory for 40 TV-sized Image frames with imbedded graphics or just Graphics frames (I/G)? . . . . . I

Issued 9/90

6. Pressing G allocates the remaining memory to standard graphics frames.

Pressing I allocates the remaining memory to as many 480 by 640 image frames as possible. Frames in this group are called briefing frames on the WWW and are similar to VGA frames in that they combine images and graphics in one frame. Image levels 1-8 are converted to level 9 before being written in the WWW memory. Graphics written to these frames are written into levels 1-8. Level 0 and levels 9-255 are unchanged.

The summary of total images and graphics frames is shown below.

Total Image frames: 76 Graphics frames: 23

7. To assign more image or graphics frames instead of creating briefing frames, calculate the number of frames you could possibly allocate with the remaining memory and then answer the last group accordingly. For example:

This group of frames has 36 image frames and no graphics frames. All frames are 480 lines by 640 elements. Since this group uses all remaining memory, this is the last frame group setting.

The following text appears on the screen.

Total Image frames: 76 Graphics frames: 23

8. When the prompt below appears on the screen, reboot the system.

Press CTL+ALT+DEL to reboot system.

[C:\MCIDAS\TOOLS]

The example described above provides the WWW with 76 image frames and 23 graphics frames (assuming no briefing frames are allocated). The numbering sequence for the graphics frames is 1 to 20, 21, 26 and 31. You cannot access any graphics frames other than those specified above.

The image/graphics frame allocation is placed in a PC file called ALLOC.WWW. The first time a host command makes a reference to a frame, the host pulls this file from the PC with command SENLW. The name of the host file is WWSIZnnn, where nnn is the terminal index number of the workstation on the host. If you change the frame allocation by rerunning the SETUP program, delete this WWSIZnnn file from the host using command LWU DEL. If you don't delete the old WWSIZnnn file, the host and workstation will not agree on the size and numbers of frames. This prevents the WWW from loading images.

After you run SETUP to change the PC workstation configuration, log on to the host to make sure it acknowledges the change.

Issued 9/90

A-6

# Appendix B TrailBlazer Plus Modem

This appendix describes the line requirements and configurations for the TrailBlazer Plus modem manufactured by Telebit Corporation. The TrailBlazer Plus is capable of 19,200 bps operation, depending on line quality. The FCC registration number is ER95W5-16287-MD-E. For more information, see the *TrailBlazer Plus User's Manual*, Rev. A.

### Line Requirements

You can use the TrailBlazer Plus modem with either a dial-up or dedicated (i.e., leased or private) line. The TrailBlazer Plus has an asynchronous RS-232 interface which is used on both dedicated and dial-up lines. For dedicated line operation, the gain control resistor (R89) inside the TrailBlazer Plus must be changed to provide a 0 dBm transmit level. For a laboratory bench test of two TrailBlazer Plus modems in an end-to-end configuration, the value of R89 must provide a -9.0 dBm transmit level. See Appendix F (Leased Line Considerations) in the TrailBlazer Plus User's Manual, Rev. A, for information about dedicated operation.

#### Dial-up Line

The requirements for dial-up operation over the public switched network are:

- RJ-11C jacks installed at each modem location
- each jack/business line conditioned for touch tone or pulse operation

The ringer equivalence number is 0.4B.

#### **Dedicated Line**

The requirements for a dedicated line are:

- 2-wire dedicated land line
- full duplex
- C-1 conditioned, if available
- · RJ-11C jacks installed at each end

The transmit level is 0 dBm; the receive level is -16 dBm.

# TrailBlazer Plus Configurations for a McIDAS Workstation

The TrailBlazer Plus configuration depends on whether you have a dial-up or dedicated line and whether the modem is located at the IBM mainframe 3708 or the user workstation. The four configurations shown on the next few pages are:

- IBM mainframe 3708 dial-up operation
- IBM mainframe 3708 dedicated line operation
- workstation PC dial-up operation
- workstation PC dedicated line operation

SSEC uses the IBM mainframe 3708 dial-up configuration for the "Dial-Distribution" port.

#### **Command Settings**

The E and Q command settings vary among the configurations. The other command settings remain constant.

#### **Register Settings**

Use the command ATSN? to list the register settings and firmware revision level for the above configurations. If you have firmware revision level BA4.00, see figures 1, 3, 5 and 7 on the following pages. If you are using firmware version BA5.00, see figures 2, 4, 6 and 8. These settings were generated with an IBM PC using TrailBlazer Plus command ATSN?. If you enter this command at a McIDAS workstation, be sure to precede it with a comma.

For the IBM mainframe 3708 connections, S51 is set to 4 for an interface speed of 9600 baud. You can change this as needed for other interface speeds. For the PC configured modems, S51 is set to 255 which is the auto speed setting.

There are two registers that are not documented in the *TrailBlazer Manual* that you can set to improve performance. One is **ATS120=12** which eliminates micro packets. The other is **ATJ6S36=4** which adds a tone to the front of the packet. Each count represents 22 milliseconds (4 x 22=88 milliseconds total). Remember to save these and all register changes with the command **AT &W**.

Refer to the Telebit T2000 and TrailBlazer Plus Reference Manual, Rev. A, and the TrailBlazer Plus User's Manual for further information on register options, definitions and settings.

To use the SETUP feature that causes LOGON to send a modem command string, you must have the modem configured with the Verbose mode ON.

# Configuration for an IBM Mainframe 3708 Dial-up Operation

#### Version BA4.00

This is the configuration for a dial-up operation on the IBM mainframe 3708, using TrailBlazer Plus firmware version BA4.00.

```
ATSN?
E0 F1 M1 Q1 T V1 X1
                         Version BA4.00
S00=001 S01=000 S02=043 S03=013 S04=010 S05=008 S06=002 S07=040 S08=002 S09=006
S10=007 S11=070 S12=050
S45=000 S47=004 S48=001 S49=000
$50=000 $51=004 $52=001 $53=003 $54=000 $55=000 $56=017 $57=019 $58=003 $59=000
$60=000 $61=045 $62=003 $63=001 $64=001 $65=000 $66=001 $67=000 $68=003
S90=000 S91=000 S92=000 S95=000
S100=000 S101=000 S102=000 S104=000
S110=255 S111=255 S112=001
S121=000
NO:
N1:
N2:
N3:
N4:
N5:
N6:
N7:
N8:
N9:
OK
```

Figure 1. IBM Mainframe 3708 Dial-up Operation, Version BA4.00

Issued 9/90

#### Version BA5.00

Below is the configuration for a dial-up operation on the IBM mainframe 3708, using TrailBlazer Plus firmware version BA5.00. Note the difference between the equal sign (=) and colon (:) associated with each register setting. The equal sign signifies a factory default setting; the colon indicates a change from the factory default setting.

```
ATSN?
E0 F1 M1 Q0 T V1 W0 X1 Y0 &P0 &T4
                                         Version BA5.00
S00=001 S01=000 S02=043 S03=013 S04=010 S05=008 S06=002 S07=040 S08=002 S09=006
S10=007 S11=070 S12=050 S18=000 S25=005 S38=000
S41=000 S45=000 S47=004 S48: 001 S49=000
S50=000 S51:004 S52:001
                                $54=000 $55=000 $56=017 $57=019 $58=003 $59=000
S60=000 S61: 045 S62=003 S63=001 S64: 001 S65=000 S66: 001 S67=000 S68: 003 S69: 002
S90=000 S91=000 S92=000 S94=001 S95=000 S96:000
S100=000 S101=000 S102=000 S104=000 S105:000
S110=255 S111=255 S112=001
S121=000 S130:004 S131:001 S255:001
NO:
N1:
N2:
N3:
N4:
N5:
N6:
N7:
N8:
N9:
OK
```

Figure 2. IBM Mainframe 3708 Dial-up Operation, Version BA5.00

# Configuration for an IBM Mainframe 3708 Dedicated Line Operation

#### **Version BA4.00**

This is the configuration for a dedicated line operation on the IBM mainframe 3708, using TrailBlazer Plus firmware version BA4.00.

```
ATSN?
E0 F1 M1 Q1 T V1 X1
                          Version BA4.00
S00=000 S01=000 S02=043 S03=013 S04=010 S05=008 S06=002 S07=255 S08=002 S09=006
S10=255 S11=070 S12=050
S45=000 S47=004 S48=001 S49=000
S50=255 S51=004 S52=000 S53=001 S54=000 S55=000 S56=017 S57=019 S58=003 S59=000
S60-000 S61-045 S62-003 S63-001 S64-001 S65-000 S66-001 S67-000 S68-003
S90=000 S91=000 S92=000 S95=000
S100=000 S101=001 S102=000 S104=000
S110=255 S111=255 S112=001
S121=000
NO:
N1:
N2:
N3:
N4:
N5:
N6:
N7:
N8:
N9:
OK
```

Figure 3. IBM Mainframe 3708 Dedicated Line Operation, Version BA4.00

#### Version BA5.00

Below is the configuration for a dedicated line operation on the IBM mainframe 3708, using TrailBlazer Plus firmware version BA5.00. Note the difference between the equal sign (=) and colon (:) associated with each register setting. The equal sign signifies a factory default setting; the colon indicates a change from the factory default setting.

```
ATSN?
E0 F1 M1 Q0 T V1 W0 X1 Y0 &P0 &T4
                                          Version BA5.00
S00:000 S01=000 S02=043 S03=013 S04=010 S05=008 S06=002 S07:255 S08=002 S09=006
S10: 255 S11=070 S12=050 S18=000 S25=005 S38=000
S41=000 S45=000 S47=004 S48: 001 S49=000
S50: 255 S51: 004 S52=000
                                 S54=000 S55=000 S56=017 S57=019 S58=003 S59=000
S60-000 S61: 045 S62-003 S63-001 S64: 001 S65-000 S66: 001 S67-000 S68: 003 S69: 002
S90=000 S91=000 S92=000 S94=001 S95=000 S96:000
S100=000 S101:001 S102=000 S104=000 S105:000
S110=255 S111=255 S112=001
S121=000 S130=002 S131:001 S255:001
NO:
N1:
N2:
N3:
N4:
N5:
N6:
N7:
N8:
N9:
OK
```

Figure 4. IBM Mainframe 3708 Dedicated Line Operation, Version BA5.00

### Configuration for a PC Dial-up Operation

#### Version BA4.00

This is the configuration for a dial-up operation on the workstation PC, using TrailBlazer Plus firmware version BA4.00.

```
ATSN?
E1 F1 M1 Q0 T V1 X1
                         Version BA4.00
S00=000 S01=000 S02=043 S03=013 S04=010 S05=008 S06=002 S07=040 S08=002 S09=006
S10=007 S11=070 S12=050
S45=000 S47=004 S48=001 S49=000
S50=000 S51=255 S52=001 S53=003 S54=000 S55=000 S56=017 S57=019 S58=003 S59=000
S60=000 S61=045 S62=003 S63=001 S64=001 S65=000 S66=001 S67=000 S68=003
S90=000 S91=000 S92=000 S95=000
S100=000 S101=000 S102=000 S104=000
S110=255 S111=255 S112=001
S121=000
NO:
N1:
N2:
N3:
N4:
N5:
N6:
N7:
N8:
N9:
OK
```

Figure 5. PC Dial-up Line Operation, Version BA4.00

#### Version BA5.00

Below is the configuration for a dial-up operation on the workstation PC, using TrailBlazer Plus firmware version BA5.00. Note the difference between the equal sign (=) and colon (:) associated with each register setting. The equal sign signifies a factory default setting; the colon indicates a change from the factory default setting.

```
ATSN?
E1 F1 M1 Q0 T V1 W0 X1 Y0 &P0 &T4
                                          Version BA5.00
S00:000 S01=000 S02=043 S03=013 S04=010 S05=008 S06=002 S07=040 S08=002 S09=006
S10=007 S11=070 S12=050 S18=000 S25=005 S38=000
S41=000 S45=000 S47=004 S48:001 S49=000
                                $54=000 $55=000 $56=017 $57=019 $58=003 $59=000
S50=000 S51: 255 S52: 001
S60=000 S61: 045 S62=003 S63=001 S64: 001 S65=000 S66: 001 S67=000 S68: 003 S69: 002
S90=000 S91=000 S92=000 S94=001 S95=000 S96:000
S100=000 S101=000 S102=000 S104=000 S105:000
S110=255 S111=255 S112=001
S121=000 S130:004 S131:001 S255:001
NO:
N1:
N2:
N3:
N4:
N5:
N6:
N7:
N8:
N9:
OK
```

Figure 6. PC Workstation Dial-up Operation, Version BA5.00

### Configuration for a PC Dedicated Operation

#### **Version BA4.00**

This is the configuration for a dedicated operation on the workstation PC, using TrailBlazer Plus firmware version BA4.00.

```
ATSN?
E1 F1 M1 Q0 T V1 X1
                          Version BA4.00
S00-000 S01-000 S02-043 S03-013 S04-010 S05-008 S06-002 S07-255 S08-002 S09-006
S10=255 S11=070 S12=050
S45=000 S47=004 S48=001 S49=000
S50=255 S51=255 S52=000 S53=001 S54=000 S55=000 S56=017 S57=019 S58=003 S59=000
S60-000 S61-045 S62-003 S63-001 S64-001 S65-000 S66-001 S67-000 S68-003
S90=000 S91=000 S92=000 S95=000
S100=000 S101=002 S102=000 S104=000
S110=255 S111=255 S112=001
S121=000
NO:
N1:
N2:
N3:
N4:
N5:
N6:
N7:
N8:
N9:
OK
```

Figure 7. Workstation PC Dedicated Line Operation, Version BA4.00

#### Version BA5.00

Below is the configuration for a dedicated line operation on the workstation PC, using TrailBlazer Plus firmware version BA5.00. Note the difference between the equal sign (=) and colon (:) associated with each register setting. The equal sign signifies a factory default setting; the colon indicates a change from the factory default setting.

```
ATSN?
E1 F1 M1 Q0 T V1 W0 X1 Y0 &P0 &T4
                                          Version BA5.00
S00:000 S01=000 S02=043 S03=013 S04=010 S05=008 S06=002 S07:255 S08=002 S09=006
S10: 255 S11=070 S12=050 S18=000 S25=005 S38=000
S41=000 S45=000 S47=004 S48: 001 S49=000
S50: 255 S51: 255 S52=000
                                 S54=000 S55=000 S56=017 S57=019 S58=003 S59=000
S60=000 S61: 045 S62=003 S63=001 S64: 001 S65=000 S66: 001 S67=000 S68: 003 S69: 002
S90=000 S91=000 S92=000 S94=001 S95=000 S96:000
S100=000 S101:002 S102=000 S104=000 S105:000
S110=255 S111=255 S112=001
S121=000 S130=002 S131:001 S255:001
NO:
N1:
N2:
N3:
N4:
N5:
N6:
N7:
N8:
N9:
OK
```

Figure 8. PS/2 Workstation Dedicated Line Operation, Version BA5.00

# **Appendix C Asynchronous Communication**

This appendix provides the steps for establishing a McIDAS session with a host using asynchronous communication. It assumes you're using a TrailBlazer Plus modem manufactured by Telebit Corporation. You can use standard Hayes modems operating at lower baud rates, but they have a higher error frequency and slower data transfer. For information not covered here, see the *TrailBlazer Plus User's Manual*.

- 1. Connect your modem to the PC's serial port. If you're using a 25 to 9-pin adapter, be careful not to reverse the pin arrangement.
- 2. Configure your modem using the settings in Appendix B. The configuration must match these settings exactly, or the modem may not operate correctly with McIDAS-OS2. To modify the register and command settings, begin each request with a comma, e.g., AT.

In some cases a modem's initial settings are so incompatible with McIDAS that McIDAS cannot modify the settings. If this happens, change the settings using another software package, e.g., PROCOMM<sup>TM</sup>.

- 3. Run the SETUP program described in the Installation Procedure chapter of this manual. Define the appropriate data communications, serial port and printer port. If you're using the auto-connect feature, be sure to enter the entire modem command.
- 4. Toggle the modem power switch ON. The CTS and MR lights will illuminate. Start McIDAS-OS2. You will receive this asynchronous communication message (in magenta):

\*\*\* Async comm active on COM1 at 9600

The modem's DTR light will also illuminate. This means the workstation and serial port are connected and ready to transmit and receive data. To confirm this status,

Type: ,AT

The workstation will respond with the message below.

OK

 When you receive the OK message, enter a modem dial command or the LOGON command if you selected the auto-connect feature during SETUP. Modem commands from McIDAS-OS2 always begin with a comma. For example,

#### Type: ,ATDT9W6085551234

In this entry, the modem dials a number (608/555-1234) using tone dialing (DT9). It waits for an outside line (W) and then completes the dialing sequence. AT must precede all modem commands.

When the modem successfully contacts the mainframe, you will receive this message:

#### **CONNECT FAST**

If you receive the message

### **UNSUPPORTED FUNCTION**

after the CONNECT FAST statement, ignore it. The host (VTAM) generates this message because it is initially unaware that this is a McIDAS connection.

6. When you receive the CONNECT FAST message, log on to the host McIDAS. You may receive this message:

#### MCIDAS TERMINAL NOT LOGGED ON

Ignore it; try to log on again. Your second attempt should prove successful. This message, like the one above, is sent when the host is not expecting McIDAS. In either case, the auto-connect sequence activated by LOGON may fail and you must enter another LOGON command.

Note

If an alternate value of the XOFF character is required, place the decimal value into a file named \MCIDAS\DATA\XONXOFF.PTR as ASCII text. The normal value is 19.

#### Non-McIDAS Use

To send control characters or the modem escape sequence to the modem, use the McIDAS-OS2 CTRL command documented in the Commands section of this manual.

To use the modem for another purpose, such as using PROCOMM to connect with a data service, set User Common word 168 to one (1) with the McIDAS-OS2 UCU POKE command. After a few seconds, the modem's DTR light turns off indicating you can use the modem with other software. If you run this software in the DOS Compatibility Box, you may need to enter this DOS command.

Type: SETCOM40 COMx=ON

x is the port number the modem uses. McIDAS is still active and communicating. To reestablish control of the modem, check that the DTR light is not illuminated, then use the command UCU POKE to set word 168 back to zero. After a few seconds, the asynchronous communication message reappears.

The current status of the asynchronous communication is on window six. The data rate is updated after about 10K bytes of data is transferred.

Issued 9/90

To rend coptrol of arguests or the modern votage sequence to the modern, use the McIllAB-OSS CTR, command documented in the

To use the modem for another purp so, fuch as using PhOCOMM is comment with a case service, set I feet Common word 168 to one (1) with the McIDAS-ORS USU POLIS command. After a few reconds the modem's LTE light turns off indicating you can use the modem with diner achievance. If you rap the setware in the DOS Command. Commentationity Box, you may need to secure the POS command.

r is the post number the nuclear uses. Mc1DAS is still active and communicating. To resutabilish control of the modern, ensets that the DTS light is not illuminated, then use the constant UCU POME test word 168 back to zero. After a few seconds, the mynchronous

The current status of the saynch phone communication is on whichow

its. The data rate is undated after about 1000 proceed data is

# **Appendix D McIDAS-OS2 System Drivers**

This appendix provides a list of drivers used in the McIDAS-OS2 system. This information is useful if your site plans to install unique hardware on your workstations which have addresses or interrupt levels that interfere with those used by McIDAS-OS2.

#### **TVSYNC Drivers**

TVSYNC drivers coordinate the timing between the display head, i.e., either the tower or WIDE WORD workstation (WWW), and the computer. TVSYNC.SYS is the driver for PC/ATs; it uses Interrupt Request IRQ 15.

TVSYNC2.SYS is the driver for PS/2s. It also uses Interrupt Request IRQ 15. Since PS/2 interrupts are level rather than edge, it uses I/O location 334 to reset the level.

#### **Tower Driver**

Tower driving software is used with tower-based workstations only. The tower uses a memory interface starting at 0D0000.

#### **WWW Driver**

The WWW.SYS driver is for WIDE WORD workstations only. The WWW.SYS driver uses memory from C00000 to C1FFFF; it uses I/O locations 336, 338, 33a, 33c and 33e. You cannot have more than 12 megabytes of main memory in a computer driving a WWW because the system will see the WWW control memory as contiguous to the main memory and think it belongs to the system.

#### **ProNET Driver**

The ProNET driver is used for Proteon's ProNET communications. The PC/AT driver for ProNET is named PRONETA.SYS; it uses IRQ 9 and I/O ports starting at 0300. The PS/2 ProNET driver, PRONET.SYS, uses IRQ 5 and I/O locations starting at 10e0. SSEC ProNET drivers do not read the data from the PS/2 I/O configuration process, so you must manually assure that there are no memory, I/O or interrupt conflicts with other adapters.

#### **DRV** Driver

All configurations require a DRV.SYS driver which is the memory mapper.

#### **Removing Drivers**

You can remove unneeded drivers from your CONFIG.SYS file. WIDE WORD workstations need TVSYNC2.SYS and WWW.SYS. Tower workstations need TVSYNC.SYS or TVSYNC2.SYS. ProNET needs PRONET.SYS or PRONETA.SYS.

# **Appendix E Required System Files**

Listed below in alphabetical order are the required McIDAS-OS2 files in the \MCIDAS\DATA subdirectory and their functions.

File name	Function
ALLOC.WWW	allocation of frames and graphics for WWWs
AREAnnnn	area files, where nnnn is the area number
CONTEXT.SLT	LOOP management context file (DEFBRIEF, MOVIE, etc.)
DCISFC	MD file schema for ISFC data (ASCII format)
DCRAOB	MD file schema for RAOB data (ASCII format)
DCSVCA	MD file schema for SVCA data (ASCII format)
DNKEYS	list of MD file keys, field widths and units used by the system commands (ASCII format). LW file FLDWDTH is generated from this list.
EXPORT	text of F0-packets queued to go to the mainframe
FLDWDTH	LW file list of MD file keys and field widths for the MDL command
FRAMED	frame directory
FRAMENAV	frame navigation information
GRaannn	grid files where aa is either part of the grid file number or letters ID; nnnn is the grid file number.
GRAPHIC.ET	graphics palette for the GU command
HELP.DAT	list of documented commands on the McIDAS-OS2 system (ASCII format)
HOST.PTR	command to contact the host in the TCP or ASYNC domain

Issued 3/91

File name	Function
IDSVCA	surface station identifiers (binary format)
IMAGE.ET	image palette for the EU and GU commands
MDaannnn	MD files where $aa$ is either part of the MD file number or letters XX; $nnnn$ is the MD file number.
MENU	compiled menu file output from the MAKMNU command; delete this file to prevent McIDAS-OS2 from booting in the menu mode.
NUM.FRM	VGA frame allocation information
OFFSET.GMT	the offset in hours between local and GMT time
OUTLHPOL	world political boundary basemap (binary format)
OUTLHRES	North America high-resolution basemap (binary format)
OUTLSUPU	high resolution USA basemap
OUTLSUPW	world outline basemap (binary format)
OUTLUSAL	North America low-resolution basemap (binary format)
OUTLUSAM	North American medium-resolution basemap (binary format)
OUTLWRLD	world basemap (binary format)
*.PIC	VGA image files (UNIDATA version)
RADAR.ET	radar palette for the EU and GU commands
RAOBMASK	required for decoding RAOB MD files
RSIGMASK	required for decoding RAOB MD files
SKEDFILE	system scheduler file
STARTUP.SYS	list of McIDAS components to start for different communications or display configurations
STRTABLE	system string table files

File name	Function
SVCAMASK	required for decoding imported surface MD files
SYSIMAGE.VIF	used as a back store for images during DF on VGA displays
SYSKEY.DOC	system key table; ASCII representation for the SYSKEY.TAB file
SYSKEY.TAB	system key table derived from SYSKEY.DOC (binary format)
UNIDATA.MNU	sample F Key Menu template file (ASCII format)
VERSION.TXT	ASCII text for the current version of McIDAS-OS2
*.VFF	VGA image files (old version)
*.VIF	VGA image files saved with the SVF command
WINQUFIL	queueing file used for cloud drift wind processing with the mainframe
WWW.PAL	16-bit enhancement temporary storage
WX.TAB	sample tablet created from the WX.TXT file (binary format)
WX.TXT	sample Soft Tablet descriptor file and documentation (ASCII format)

Finance

Formused for decoding imported earlies MD flass

SYSHALE Under sea a lack store for images during OF on

VOA deeplays

SYSKEY LDOC

SYSKEY LAB file

SYSKEY LAB

Granty format)

UNIDATA AIMU

ASCH received from SYSKEY LDOC

Granty format)

VERSION TXT

VOA image files used with the SYF command

WINGER LAB

WINGER LAB

WERSION TXT

Setting file used for dead drift wind

WINGER LAB

Setting is talest content that WX TXT file

SETTING TORMAT

Setting is talest content file with the MX TXT file

Setting is talest content file with the main file

WX TAB

SETTING Tablet descriptor file and

# **Appendix F Exception Vector Assignments**

If you're running remotely or don't always monitor your machines, you may want to include the AUTOFAIL=YES statement in your CONFIG.SYS file. This will prevent interrupts of the entire computer when a problem occurs in some session (except for the DOS box).

TRAP	#	Туре	Description
0000	0	Divide Error	Division by zero was attempted.
0001	1	Debug Exception	Trap caused by single stepping or debug trap.
0002	2	Hardware Error	Probably a memory error.
0003	3	Breakpoint	A breakpoint instruction was executed; 0xCC is a single byte opcode used to trigger a breakpoint.
0004	4	Integer Overflow	Integer overflow exception caused when the OF overflow flag is set.
0005	5	Bounds Violation	Caused when the processor detects a bounds violation.
0006	6	Invalid Opcode	Processor attempted to execute an instruction which was not a valid value.
0007	7	Coprocessor Missing	An instruction was executed that required a numeric coprocessor which is not present in the current configuration.
0008	8	Double Fault	Caused by an interrupt occurring while an interrupt service routine or exception handler is currently being processed.
0009	9	Coprocessor Operand Segment Overrun	An operand for the numeric coprocessor crossed a segment boundary.

Segment the contents of the TSS register when performing a task switch segment loaded into memory (fix lock segment into memory).  Oooc 12 Segment loaded into stack overflow occurred or star pointer got corrupted.  Oood 13 General protection memory was accessed that was not owned by the process.	TRAP#		Туре	Description	
CS, DS, ES, FS, GS memory (fix lock segment into is not present memory).  O00c 12 Segment loaded into Stack overflow occurred or stars is not present pointer got corrupted.  O00d 13 General protection Memory was accessed that was violation not owned by the process.  O00e 14 Page fault Program attempted to access a page in violation of its access rights.  O010 16 Numeric Coprocessor An error was generated by the	000a	10 0122		The 80386 detected an error in the contents of the TSS register when performing a task switch.	
ss is not present pointer got corrupted.  Out 13 General protection Memory was accessed that was not owned by the process.  Out 14 Page fault Program attempted to access a page in violation of its access rights.  Out 16 Numeric Coprocessor An error was generated by the	000b	MATOT ni tnev	CS, DS, ES, FS, GS	memory (fix lock segment into	
violation not owned by the process.  Oooe 14 Page fault Program attempted to access a page in violation of its access rights.  Oo10 16 Numeric Coprocessor An error was generated by the	000c	12		Stack overflow occurred or stack pointer got corrupted.	
page in violation of its access rights.  Numeric Coprocessor An error was generated by the	000d	13	The state of the s	Memory was accessed that was not owned by the process.	
	000e	14	Page fault		
	0010	16	_		

# Appendix G File Redirection

File redirection is the relocating of a McIDAS file to any directory or subdirectory on any drive. You can redirect LW files, MD files, areas and grid files. For example, you can use file redirection to store areas, MD files and grid files in a subdirectory for a particular study. File redirection is also useful if you don't have much memory on your hard drive; you can use it to write and read files on the floppy disk drive.

#### Restrictions

Redirecting some system files will cause problems on your PC. Below is a list of files that should never be redirected.

ALLOC.WWW	NUM.FRM
CONTXT.SLT	REDIRECT
EXPORT	SKEDFILE
FRAMED	STARTUP.SYS
FRAMENAV	STRTABLE
HELP.DAT	SYSIMAGE.VIF
HOST.PTR	VERSION.TTT
MENU	WINQUFIL

## Creating a Redirection File

Redirection files can be created with a text editor or with command REDIRECT MAKE from McIDAS. The only difference is that REDIRECT MAKE does not allow you to enter comments. (For more information about the REDIRECT command, see the Commands section of this manual.) A redirection file may contain both paths and comments, where "path" refers to the OS/2 convention of paths, e.g., C:\JUNE\STORM\INNJ. To make a comment, type a double quote (") in the first character position, followed by the comment, e.g., "This is a comment.

To make a redirection path, type the file name you want redirected, followed by a space and the path to the file's destination. The maximum length is 32 characters, 12 for the file being redirected and 19 for the path itself, where the twentieth character can only be a backslash (\). Here is an example: filename.xxx x:\xxxxx\xxxxx\xxxxx\xxxxx

All redirection files must be stored in C:\MCIDAS\DATA as text files.

# Using a Text File Editor

Use the steps below to create a redirection file with a text file editor.

1. From a text file editor, enter these lines creating file EXAMPLE.EXA.

"REDIRECT MD FILE 1000 INTO A:\
MDXX1000 A:\
"REDIRECT AREAS 500-509 TO C:\JUNE\STORM\STUDY
AREA05\* C:\JUNE\STORM\STUDY
"REDIRECT GRID 5534 INTO C:\MCIDAS
GRID5534 C:\MCIDAS
"REDIRECT VIRTUAL FRAME FILE STORM INTO A:\STORM
STORM.VIF A:\STORM

- 2. Save the file in C:\MCIDAS\DATA.
- 3. Go back into McIDAS. Then restore the file you created into the dynamic memory (described below) and the file LWPATH.NAM.

Type: REDIRECT REST EXAMPLE.EXA

Press: Enter

# Using REDIRECT MAKE

The second way to create a redirection file is to use REDIRECT MAKE from McIDAS. Then use REDIRECT ADD to set up your file redirections. This example creates the same redirect file as above and saves the new entries. From McIDAS,

Type: REDIRECT MAKE

REDIRECT ADD MDXX1000 "A:\

REDIRECT ADD AREA05\* "C:\JUNE\STORM\STUDY

REDIRECT ADD GRID5534 "C:\MCIDAS REDIRECT ADD STORM.VIF "A:\STORM REDIRECT SAVE EXAMPLE.EXA

G-2

### Implementing a Redirection File

File redirection is stored in three places:

- · The test file you created.
- A file called LWPATH.NAM that holds the current file redirection (file direction in use). This file writes the file redirection into dynamic memory.
- The dynamic memory which is read by McIDAS to do the redirection.

Below is an example of a redirection file and how to get these redirections into memory.

1. This file (called RESEARCH.RED) redirects areas, MD files and enhancements. It was created in the editor.

"OK TORNADO 4/32/87 VISIBLE IMAGES
AREA939\* A:\OK\TORNADO\VIS
"OK TORNADO 4/23/87 IR IMAGES
AREA940\* A:\OK\TORNADO\IR
"OK TORNADO 4/23/87 SURFACE DATA
MDXX321\* A:\OK\TORNADO\SURF
"TX HURRICANE 8/23/85 VISIBLE IMAGES
AREA601\* C:\TX\HURRICANE\VIS
"TX HURRICANE 8/23/85 IR IMAGES
AREA939\* C:\TX\HURRICANE\IR
"TX HURRICANE 8/23/85 ENHANCEMENTS FOR VISIBLE
IMAGES
TXHUR.ENH C:\TX\HURRICANE\ENH

2. To install this file redirection, from McIDAS,

Type: REDIRECT REST RESEARCH.RED

Press: Enter

This entry writes the file RESEARCH.RED into both the dynamic memory and file LWPATH.NAM. To check that the correct file was put into dynamic memory, use REDIRECT LIST to list its contents. Now, any program using areas 9400-9409 will look for the data on the A: drive subdirectory \OK\TORNADO\IR.

If your workstation has multiple users, you may want to clear the dynamic memory and file LWPATH.NAM at the end of your workstation session. To do this,

Type: REDIRECT CLEAR

Press: Enter

Now another user will not use your redirections and McIDAS will use the default redirection of C:\MCIDAS\DATA.

# Appendix H McBASI Interpreter for McIDAS-OS2

This appendix contains an introduction to McBASI in McIDAS-OS2, a description of the McBASI interpreter commands and reserved words, and three McBASI sample programs.

#### Introduction

The name McBASI was first coined in 1985 on McIDAS-MVS to describe a line oriented editor and on-line BASIC language interpreter within the mainframe McIDAS environment. In McIDAS-OS2, only the interpreter (the RUN command) has survived.

McBASI programs are presented as ASCII text files created by either the OS/2 editor, or any other editor that stores text as ASCII text with a carriage return <cr> character at the end of each line.

Commands may be in uppercase or lowercase; line numbers are only needed on program lines that are referenced as targets of GOTO or GOSUB statements.

# McBASI Interpreter Commands and Reserved Words

Use the following McBASI interpreter commands and reserved words to create and run a McBASI program. They are listed alphabetically. Each description contains the command's function, syntax and one or more examples.

#### CLOSE

Frees the I/O table entry for the specified unit (LW file). A maximum of 10 files are active at once.

Syntax: CLOSE unit where unit is any valid numeric expression associated with an LW file by a previous OPEN command.

Example: CLOSE 10 where 10 is the *unit* number associated with an LW file by a prior OPEN command.

Issued 9/91

#### **GOSUB**

Changes the normal downward flow of control. This command is like GOTO, except control may be returned to the statement following the GOSUB by executing a RETURN statement.

GOSUB x Syntax: where x is any valid numeric expression.

**GOSUB 1000** Example:

100 REM Return Here

1000 PRINT B 1010 RETURN

In this example, control is returned to line 100.

Changes the downward, line-by-line flow of control.

Syntax: GOTO x

where x is any valid numeric expression.

Examples: GOTO 300 GOTO 13+6\*X

IF

Compares expressions, using relational operators, to determine whether to execute a statement, e.g., IF X+13>Y-9 GOTO 310. If several statements are used, either all are done (if the relationship is true) or none are done (if the relationship is false). To compare character strings, use only the = and <> relational operators. If statement is a let statement, i.e., a replacement statement, use the command LET.

Syntax: IF expr relop expr statement

where:

expr is any valid expression.

relop is any relational operator.

= means equal <> or >< means not equal

> means greater than

< means less than >= or => means greater than or equal to

<= or =< means less than or equal to statement is the step to be executed if the relationship

is true.

Example: IF X=8 LET Y=13:LET J=9:GOTO 890 In this example, if X=8 is true, both LET statements and the GOTO statement are executed.

#### **INPUT**

Allows data to be gathered from an LW file, a RUN statement, or the keyboard. The input statement for LW files is restricted; only one character variable may be designated in the list and the record from the file will be read into this variable. The syntax of this LW file input is shown below. This form of INPUT is useful for reading text files. Refer to the OPEN statement regarding fixed length and variable length records. The INPUT statement in this form handles both; the (r) record number is available for either format.

Syntax:

INPUT @u(r), A\$

where:

- u is a numeric expression for the unit number; @ is required.
- (r) is a numeric expression used to specify a record number; record numbers always begin with zero.

A\$ is the variable into which the record is read.

The syntax of the INPUT statement used to obtain values from the RUN statement is shown below.

Syntax: INPUT a,b,c where a,b,c are the variables.

Values are taken from the RUN command line as positional parameters of a normal McIDAS command. If the named variable is numeric, it is picked up as a number. If the variable is a character string, the value is picked up as a character parameter (up to 12 characters, no blanks). Each INPUT statement of this form picks up the next positional parameter. Thus, these statements are equivalent to the single INPUT statement above:

INPUT a

INPUT b

INPUT c

If the RUN command line contains a quoted string (for example, "THIS IS A QUOTED STRING), it may be read by using a character variable. The first character in the variable is a double quote (") to indicate it was picked up from the quoted string. An attempt to input a parameter which is not present results in either a numeric value of zero or a character string of length zero.

If the file OPENed is named "KBD\*", input may be obtained from the keyboard. Only one character variable may be used: INPUT A\$. See the LOCATE statement regarding cursor positioning and selecting alternate text windows.

Example: INPUT @3, A\$

IF MID\$(A\$,1,4)=EOF\$ GOTO xxx

This example tests for an end-of-file, using the pseudovariable EOF\$.

#### **KEYIN**

Submits a McIDAS command to be executed.

Syntax: KEYIN list

where *list* is zero or more expressions. Place a comma or semicolon between expressions. Commas tabulate to a print position (column) that is a multiple of 16. Semicolons allow no spaces to be inserted. Do not end the *list* with a semicolon or comma unless you don't want the statement to execute until you've entered another KEYIN statement that does not terminate with a semicolon.

Example: LET A\$="MSN"

LET T= 12.0

KEYIN "SL A ";

**KEYIN A\$**;

KEYIN " ";T

This example submits the following command: SL A MSN 12

LET

Creates a replacement statement in a McBASI program.

Syntax: LET var = expr

where: var

is a variable for numeric quantities; it is a single

letter or a single letter followed by a digit. Numeric variables are REAL\*4 quantities. For character strings, A\$ through Z\$ are available and

may contain up to 255 characters each.

expr is any valid numeric or character expression; numeric

expressions may contain the operators +,-,\*,/,\*\*, with normal precedence rules. For character or string expressions, expr may be a string variable, a string constant enclosed in quotes ("ABC"), a concatenation of two strings with the + operator, or a string function, e.g., pseudovariable TIME\$.

The hexadecimal constant \$nnnn is available, e.g., \$FE equals 254. A single array is also available; one thousand words are reserved and referenced by following a numeric variable name with a parenthetical expression. The value of this expression is added to the value of the variable to obtain an index into this array space.

Example: LET A=0

LET B=A(13) references the 13th word

LET C=10

LET B=C(13) references the 23rd word (10 + 13)

Do not mix numeric and character expressions. The VAL function converts character to numeric; STR\$ converts numeric to character. In most cases, the LET may be omitted.

#### LOCATE

Enables the use of text windows 5-9 for specifically tailored applications.

Syntax: LOCATE row, column, window, color, erasecolor

where: row is the text screen row for the next PRINT or

INPUT when using "KBD\*"; values are 0-24.

You must specify a value.

column is the column number; values are 0-79. You

must specify a value.

window is the text window that all subsequent output

should go to; values are 0-9. Specify this

parameter only if you want to change windows.

color is the text color value for subsequent output;

see the COLORS command for the list of color values. Specify this parameter only if you want

to change colors.

erasecolor if present, causes the named window (only 5-9)

to be erased to the color given. If you omit this

parameter, the window will not be erased.

You cannot omit a value unless it is the last one in the statement, e.g., LOCATE 5, 3,, 7 is not legal.

Example: LOCATE 5, 6, 7, 11, 2

PRINT "Please enter the value:"

OPEN "KBD\*", 10 INPUT @10, A\$

CLOSE 10

LOCATE 24, 0, 0

PRINT AS

This example prompts the input on window 7 and then prints the value back on window 0.

#### **OPEN**

Logically equates a *unit* number with the name of an LW file for INPUT and OUTPUT. When an OPEN statement is executed, the record pointers for input and output are set to point to the first record of the file (record zero). If these options are omitted from the INPUT or PRINT statements, the next record is used.

In order to solicit input from the user, a special file called "KBD\*" may be opened. Input from this file really obtains input from the user who must type it. See the INPUT statement.

Syntax:

OPEN filename, unit, reclength

where:

filename is a valid string expression, less than 13

characters.

unit

is any valid numeric expression.

reclength

is any valid numeric expression. It is only useful when dealing with old-style or otherwise fixed length text files. It must be specified if you want to randomly write (PRINT) data into a file; otherwise, writing is sequential. When dealing with old-style McIDAS text files, it

should be 80.

Example: OPEN "YYEXPLE",10

#### POKE

Forces a value into a User Common location.

#### Caution!

Be careful when using this command. It is possible to set your computer into a state from which the only recovery is to boot.

Syntax:

POKE value, location

where:

is a numeric or string expression. If numeric,

it's converted to an interger quantity unless a

string is specified.

location

value

is a numeric expression identifying which word

in User Common should be written into.

See also functions PEEK and PEEK\$.

#### **PRINT**

Displays command text on your CRT. When developing programs that generate commands, <u>use the PRINT statement for testing</u>. This allows you to see the would-be command text on your CRT. The PRINT statement is identical in structure to the KEYIN statement.

Syntax: PRINT list

where list is zero or more expressions. Place a comma or semicolon between expressions. Commas tabulate to a print position (column) that is a multiple of 16. Semicolons allow no spaces to be inserted. Do not end the *list* with a semicolon or comma unless you don't want the statement to execute until a future PRINT or KEYIN statement is executed.

Output may be directed to an LW file in either fixed length or variable length (text) format. This file-directed form of the PRINT statement has the following syntax.

Syntax:

PRINT @u(r), list

where:

- u is the numeric expression for the unit number; @ is required.
- r is a numeric expression used to specify the record number, which always begins with zero. Parentheses are required. This may only be specified for files with fixed length records (see the OPEN statement); variable length files are always sequentially written. If the r clause is omitted, the next record is assumed (record following the last one written). The comma is required and followed by a list of variables, constants, etc. If a PRINT statement ends with a semicolon or comma (meaning do not print this yet), the @u(r) clause is ignored.

Example: LET X=123

LET A\$= "MSN" LET T= 12.0

PRINT "this is a test";X;

KEYIN "SL A "; PRINT " of the ",

**KEYIN A\$**;

PRINT "print statement"

KEYIN " ":T

This example produces the following print line:

this is a test 123 of the

print statement

It also submits the following command: SL A MSN 12.

Example: PRINT @4,EOF\$

This is a final PRINT statement that outputs a logical end-of-file. Use it for a sequential file that will be read by another McIDAS program.

Example: LPRINT list

This entry sends output directly to the local printer

The question mark (?) may be used in place of the PRINT statement. For example, these two statements are equivalent:

? "A=";A

PRINT "A=";A

#### PTABLE

Places the value of *stringvalue* into the string table entry named *stringname*. See function TABLE\$.

Syntax: P

PTABLE stringvalue, stringname

where:

stringvalue

is the string expression to store.

stringname

is the name of the string to store the value in.

#### REM

Adds comments or inserts a help into your program. Remarks (REMs) do not affect the flow of the program.

Syntax:

REM comment

Examples: REM?

REM?

Use one of these examples to begin a help line. The normal McIDAS HELP facility can then be employed to list the help for this program.

#### **RETURN**

Returns from a subroutine call; also see GOSUB.

Syntax:

RETURN

#### RUN

Executes your McBASI program. The RUN statement can be abbreviated; see the examples below.

Syntax: RUN parameters FILE= CLEAR= VAR= where: parameters are the parameter values. FILE= runs a program from a different file. CLEAR= suppresses initialization of all variables; means the variables retain their previous values. VAR= specifies the variable's source. SHARE shares variables when one McBASI program RUNs another. specifies an LW file in which to store the variables (different from the default, which is assigned by terminal number).

Examples: RUN parameters FILE=xxxxxx 'xxxxxx parameters

where xxxxx is the file name (limited to 6 characters). These two RUN statements are interchangeable.

#### STOP

Stops your program; also stops by "falling off the end," completing the last line of a program. If you don't provide a quoted message, a line is displayed indicating the program line or statement number where the STOP occurred.

Syntax: STOP

STOP "Message"

## **Functions**

The following functions are available. x and y refer to numeric expressions; a\$ and b\$ refer to character expressions.

Function	Meaning
SIN(x), $COS(x)$	trigonometric functions; $x$ is an angle in radians;
TAN(x), $ASIN(y)$	the arc functions return values in radians
ACOS(y), $ATAN(y)$	
EXP(x)	exponential
LN(x)	natural logarithm
LOG(x)	base ten logarithm
ABS(x)	absolute value of $x$
INT(x)	integer part (truncated value) of $x$
NINT(x)	nearest integer value to x

Function	Meaning
MOD(x,y)	the remainder resulting from x/y
LEN(a\$)	length of the string in $a$ \$
INDEX(a\$,b\$)	location in $a$ \$ string of $b$ \$ substring; if $b$ \$ is not
	in $a$ \$, zero is returned
VAL(a\$)	numeric value of string $a$ \$
SQRT(x)	square root of $x$
STR\$(x)	calculates the string corresponding to the number x using McIDAS function CFG for the conversion
$\mathrm{MID}\$(a\$,x,y)$	extracts a string of length $y$ from $a$ \$, starting at character position $x$ (first position = 1)
TIME\$	a pseudostring variable of length 6 which has
	the current time in the format HH:MM:SS
DATE\$	a pseudostring variable of length 5 which has the current date in the format YYDDD
DAY\$	a pseudostring variable of length 6 which has the current date in the format YYMMDD
TFILE\$	a pseudostring variable of length 9; a temporary LW file named during execution of a BASIC
	program; it is deleted (via LWD) when the
EOE	program terminates
EOF\$	a pseudostring variable; contains the universal value Z80808080
PEEK(x)	returns a value from User Common (UC)
	location $x$ ; the value in UC is assumed integer
	and is converted to REAL*4
PEEK\$(x)	returns a character string
BIN(string\$)	the real number equivalent of the binary integer value in <i>string\$</i> ; assumes the first four bytes are an integer value (in binary)
CHR\$(x)	returns a string of length one which is equivalent to the ASCII code value x
KSYS(x)	returns the value from the System KeyTable location x; the value in SYSKEY is assumed to
KSYS\$(x)	be an integer and is converted to REAL*4 returns the value from the System KeyTable location x; the value in SYSKEY is assumed to
TABLE\$(a\$)	be a character string of length 4 returns the value of the string stored in the current string table under the name a\$

H-10

### McBASI Sample Programs

1. In this program, parameters are read from the RUN command until the list is exhausted. DEV=CNN suppresses the normal DONE message from YA. This sends the standard output to the CRT, but does not send the error or debug output. Use RUN MSN MKE CLE BOS DCA or RUN MEM ORD for this example. A step-by-step practice session with this example follows.

```
10 INPUT A$
IF LEN(A$) < 3 GOTO 100
KEYIN "YA SA ";A$;" DEV=CNN"
KEYIN "YA FT ";A$;" DEV=CNN"
GOTO 10
100 REM FINISHED...
```

2. This program illustrates a method of looping. The NINT function ensures that B will at some time be exactly equal to 101. No parameters are necessary in the RUN statement.

```
let a=0
let b=0
30 let a=a+b
let b=b+1
if nint(b)=101 goto 30
print a
```

3. In this example, the two character variables are read from the RUN statement. If they are identical, line 20 causes EQUAL to be displayed on the CRT and the program stops at line 100. If they are not equal, line 30 causes NOT EQUAL to be displayed, and lines 40 and 50 use the INDEX function to find out if one is a subset of the other. The semicolons between PRINT list items are omitted, as they are only required to prevent syntax ambiguities.

For example, RUN ABC ABC produces EQUAL on the CRT while RUN ABC DEFABCGHI produces NOT EQUAL plus BUT ABC IS WITHIN DEFABCGHI.

```
INPUT A$,B$
IF A$=B$ PRINT "EQUAL": GOTO 100
IF A$< >B$ PRINT "NOT EQUAL"
IF INDEX(A$,B$)< >0/ PRINT " BUT "B$" IS WITHIN "A$
IF INDEX(B$,A$)< >0/ PRINT " BUT "A$" IS WITHIN "B$

100 STOP
```

### McBASI Sample Programs

in this progests, purpositers are read from the RUN compand until the first is exhauster. DEACTIV suppresses the normal DONE mossage from Y.A. This sends the standard output to the CET, but does not send the error or debug output. Use VEIN MAIN MAIN SHILE CLE BOS DOA or RUN MI. S. ORD. Serials example. A step-by-stap practice sension with this exempt. More

10 JNPUTAS
IE LEN(AS) - 3 GGTO 100
KEYIN "YA SA ', AS" DEV-CHN"
KEYIN "YA FT ",AS" CEV-CHN"
COTO 10
REM FINISHED

E. This program illustrates a method of leading. The NAAT functions assumes that B will at some time be exactly equal to 101. No personal safe programs in the RUN statement.

30 tat a=0 (at a=a tal) (at b=a tal) (at b=a tal) (at atal) (b) = (al) gota (30)

In this example, the two character variables are read from the RUIV statement. If they are identical, line 10 causes EQUAL to be displayed on the CET and the program stope at line 100. If they are not equal, line 30 causes NOT EQUAL to be displayed, and lines 40 and 50 was the RVDEX function to find out if one is a subset of the other. The semicolous between PRINT list items are emitted, as that are only required to prevent a relax ambiguiries.

For example, BLCY ARC ALIG produces EQUAL on the CRT while BUTN ABC DRIVANCOIN produces NOT EQUAL plus BUT ABC IS WITCHIN DEPARCORE.

INPUT AULES
IF ASHEL PRINT "EQUAL", GOTO 100
IF ASH > BS PIGNT "NOT EQUAL"
IF INDEX(AS BS) - AV PRINT " BUT "BS" IS WITHIN "AS
IF INDEX(BS.AS) - AV, PRINT " BUT "AS" IS WITHIN "BS
TOP

# McIDAS-OS2 Users Guide Update

# September 1991

Chapter	Pages to Remove	Pages to Insert	Modifications
	Title page	Title page	Changed the revision date.
Table of Contents	i thru iv	i thru iv	Updated the Table of Contents.
Installation Procedure	1-1 thru 1-22	1-1 thru 1-20	Added two sections: Installing OS/2 Version 1.3 Extended Edition for TCP/IP, and Installing TCP/IP Version 1.1; updated the procedure for installing McIDAS-OS2 software; deleted all OS/2 V1.2 documentation.
Commands AA	3-9	3-9	Added a remark.
AAMAP	3-11	3-11	Updated the defaults for line and ele; documented the SPLINE= keyword.
CA thru ZM	3-17 thru 3-186	3-17 thru 3-210	Added 8 commands: CCODE, IMGPRO, ISENT, LWTODOS, MOVIT, SENAA, SU, SYSKEY; deleted TRANEU; updated the commands below:
		DEFLOOP DOSTOLW IGU LOGON MAKMNU PC SYSVAL XSECT ZA	Added parameters bloop and eloop. Added the R parameter; updated the remarks. Added the parameter maxgrd. Updated the password information. Deleted the type parameter; added the keywords INIT= and TYPE=. Deleted the G parameter and keyword. Updated the remarks. Updated the "text parameter and keywords LAT= and LON=. Added the keyword ENCL=.
F Key Menu System	4-14	4-14	Updated the command lines.
Soft Tablet Interface	6-9 thru 6-14	6-9 thru 6-18	Added commands CLOCK and STRING; updated the IF command.
Appendix G	G-1 thru G-4	G-1 thru G-4	Editorial changes.
Appendix H		H-1 thru H-12	New information.



# MolDAS-OS2 Users Guide Update

### September 1991

			A tided commands OLOOK and STELEO, updated the IF command.		
			Editorial abangen.		